

Environmental Protection Agency

Pt. 63, Subpt. MMM, Table 3

Emission source	Applicability	Requirement
Equipment leaks	Same criteria as for existing sources Total HAP load in wastewater POD streams $\geq 2,100$ Mg/yr.. Subpart H	Reduce concentration of total Table 9 compounds to <50 ppmw (or other options). 99% reduction of Table 9 compounds from all streams. Subpart H with minor changes, including monitoring frequencies consistent with the proposed CAR.
Product dryers and bag dumps.	Dryers used to dry PAI that is also a HAP, and bag dumps used to introduce feedstock that is a solid and a HAP.	Particulate matter concentration not to exceed 0.01 gr/dscf.
Heat exchange systems	Each heat exchange system used to cool process equipment in PAI manufacturing operations.	Monitoring and leak repair program as in HON.

^aTable 9 is listed in the appendix to subpart G of 40 CFR part 63.

TABLE 3 TO SUBPART MMM OF PART 63—MONITORING REQUIREMENTS FOR CONTROL DEVICES ^A

Control device	Monitoring equipment required	Parameters to be monitored	Frequency
All control devices	1. Flow indicator installed at all bypass lines to the atmosphere and equipped with continuous recorder or.	1. Presence of flow diverted from the control device to the atmosphere or.	Hourly records of whether the flow indicator was operating and whether a diversion was detected at any time during each hour.
Scrubber	2. Valves sealed closed with car-seal or lock-and-key configuration. Liquid flow rate or pressure drop mounting device. Also a pH monitor if the scrubber is used to control acid emissions..	2. Monthly inspections of sealed valves. 1. Liquid flow rate into or out of the scrubber or the pressure drop across the scrubber.. 2. pH of effluent scrubber liquid.	Monthly. 1. Every 15 minutes. 2. Once a day.
Thermal incinerator	Temperature monitoring device installed in firebox or in ductwork immediately downstream of firebox ^b .	Firebox temperature	Every 15 minutes.
Catalytic incinerator	Temperature monitoring device installed in gas stream immediately before and after catalyst bed.	Temperature difference across catalyst bed.	Every 15 minutes.
Flare	Heat sensing device installed at the pilot light.	Presence of a flame at the pilot light.	Every 15 minutes.
Boiler or process heater <44 megawatts and vent stream is not mixed with the primary fuel.	Temperature monitoring device installed in firebox ^b .	Combustion temperature	Every 15 minutes.
Condenser	Temperature monitoring device installed at condenser exit.	Condenser exit (product side) temperature.	Every 15 minutes.
Carbon adsorber (nonregenerative).	None	Operating time since last replacement.	N/A.
Carbon adsorber (regenerative).	Stream flow monitoring device, and. Carbon bed temperature monitoring device.	1. Total regeneration stream mass or volumetric flow during carbon bed regeneration cycle(s). 2. Temperature of carbon bed after regeneration. 3. Temperature of carbon bed within 15 minutes of completing any cooling cycle(s). 4. Operating time since end of last regeneration. 5. Check for bed poisoning	1. For each regeneration cycle, record the total regeneration stream mass or volumetric flow. 2. For each regeneration cycle, record the maximum carbon bed-temperature. 3. Within 15 minutes of completing any cooling cycle, record the carbon bed temperature. 4. Operating time to be based on worst-case conditions. 5. Yearly.

^a As an alternative to the monitoring requirements specified in this table, the owner or operator may use a CEM meeting the requirements of Performance Specifications 8 or 9 of appendix B of part 60 to monitor TOC every 15 minutes.

^b Monitor may be installed in the firebox or in the ductwork immediately downstream of the firebox before any substantial heat exchange is encountered.