

Environmental Protection Agency

§ 258.50

(3) The owner and/or operator may increase the moisture content of the waste mass in Phases IIIB and IVA by recirculating leachate and landfill gas condensate, and by adding storm water and groundwater, to the below grade portions of Phases IIIB and IVA.

(4) The owner and/or operator shall maintain less than a 30-cm depth of leachate on the liner.

(5) The owner and/or operator shall submit reports to the Director of the Waste Management Division at EPA Region 9 as specified in "Research, Development, and Demonstration Permit Application Salt River Landfill," dated September 24, 2007 and amended on April 8, 2008 including an annual report showing whether and to what extent the site is progressing in attaining project goals. The annual report will also include a summary of all monitoring and testing results, as specified in the application.

(6) The owner and/or operator may not operate the facility pursuant to the authority granted by this section if there is any deviation from the terms, conditions, and requirements of this section unless the operation of the facility will continue to conform to the standards set forth in §258.4 of this chapter and the owner and/or operator has obtained the prior written approval of the Director of the Waste Management Division at EPA Region 9 or his or her designee to implement corrective measures or otherwise operate the facility subject to such deviation. The Director of the Waste Management Division or designee shall provide an opportunity for the public to comment on any significant deviation prior to providing his or her written approval of the deviation.

(7) Paragraphs (a)(2), (3), (5), (6) and (9) of this section will terminate 36 months after date of publication in the FEDERAL REGISTER unless the Director of the Waste Management Division at EPA Region 9 or his or her designee renews this authority in writing. Any such renewal may extend the authority granted under paragraphs (a)(2), (3), (5), (6) and (9) of this section for up to an additional three years, and multiple renewals (up to a total of 12 years) may be provided. The Director of the Waste Management Division or designee shall

provide an opportunity for the public to comment on any renewal request prior to providing his or her written approval or disapproval of such request.

(8) In no event will the provisions of paragraphs (a)(2), (3), (5), (6) or (9) of this section remain in effect after 12 years after date of publication in the FEDERAL REGISTER. Upon termination of paragraphs (a)(2), (3), (5), (6) and (9) of this section, and except with respect to paragraphs (a)(1) and (4) of this section, the owner and/or operator shall return to compliance with the regulatory requirements which would have been in effect absent the flexibility provided through this site-specific rule.

(9) In seeking any renewal of the authority granted under or other requirements of paragraphs (a)(2), (3), (5) and (6) of this section, the owner and/or operator shall provide a detailed assessment of the project showing the status with respect to achieving project goals, a list of problems and status with respect to problem resolutions, and any other requirements that the Director of the Waste Management Division at EPA Region 9 or his or her designee has determined are necessary for the approval of any renewal and has communicated in writing to the owner and operator.

(10) The owner and/or operator's authority to operate the landfill in accordance with paragraphs (a)(2), (3), (5), (6) and (9) of this section shall terminate if the Director of the Waste Management Division at EPA Region 9 or his or her designee determines that the overall goals of the project are not being attained, including protection of human health or the environment. Any such determination shall be communicated in writing to the owner and operator.

(b) [Reserved]

[74 FR 11680, Mar. 19, 2009]

§§ 258.43–258.49 [Reserved]

Subpart E—Ground-Water Monitoring and Corrective Action

§ 258.50 Applicability.

(a) The requirements in this part apply to MSWLF units, except as provided in paragraph (b) of this section.

§ 258.50

40 CFR Ch. I (7-1-11 Edition)

(b) Ground-water monitoring requirements under § 258.51 through § 258.55 of this part may be suspended by the Director of an approved State for a MSWLF unit if the owner or operator can demonstrate that there is no potential for migration of hazardous constituents from that MSWLF unit to the uppermost aquifer (as defined in § 258.2) during the active life of the unit and the post-closure care period. This demonstration must be certified by a qualified ground-water scientist and approved by the Director of an approved State, and must be based upon:

(1) Site-specific field collected measurements, sampling, and analysis of physical, chemical, and biological processes affecting contaminant fate and transport, and

(2) Contaminant fate and transport predictions that maximize contaminant migration and consider impacts on human health and environment.

(c) Owners and operators of MSWLF units, except those meeting the conditions of § 258.1(f), must comply with the ground-water monitoring requirements of this part according to the following schedule unless an alternative schedule is specified under paragraph (d) of this section:

(1) Existing MSWLF units and lateral expansions less than one mile from a drinking water intake (surface or subsurface) must be in compliance with the ground-water monitoring requirements specified in §§ 258.51-258.55 by October 9, 1994;

(2) Existing MSWLF units and lateral expansions greater than one mile but less than two miles from a drinking water intake (surface or subsurface) must be in compliance with the ground-water monitoring requirements specified in §§ 258.51-258.55 by October 9, 1995;

(3) Existing MSWLF units and lateral expansions greater than two miles from a drinking water intake (surface or subsurface) must be in compliance with the ground-water monitoring requirements specified in §§ 258.51-258.55 by October 9, 1996.

(4) New MSWLF units must be in compliance with the ground-water monitoring requirements specified in §§ 258.51-258.55 before waste can be placed in the unit.

(d) The Director of an approved State may specify an alternative schedule for the owners or operators of existing MSWLF units and lateral expansions to comply with the ground-water monitoring requirements specified in §§ 258.51-258.55. This schedule must ensure that 50 percent of all existing MSWLF units are in compliance by October 9, 1994 and all existing MSWLF units are in compliance by October 9, 1996. In setting the compliance schedule, the Director of an approved State must consider potential risks posed by the unit to human health and the environment. The following factors should be considered in determining potential risk:

(1) Proximity of human and environmental receptors;

(2) Design of the MSWLF unit;

(3) Age of the MSWLF unit;

(4) The size of the MSWLF unit; and

(5) Types and quantities of wastes disposed including sewage sludge; and

(6) Resource value of the underlying aquifer, including:

(i) Current and future uses;

(ii) Proximity and withdrawal rate of users; and

(iii) Ground-water quality and quantity.

(e) Owners and operators of all MSWLF units that meet the conditions of § 258.1(f)(1) must comply with all applicable ground-water monitoring requirements of this part by October 9, 1997.

(f) Once established at a MSWLF unit, ground-water monitoring shall be conducted throughout the active life and post-closure care period of that MSWLF unit as specified in § 258.61.

(g) For the purposes of this subpart, a *qualified ground-water scientist* is a scientist or engineer who has received a baccalaureate or post-graduate degree in the natural sciences or engineering and has sufficient training and experience in groundwater hydrology and related fields as may be demonstrated by State registration, professional Certifications, or completion of accredited university programs that enable that individual to make sound professional judgements regarding ground-water monitoring, contaminant fate and transport, and corrective-action.

Environmental Protection Agency

§ 258.51

(h) The Director of an approved State may establish alternative schedules for demonstrating compliance with § 258.51(d)(2), pertaining to notification of placement of certification in operating record; § 258.54(c)(1), pertaining to notification that statistically significant increase (SSI) notice is in operating record; § 258.54(c) (2) and (3), pertaining to an assessment monitoring program; § 258.55(b), pertaining to sampling and analyzing appendix II constituents; § 258.55(d)(1), pertaining to placement of notice (appendix II constituents detected) in record and notification of notice in record; § 258.55(d)(2), pertaining to sampling for appendix I and II to this part; § 258.55(g), pertaining to notification (and placement of notice in record) of SSI above ground-water protection standard; §§ 258.55(g)(1)(iv) and 258.56(a), pertaining to assessment of corrective measures; § 258.57(a), pertaining to selection of remedy and notification of placement in record; § 258.58(c)(4), pertaining to notification of placement in record (alternative corrective action measures); and § 258.58(f), pertaining to notification of placement in record (certification of remedy completed).

[56 FR 51016, Oct. 9, 1991; 57 FR 28628, June 26, 1992, as amended at 58 FR 51547, Oct. 1, 1993; 60 FR 52342, Oct. 6, 1995]

§ 258.51 Ground-water monitoring systems.

(a) A ground-water monitoring system must be installed that consists of a sufficient number of wells, installed at appropriate locations and depths, to yield ground-water samples from the uppermost aquifer (as defined in § 258.2) that:

(1) Represent the quality of background ground water that has not been affected by leakage from a unit. A determination of background quality may include sampling of wells that are not hydraulically upgradient of the waste management area where:

(i) Hydrogeologic conditions do not allow the owner or operator to determine what wells are hydraulically upgradient; or

(ii) Sampling at other wells will provide an indication of background ground-water quality that is as representative or more representative

than that provided by the upgradient wells; and

(2) Represent the quality of ground water passing the relevant point of compliance specified by Director of an approved State under § 258.40(d) or at the waste management unit boundary in unapproved States. The down-gradient monitoring system must be installed at the relevant point of compliance specified by the Director of an approved State under § 258.40(d) or at the waste management unit boundary in unapproved States that ensures detection of ground-water contamination in the uppermost aquifer. When physical obstacles preclude installation of ground-water monitoring wells at the relevant point of compliance at existing units, the down-gradient monitoring system may be installed at the closest practicable distance hydraulically down-gradient from the relevant point of compliance specified by the Director of an approved State under § 258.40 that ensure detection of groundwater contamination in the uppermost aquifer.

(b) The Director of an approved State may approve a multiunit ground-water monitoring system instead of separate ground-water monitoring systems for each MSWLF unit when the facility has several units, provided the multiunit ground-water monitoring system meets the requirement of § 258.51(a) and will be as protective of human health and the environment as individual monitoring systems for each MSWLF unit, based on the following factors:

(1) Number, spacing, and orientation of the MSWLF units;

(2) Hydrogeologic setting;

(3) Site history;

(4) Engineering design of the MSWLF units, and

(5) Type of waste accepted at the MSWLF units.

(c) Monitoring wells must be cased in a manner that maintains the integrity of the monitoring well bore hole. This casing must be screened or perforated and packed with gravel or sand, where necessary, to enable collection of ground-water samples. The annular space (i.e., the space between the bore hole and well casing) above the sampling depth must be sealed to prevent