### § 420.53

#### SUBPART E

	BPT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSSpH	0.0156 (¹)	0.00521 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

# § 420.53 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

## SUBPART E

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
LeadZinc	0.0000939 0.000141	0.0000313 0.0000469

# § 420.54 New source performance standards (NSPS).

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the values set forth below.

#### SUBPART E

	New source performance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSSLead	0.00730 0.0000939 0.000141	0.00261 0.0000313 0.0000469

## SUBPART E—Continued

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 con- secutive days
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

# § 420.55 Pretreatment standards for existing sources (PSES).

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

#### SUBPART E

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
LeadZinc	0.0000939 0.000141	0.0000313 0.0000469

# § 420.56 Pretreatment standards for new sources (PSNS).

Any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources.

### SUBPART E

	Pretreatment standards for new sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb of product	
LeadZinc	0.0000939 0.000141	0.0000313 0.0000469