Environmental Protection Agency

SUBPART J

[PSES for secondary fiber non-deink facilities where molded products from wastepaper are produced without deinking]

| | Maximum for any 1 day | |
|---------------------------------|----------------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| Pentachlorophenol | (0.032)(21.1)y (0.010)(21.1)y | 0.0028 0.00088 |

^aThe following equivalent mass limitations are provided as guidance in cases when POTWs find it necessary to impose mass effluent limitations.

§ 430.107 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must: Comply with 40 CFR part 403; and

achieve the following pretreatment standards for new sources (PSNS) if it uses chlorophenolic-containing biocides. Permittees not using chlorophenolic-containing biocides must certify to the permit-issuing authority that they are not using these biocides:

SUBPART J [PSNS for secondary fiber non-deink facilities where paperboard from wastepaper is produced]

| | Maximum for any 1 day | |
|---------------------------------|----------------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| Pentachlorophenol | (0.072)(3.2)/y (0.023)(3.2)/y | 0.00096 0.00030 |

^a The following equivalent mass limitations are provided as guidance in cases when POTWs find it necessary to impose mass effluent limitations

SUBPART J

[PSNS for secondary fiber non-deink facilities where builders' paper and roofing felt from wastepaper are produced]

| | Maximum for any 1 day | |
|---------------------------------|-------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| Pentachlorophenol | | |

^aThe following equivalent mass limitations are provided as guidance in cases when POTWs find it necessary to impose mass effluent limitations.

SUBPART J

[PSNS for secondary fiber non-deink facilities where tissue from wastepaper is produced without deinking]

| | Maximum for any 1 day | |
|---------------------------------|------------------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| Pentachlorophenol | (0.049)(16.3)/y (0.015)(16.3)/y | 0.0034 0.0011 |

§430.110

SUBPART J—Continued

IPSNS for secondary fiber non-deink facilities where tissue from wastepaper is produced without deinking

| | Maximum for any 1 day | |
|---|-------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| y = wastewater discharged in kgal per ton of product. | | |

^a The following equivalent mass limitations are provided as guidance in cases when POTWs find it necessary to impose mass effluent limitations.

SUBPART J

[PSNS for secondary fiber non-deink facilities where molded products from wastepaper are produced without deinking]

| | Maximum for any 1 day | |
|---------------------------------|-------------------------|--|
| Pollutant or pollutant property | Milligrams/liter (mg/l) | Kg/kkg (or pounds per 1,000 lb) of product ^a |
| Pentachlorophenol | | |

^aThe following equivalent mass limitations are provided as guidance in cases when POTWs find it necessary to impose mass effluent limitations.

Subpart K—Fine and Lightweight Papers from Purchased Pulp Subcategory

§ 430.110 Applicability; description of the fine and lightweight papers from purchased pulp subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of: fine paper at nonintegrated mills; and lightweight paper at nonintegrated mills.

§ 430.111 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided in paragraphs (b) and (c) of this section, the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 and §430.01 of this part shall apply to this subpart.

(b) Cotton fiber furnish subdivision mills are those mills where significant quantities of cotton fibers (equal to or greater than 4 percent of the total product) are used in the production of fine papers.

(c) Wood fiber furnish subdivision mills are those mills where cotton fibers are not used in the production of fine papers.

§ 430.112 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT), except that non-continuous dischargers shall not be subject to the maximum day and average of 30 consecutive days limitations but shall be subject to annual average effluent limitations: