

**Environmental Protection Agency**

**§ 461.31**

(b) There shall be no discharge allowance for process wastewater pollutants from any battery manufacturing operation other than those battery manufacturing operations listed above.

**Subpart B—Calcium Subcategory**

**§ 461.20 Applicability; description of the calcium subcategory.**

This subpart applies to discharges to waters of the United States and introductions of pollutants into publicly owned treatment works from manufacturing calcium anode batteries.

**§§ 461.21–461.22 [Reserved]**

**§ 461.23 New source performance standards (NSPS).**

(a) The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

(b) There shall be no discharge for process wastewater pollutants from any battery manufacturing operations.

**§ 461.24 [Reserved]**

**§ 461.25 Pretreatment standards for new sources (PSNS).**

(a) Except as provided in § 403.7 any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the pretreatment standards for new sources listed below.

(b) There shall be no discharge for process wastewater pollutants from any battery manufacturing operations.

**Subpart C—Lead Subcategory**

**§ 461.30 Applicability; description of the lead subcategory.**

This subpart applies to discharges to waters of the United States and introduction of pollutants into publicly owned treatment works from the manufacturing of lead anode batteries.

**§ 461.31 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available:

(1) Subpart C—Closed Formation—Double Fill, or Fill and Dump.

**BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	0.86	0.45
Lead .....	0.19	0.090
Iron .....	0.54	0.27
Oil and grease .....	9.00	5.40
TSS .....	18.45	8.78
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(2) Subpart C—Open Formation—Dehydrated.

**BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	20.99	11.05
Lead .....	4.64	2.21
Iron .....	16.13	6.74
Oil and grease .....	221.00	132.60
TSS .....	453.05	215.47
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(3) Subpart C—Open Formation—Wet.

§ 461.31

40 CFR Ch. I (7-1-12 Edition)

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	0.10	0.05
Lead .....	0.02	0.01
Iron .....	0.06	0.03
Oil and grease .....	1.06	0.64
TSS .....	2.17	1.03
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(4) Subpart C—Plate Soak.

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	0.040	0.020
Lead .....	0.009	0.004
Iron .....	0.030	0.010
Oil and grease .....	0.420	0.250
TSS .....	0.860	0.410
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(5) Subpart C—Battery Wash (with Detergent).

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	1.71	0.90
Lead .....	0.38	0.18
Iron .....	1.08	0.55
Oil and grease .....	18.00	10.80
TSS .....	36.90	17.55
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(6) Subpart C—Battery Wash (Water Only).

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	1.12	0.59
Lead .....	0.25	0.12
Iron .....	0.71	0.36
Oil and grease .....	11.80	7.08
TSS .....	24.19	11.51
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(7) Subpart C—Direct Chill Lead Casting.

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	0.00040	0.00020
Lead .....	0.00008	0.00004
Iron .....	0.00020	0.00010
Oil and grease .....	0.00400	0.00200
TSS .....	0.00800	0.00300
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(8) Subpart C—Mold Release Formulation.

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		Metric units—mg/kg of lead used
Copper .....	0.011	0.006
Lead .....	0.002	0.001
Iron .....	0.007	0.004
Oil and grease .....	0.120	0.072
TSS .....	0.246	0.117
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(9) Subpart C—Truck Wash.

**Environmental Protection Agency**

**§ 461.32**

**BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead in trucked batteries	
	English units—pounds per 1,000,000 pounds of lead in trucked batteries	
Copper .....	0.026	0.014
Lead .....	0.005	0.002
Iron .....	0.016	0.008
Oil and grease .....	0.280	0.168
TSS .....	0.574	0.273
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

**(10) Subpart C—Laundry.**

**BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	0.21	0.11
Lead .....	0.05	0.02
Iron .....	0.13	0.07
Oil and grease .....	2.18	1.31
TSS .....	4.47	2.13
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

**(11) Subpart C—Miscellaneous Wastewater Streams.**

**BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	0.81	0.43
Lead .....	0.18	0.09
Iron .....	0.51	0.26
Oil and grease .....	8.54	5.12
TSS .....	17.51	8.33
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

**(b) There shall be no discharge allowance for process wastewater pollutants**

from any battery manufacturing operation other than those battery manufacturing operations listed above.

[49 FR 9134, Mar. 9, 1984; 49 FR 13879, Apr. 9, 1984]

**§ 461.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

**(1) Subpart C—Open Formation—Dehydrated.**

**BAT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	3.19	1.68
Lead .....	0.71	0.34
Iron .....	2.02	1.02

**(2) Subpart C—Open Formation—Wet.**

**BAT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of lead used	
	English units—pounds per 1,000,000 pounds of lead used	
Copper .....	0.100	0.053
Lead .....	0.022	0.010
Iron .....	0.06	0.03

**(3) Subpart C—Plate Soak.**