## **Environmental Protection Agency**

# § 461.3 Monitoring and reporting requirements.

The "monthly average" regulatory values shall be the basis for the monthly average discharge in direct discharge permits and for pretreatment standards. Compliance with the monthly discharge limit is required regardless of the number of samples analyzed and averaged.

### § 461.4 Compliance date for PSES.

The compliance date for pretreatment standards for existing sources is March 9, 1987.

# Subpart A—Cadmium Subcategory

# §461.10 Applicability; description of the cadmium subcategory.

This subpart applies to discharges to waters of the United States, and introductions of pollutants into publicly owned treatment works from the manufacturing of cadmium anode batteries.

# § 461.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available:

(1) Subpart A—Pasted and Pressed Powder Anodes.

#### **BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of cadmium	
	English units- 1,000,000 cadmium	—pounds per pounds of
Cadmium	0.92	0.41
Nickel	5.18	3.43
Zinc	3.94	1.65
Cobalt	0.57	0.24
Oil and grease	54.00	32.40
TSS	111.00	52.65
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(2) Subpart A—Electrodeposited Anodes.

### **BPT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of cadmium	
	English units- 1,000,000 cadmium	—pounds per pounds of
Cadmium	237.0 1,338.2	104.6 885.2
ZincCobalt	1,017.6	425.2 62.7
Oil and grease	13,940.0 28,577.0	8,364.0 13,592.0
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(3) Subpart A—Impregnated Anodes.

## BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/kg of cadmium	
	English units- 1,000,000 cadmium	
Cadmium	339.3	149.7
Nickel	1,916.2	1,267.5
Zinc	1,457.1	608.8
Cobalt	209.6	89.8
Oil and grease	19,960.0	11,976.0
TSS	40,918.0	19,461.0
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(4) Subpart A—Nickel Electrodeposited Cathodes.