

§ 463.35

40 CFR Ch. I (7–1–12 Edition)

SUBPART C
[Finishing water]

| Concentration used to calculate NSPS | | |
|--------------------------------------|------------------------------|------------------------------------|
| Pollutant or pollutant property | Maximum for any 1 day (mg/l) | Maximum for monthly average (mg/l) |
| TSS | 130 | 37 |
| pH | (¹) | (¹) |

¹ Within the range of 6.0 to 9.0 at all times.

The permit authority will obtain the average process water usage flow rate for the new source finishing water processes from the permittee.

§ 463.35 Pretreatment standards for existing sources.

(a) PSES for bis(2-ethylhexyl) phthalate, di-n-butyl phthalate, and dimethyl phthalate are reserved.

(b) Any existing source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403—General Pretreatment Regulations.

§ 463.36 Pretreatment standards for new sources.

(a) PSNS for bis(2-ethylhexyl) phthalate, di-n-butyl phthalate, and dimethyl phthalate are reserved.

(b) Any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403—General Pretreatment Regulations.

§ 463.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

PART 464—METAL MOLDING AND CASTING POINT SOURCE CATEGORY

GENERAL PROVISIONS

- Sec.
- 464.01 Applicability.
- 464.02 General definitions.
- 464.03 Monitoring and reporting requirements.
- 464.04 Compliance date for PSES.

Subpart A—Aluminum Casting Subcategory

- 464.10 Applicability; description of the aluminum casting subcategory.
- 464.11 Specialized definitions.
- 464.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 464.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 464.14 New source performance standards.
- 464.15 Pretreatment standards for existing sources.
- 464.16 Pretreatment standards for new sources.
- 464.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

Subpart B—Copper Casting Subcategory

- 464.20 Applicability; description of the copper casting subcategory.
- 464.21 Specialized definitions.
- 464.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 464.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 464.24 New source performance standards.
- 464.25 Pretreatment standards for existing sources.
- 464.26 Pretreatment standards for new sources.
- 464.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

Subpart C—Ferrous Casting Subcategory

- 464.30 Applicability; description of the ferrous casting subcategory.
- 464.31 Specialized definitions.
- 464.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 464.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best