

§ 133.110

46 CFR Ch. I (10–1–12 Edition)

(iii) On an OSV on a coastwise route, must be approved under approval series 160.051 or 160.151, with any approved equipment pack.

(2) Each rigid liferaft must be approved under approval series 160.118 and be equipped as specified in table 133.175 of this part.

(3) Each inflatable buoyant apparatus must be approved under approval series 160.010.

(4) Each lifefloat must be approved under approval series 160.027 and be equipped with the following:

(i) *One boathook.*

(ii) *Two paddles.* Each paddle must be at least 1.2 meters (4 feet) long and buoyant.

(iii) *One painter.* The painter must—

(A) Be at least 30 meters (100 feet) long, but not less than three times the distance between the deck where the lifefloats are stowed and to the OSV's waterline in the lightest seagoing condition;

(B) Have a breaking strength of at least 6.7 kiloNewtons (1,500 pounds-force), except that if the capacity of the lifefloat is 50 persons or more, the breaking strength must be at least 13.4 kiloNewtons (3,000 pounds-force);

(C) If made of a synthetic material, be dark in color or certified by the manufacturer to be resistant to deterioration from ultraviolet light;

(D) Be stowed in such a way that it runs out freely when the buoyant apparatus, inflatable buoyant apparatus, or lifefloat floats away from the sinking OSV; and

(E) Have a float-free link meeting the requirements of part 160, subpart 160.073 of this chapter, connecting the painter to the OSV.

(iv) *One self-igniting light.* The self-igniting light must be approved under approval series 161.010, and must be attached to the buoyant apparatus, inflatable buoyant apparatus, or lifefloat by a 12-thread manila or equivalent lanyard, at least 5.5 meters (18 feet) long. The self-igniting light is not required on a lifefloat with a capacity of 24 persons or less.

(5) Each marine evacuation system must be approved under approval series 160.175.

(6) Lifeboats may be substituted for liferafts. If lifeboats are installed on an

OSV, their installation and arrangement must meet the applicable requirements of subchapter W of this chapter.

(b) Except as provided in paragraph (c) of this section, OSVs must carry one or more liferafts with an aggregate capacity that will accommodate the total number of persons on board. The liferafts must be—

(1) Stowed in a position providing for easy side-to-side transfer at a single open deck level; or

(2) Additional liferafts must be provided to bring the total capacity available on each side to at least 100 percent of the total number of persons on board. If additional liferafts are provided and the rescue boat required under § 133.135 is also a lifeboat, it may be included in the aggregate capacity requirement.

(c) Each OSV operating in the Gulf of Mexico, as an alternative to the requirements of paragraph (b) of this section, may carry a sufficient number of inflatable buoyant apparatus or a sufficient number of lifefloats, having an aggregate capacity that, together with any lifeboats, rescue boats, and liferafts, will accommodate the total number of persons on board.

[CGD 84-069, 61 FR 25304, May 20, 1996; 61 FR 40281, Aug. 1, 1996]

§ 133.110 Survival craft muster and embarkation arrangements.

(a) Each OSV must have muster stations that—

(1) Are near the embarkation stations, unless the muster station is the embarkation station;

(2) Permit ready access for the offshore workers to the embarkation station, unless the muster station is the embarkation station; and

(3) Have sufficient room to marshal and instruct the offshore workers.

(b) Each muster station must have sufficient space to accommodate all persons assigned to muster at that station. One or more muster stations must be close to each embarkation station.

(c) Each muster station and embarkation station must be readily accessible to accommodation and work areas.

(d) Each muster station and embarkation station must be adequately illuminated by lighting supplied from the emergency source of electrical power.

(e) Each davit-launched survival craft muster station and embarkation station must be arranged to enable stretcher cases to be placed in the survival craft.

(f) Each launching station or each two adjacent launching stations with an embarkation position more than 3 meters (10 feet) above the waterline in the lightest seagoing condition, must have an embarkation ladder as follows:

(1) Each embarkation ladder must be approved under approval series 160.117 or approval series 160.017.

(2) Each embarkation ladder must extend in a single length, from the deck to the waterline in the lightest seagoing condition under unfavorable conditions of trim and with the OSV listed not less than 15 degrees either way.

(3) Each embarkation ladder may be replaced by a device approved to provide safe and rapid access to survival craft in the water, if the OCMI permits the device, provided that there is at least one embarkation ladder on each side of the OSV.

(g) Each davit-launched liferaft must be arranged to be boarded and launched from a position immediately adjacent to the stowed position or from a position to where, under §133.130, the liferaft is transferred before launching.

(h) If a davit-launched survival craft is embarked over the edge of the deck, the craft must be provided with a means for bringing it against the side of the OSV and holding it alongside the OSV to allow persons to safely embark.

(i) If a davit-launched survival craft or rescue boat is not intended to be moved to the stowed position with persons on board, the craft must be provided with a means for bringing it against the side of the OSV and holding it alongside the OSV to allow persons to safely disembark after a drill.

§ 133.120 Launching stations.

(a) Each launching station must be positioned to ensure safe launching with clearance from—

- (1) The propeller; and
- (2) The steeply overhanging portions of the hull.

(b) Each survival craft must be launched down the straight side of the OSV.

(c) Each launching station in the forward part of the OSV must—

- (1) Be located aft of the collision bulkhead in a sheltered position; and
- (2) Have a launching appliance approved as being of sufficient strength for forward installation.

[CGD 84-069, 61 FR 25304, May 20, 1996; 61 FR 40281, Aug. 1, 1996]

§ 133.130 Stowage of survival craft.

(a) *General.* Each survival craft must be stowed as follows:

(1) Each survival craft must be as close to the accommodation and service spaces as possible.

(2) Each survival craft must be stowed in a way that neither the survival craft nor its stowage arrangements will interfere with the embarkation and operation of any other survival craft or rescue boat at any other launching station.

(3) Each survival craft must be as near the water surface as is safe and practicable.

(4) Other than liferafts intended for throw-overboard launching, each survival craft must be not less than 2 meters above the waterline with the OSV—

- (i) In the fully loaded condition;
- (ii) Under unfavorable conditions of trim; and

(iii) Listed up to 20 degrees either way, or to the angle where the OSV's weatherdeck edge becomes submerged, whichever is less.

(5) Each survival craft must be sufficiently ready for use so that two crew members can complete preparations for embarkation and launching in less than 5 minutes.

(6) Each survival craft must be fully equipped as required under this part.

(7) Each survival craft must be in a secure and sheltered position and protected from damage by fire and explosion, as far as practicable.

(8) Each survival craft must not require lifting from its stowed position in order to launch, except that—

- (i) A davit-launched liferaft may be lifted by a manually powered winch from its stowed position to its embarkation position; or