

## Coast Guard, DHS

## § 97.19-1

sealed and suitably labeled at the time the supply is received on board, a half-pint sample of each lot of fuel oil. These samples shall be preserved until the particular supply of oil is exhausted.

[CGFR 65-50, 30 FR 17011, Dec. 30, 1965, as amended by CGFR 68-82, 33 FR 18901, Dec. 18, 1968; USCG-2000-7790, 65 FR 58461, Sept. 29, 2000]

### § 97.15-60 Firefighting equipment, general.

(a) It shall be the duty of the owner, master, or person in charge to see that the vessel's firefighting equipment is at all times ready for use and that all such equipment required by the regulations in this subchapter is provided, maintained, and replaced as indicated.

(b) It shall be the duty of the owner, master, or person in charge to require and have performed at least once in every twelve months the tests and inspections of all hand portable fire extinguishers, semiportable fire extinguishing systems, and fixed fire extinguishing systems on board, as described in Tables 91.25-20(a)(1) and 91.25-20(a)(2) in § 91.25-20 of this subchapter. The owner, master, or person in charge shall keep records of such tests and inspections showing the dates when performed, the number and/or other identification of each unit tested and inspected, and the name(s) of the person(s) and/or company conducting the tests and inspections. Such records shall be made available to the inspector upon request and shall be kept for the period of validity of the vessel's current certificate of inspection. Where practicable these records should be kept in or with the vessel's log book. The conduct of these tests and inspections does not relieve the owner, master, or person in charge of his responsibility to maintain this firefighting equipment in proper condition at all times.

### § 97.15-75 Test of inflatable hopper gate seals on Great Lakes bulk dry cargo vessels.

(a) It is the duty of the Master to ensure that the inflatable hopper gate seals installed on vessels required to meet the damage stability requirements of subpart H of part 172 of this

chapter are tested after each carriage of cargo.

(b) Where inflatable hopper gate seals are installed, the test must consist of inflating the seals and assuring they hold the design pressure for at least 15 minutes without a drop in pressure.

(c) The date of the test and the condition of the equipment must be noted in the vessel's official logbook.

[CGD 80-159, 51 FR 33059, Sept. 18, 1986]

## Subpart 97.16—Auto Pilot

### § 97.16-1 Use of auto pilot.

Except as provided in 33 CFR 164.15, when the automatic pilot is used in—

(a) Areas of high traffic density;

(b) Conditions of restricted visibility; and

(c) All other hazardous navigational situations, the master shall ensure that—

(1) It is possible to immediately establish manual control of the ship's steering;

(2) A competent person is ready at all times to take over steering control;

(3) The changeover from automatic to manual steering and vice versa is made by, or under, the supervision of the officer of the watch.

[CGD 75-074, 42 FR 5964, Jan. 31, 1977]

## Subpart 97.19—Maneuvering Characteristics

### § 97.19-1 Data required.

For each ocean and coastwise vessel of 1,600 gross tons or over, the following apply:

(a) The following maneuvering information must be prominently displayed in the pilothouse on a fact sheet:

(1) For full and half speed, a turning circle diagram to port and starboard that shows the time and the distance of advance and transfer required to alter the course 90 degrees with maximum rudder angle and constant power settings.

(2) The time and distance to stop the vessel from full and half speed while maintaining approximately the initial heading with minimum application of rudder.

(3) For each vessel with a fixed propeller, a table of shaft revolutions per