Coast Guard, DHS § 160.054–4

- (1) Plans and specifications containing the information required by \$159.005-12 of this chapter, including drawings, product description, construction specifications, and bill of materials.
- (2) The information specified in $\S159.005-5(a)(2)$ (i) through (iii) of this chapter, except that, if preapproval review has been waived, the manufacturer is not required to send a prototype work vest sample to the Commandant.
- (3) Performance testing results of the design performed by an independent laboratory, that has a Memorandum of Understanding with the Coast Guard under \$159.010–7 of this subchapter covering the in-water testing of personal flotation devices, showing equivalence to the standard design's performance in all material respects.
- (4) Any special purpose(s) for which the work vest is designed and the vessel(s) or vessel type(s) on which its use is intended.
- (5) Buoyancy and other relevant tolerances to be complied with during production.
- (6) The text of any optional marking to be included on the work vest in addition to the markings required by §160.053.

[CGD 95-028, 62 FR 51215, Sept. 30, 1997]

Subpart 160.054—Kits, First-Aid, for Inflatable Liferafts

SOURCE: CGFR 60–36, 25 FR 10637, Nov. 5, 1960, unless otherwise noted.

§ 160.054-1 Applicable specification.

- (a) Specification. The following specification of the issue in effect on the date first aid kits are manufactured forms a part of this subpart:
- (1) Coast Guard specification 160.041—Kits, First-Aid.
 - (2) [Reserved]
- (b) Copies on file. Copies of the specification regulations referred to in this

section shall be kept on file by the manufacturer, together with the approved plans and certificate of approval. They shall be kept for a period consisting of the duration of approval and 6 months after termination of approval. The Coast Guard specification may be obtained from the Commandant (CG-ENG), U.S. Coast Guard,2100 2nd St., SW., Stop 7126, Washington, DC 20593-7126.

[CGFR 60-36, 25 FR 10637, Nov. 5, 1960, as amended by CGFR 65-16, 30 FR 10899, Aug. 21, 1965; CGD 88-070, 53 FR 34536, Sept. 7, 1988; CGD 95-072, 60 FR 50467, Sept. 29, 1995; CGD 96-041, 61 FR 50733, Sept. 27, 1996; USCG-2009-0702, 74 FR 49237, Sept. 25, 2009]

§ 160.054-2 Type and size.

- (a) *Type*. First-aid kits covered by this specification shall be of the water-tight type. Alternate arrangements of materials meeting the performance requirements of this specification will be given special consideration.
- (b) Size. First-aid kits shall be of a size adequate for packing 12 standard single cartons of the kind indicated in specification subpart 160.041.

§ 160.054-3 Construction.

- (a) Construction. The container shall be constructed of tough transparent material, not less than .008 inch nominal thickness, properly sealed around three edges, and having the fourth edge closed in such manner that it is capable of being opened and reclosed wateright. The re-openable closure may be a plastic zip seal closure without slider, or other means which meet the test requirements of § 160.054–5.
 - (b) [Reserved]

§ 160.054-4 Contents.

- (a) *Individual cartons*. Cartons and their contents shall be the type indicated in Specification subpart 160.041.
- (b) *Items*. The items contained in first-aid kit shall be as listed in Table 160.054-4(b).

TABLE 160.054-4(b)-ITEMS FOR FIRST-AID KIT

ltem	No. per pkg.	Size of pkg.	No. of pkgs.
Bandage compress—4 inches	1	Single	1
Bandage compress—2 inches	4	Single	1
Waterproof adhesive compress—1 inch	16	Single	1