

**Coast Guard, DHS**

**§ 160.061-3**

HH-P-91—Packing, fiber, hard sheet.  
CCC-F-451—Flannel, canton.

(2) Military specifications:

MIL-H-2846—Hooks, fish, steel.  
MIL-B-1418—Blades, razor, safety.  
MIL-A-140—Adhesive, water-resistant, W.P. barrier-material.

(b) Copies of the specifications referred to in this section shall be kept on file by the manufacturer, together with the approved plans, if any, and the certificate of approval.

(1) The Federal Specifications may be purchased from the Business Service Center, General Services Administration, Washington, DC 20407.

(2) The Military Specifications may be obtained from the Commanding Officer, Naval Supply Depot, 5801 Tabor Avenue, Philadelphia, Pa. 19120.

**§ 160.061-2 Requirements.**

(a) *Material.* Material shall be as specified in this subpart.

(b) *Assembly.* Emergency fishing kits shall consist of fishing rigs, accessories, and instructions furnished in a hermetically sealed container.

(c) *Components.* Each fishing kit shall consist of the items listed in table 160.06-2(c).

**TABLE 160.061-2(c)—FISHING KITS—Continued**

Item No.	Description <sup>1</sup>	Quantity
12 .....	Lure, spoon, removable No. 6 hook, yellow feathers, blade length 1 <sup>3</sup> / <sub>32</sub> inches, width 1 <sup>5</sup> / <sub>32</sub> inch, weight 1/20 ounce, polished copper finish.	1 ea.
13 .....	Lure, spoon, removable No. 5/0 hook, yellow feathers, blade length 3 inches, width 7/8 inch, weight 2/5 ounce, polished chrome finish.	1 ea.
14 .....	Lure, spoon, free swinging No. 1 treble double strength, short shank, blade length 2 <sup>3</sup> / <sub>16</sub> inches, width 1 <sup>3</sup> / <sub>16</sub> inch, weight 1/4 ounce, stainless steel or chrome plated brass.	1 ea.
15 .....	Sinkers, pinch on or equal, 1/4 ounce, 5/16 ounce, 1 ounce.	1 ea.
16 .....	Foil, shiny, 4 inches square .....	1 ea.
17 .....	Squid, tinned body, length 2 inches, weight 1/2 ounce.	1 ea.
18 .....	Jig, painted lead head, bucktail feathered with 1/0 hook.	1 ea.
19 .....	Jig, painted lead head, bucktail feathered with 3/0 hook.	1 ea.
20 .....	Blades, razor, safety, single edge ...	1 ea.
21 .....	Bait, pork rind, 4 inches long, 1/2 inch wide, with ends tapered to 1/8 inch wide and rounded.	4 ea.
22 .....	Snap and swivels, No. 3 .....	6 ea.
23 .....	Card, leader knots and hitches (fig. 1).	1 ea.
24 .....	Winder (see § 160.061-3(h)) .....	2 ea.

<sup>1</sup>The tolerances of these items shall be plus or minus 1/32-inch on all dimensions.

**TABLE 160.061-2(c)—FISHING KITS**

Item No.	Description <sup>1</sup>	Quantity
1 .....	Booklet, Fishing Instructions (Refer to § 160.061-3(i)).	1 ea.
2 .....	Container, Fishing Kit (See Fig. 2) ..	1 ea.
3 .....	Hooks, treble, size 1, short shank ...	2 ea.
4 .....	Hooks, size 7/0, 5/0, 1/0, 2, 6, 8, O'Shaugnessy, straight shank, double strength.	2 ea.
5 .....	Leader, wire, 0.011-inch diameter, 27-pound test (with No. 3 snap on one end and No. 7 swivel on the other end) 6-inch length.	2 ea.
6 .....	Leader, wire, 0.016-inch diameter, 58-pound test (with No. 3 snap on one end and No. 4 swivel on the other end) 12-inch length.	2 ea.
7 .....	Leader, monofilament, 0.021-inch diameter, 15-pound test, 4-foot length.	4 ea.
8 .....	Line, monofilament, 18-pound test, 100-foot length.	1 ea.
9 .....	Line, nylon or dacron, braided, 63-pound test, 150 feet length.	1 ea.
10 .....	Pad, canton flannel, 2 <sup>3</sup> / <sub>4</sub> inches square, specification CCC-F-451, color, bright yellow.	1 ea.
11 .....	Pad, canton flannel, 2 <sup>3</sup> / <sub>4</sub> inches square, specification CCC-F-451, color, bright red.	1 ea.

**§ 160.061-3 Design and construction.**

(a) *Container.* The container shall be made of ethyl cellulose, clear, type EM-1, Specification MIL-P-3412 or better. The dimensions shall not exceed those specified in Figure 2. Other packaging arrangements acceptable to the Commandant will be considered.

(b) *Card.* A card showing leader knots and hitches shall be provided as per Figure 1. Size of card should not exceed 2<sup>3</sup>/<sub>4</sub> by 4<sup>3</sup>/<sub>4</sub> inches.

(c) *Hooks.* Unless otherwise specified, all hooks shall be of forged steel, hollow ground with filed out points. The hooks shall be of ringed type and shall be tinned. Hooks shall be tempered, tough, flexible, and resilient.

(d) *Leaders.* Wire leaders shall be of stainless steel, and shall be attached to snaps and swivels with not less than six turns of wire. Monofilament leaders shall be blue mist and shall be provided with a 5/8-inch inside diameter end loop on one end.