§ 185.506

or with a representative of the owner or managing operator of the vessel. The passenger count shall be available to the Coast Guard upon request.

§ 185.506 Passenger safety orientation.

- (a) Except as allowed by paragraphs (b) and (c) of this section, before getting underway on a voyage or as soon as practicable thereafter, the master of a vessel shall ensure that suitable public announcements are made informing all passengers of the following:
- (1) The location of emergency exits, survival craft embarkation areas, and ring life buoys;
- (2) The stowage location(s) of life jackets;
 - (3) Either:
- (i) The proper method of donning and adjusting life jackets of the type(s) carried on the vessel including a demonstration of the proper donning of a lifejacket. or
- (ii) That passengers may contact a crew member for a demonstration as appropriate, prior to beginning an oceans or coastwise voyage;
- (4) The location of the instruction placards for life jackets and other life-saving devices;
- (5) That all passengers will be required to don life jackets when possible hazardous conditions exist, as directed by the master; and
- (6) If the vessel is operating with reduced manning or equipment requirements in §176.114 of this chapter.
- (b) As an alternative to an announcement that complies with paragraph (a) of this section, the master or other designated person may—
- (1) Prior to getting underway, deliver to each passenger or, on a vessel that does not carry vehicles and that has seats for each passenger, place near each seat, a card or pamphlet that has the information listed in paragraphs (a)(1) through (a)(6) of this section; and
- (2) Make an abbreviated announcement consisting of:
- (i) A statement that passengers should follow the instructions of the crew in an emergency;
- (ii) The location of life jackets; and
- (iii) That further information concerning emergency procedures including the donning of life jackets, location of other emergency equipment, and

emergency evacuation procedures are located on the card or pamphlet that was given to each passenger or is located near each seat.

- (c) Ferries operating on short runs of less than 15 minutes may substitute bulkhead placards or signs for the announcement required in paragraphs (a) and (b) of this section if the OCMI determines that the announcements are not practical due to the vessel's unique operation.
- (d) The master of a vessel shall ensure that a passenger, who boards the vessel on a voyage after the initial public announcement has been made as required by paragraphs (a) or (b) of this section, is also informed of the required safety information.
- (e) On a vessel on a voyage of more than 24 hours duration, passengers shall be requested to don life jackets and go to the appropriate embarkation station during the safety orientation. If only a small number of passengers embark at a port after the original muster has been held, these passengers must be given the passenger safety orientation required by paragraphs (a) or (b) of this section if another muster is not held.

[CGD 85-080, 61 FR 1005, Jan. 10, 1996; 61 FR 20557, May 7, 1996, as amended by CGD 97-057, 62 FR 51050, Sept. 30, 1997; 62 FR 51359, Sept. 30, 1997]

§ 185.508 Wearing of life jackets.

- (a) The master of a vessel shall require passengers to don life jackets when possible hazardous conditions exist, including, but not limited to:
- (1) When transiting hazardous bars and inlets:
- (2) During severe weather;
- (3) In event of flooding, fire, or other events that may possibly call for evacuation; and
- (4) When the vessel is being towed, except a non-self-propelled vessel under normal operating conditions.
- (b) The master or crew shall assist each passenger in obtaining a life jacket and donning it, as necessary.

§ 185.510 Emergency instructions.

(a) The master and crew of a vessel will be familiar with the content of and have mounted at the operating station, emergency instructions containing the

actions to be taken in the event of fire, heavy weather, or man overboard conditions.

- (b) Except when in the judgment of the cognizant OCMI the operation of a vessel does not present one of the hazards listed, the emergency instruction placard should contain at least the applicable portions of the "Emergency Instructions" listed in §185.512. The emergency instructions must be designed to address the particular equipment, arrangement, and operation of each individual vessel.
- (c) If the cognizant OCMI determines that there is no suitable mounting surface aboard the vessel, the emergency instructions need not be posted but must be carried aboard the vessel and be available to the crew for familiarization.

§ 185.512 Recommended emergency instructions format.

An emergency instruction placard containing the following information will satisfy the requirements of §185.510.

- (a) Emergency instructions—(1) Rough weather at sea, crossing hazardous bars, or flooding. (i) Close all watertight and weathertight doors, hatches, and airports to prevent taking water aboard or further flooding in the vessel.
- (ii) Keep bilges dry to prevent loss of stability due to water in bilges. Use power driven bilge pump, hand pump, and buckets to dewater.
- (iii) Align fire pumps to use as bilge pump if possible.
- (iv) Check all intake and discharge lines, which penetrate the hull, for leakage.
- (v) Passengers must remain seated and evenly distributed.
- (vi) Passengers must don life jackets if the going becomes very rough, the vessel is about to cross a hazardous bar, or when otherwise instructed by the master.
- (vii) Never abandon the vessel unless actually forced to do so.
- (viii) If assistance is needed follow the procedures on the emergency broadcast placard posted by the radiotelephone.
- (ix) Prepare survival craft (life floats, (inflatable) rafts, (inflatable) buoyant apparatus, boats) for launching.

- (2) Man overboard. (i) Throw a ring buoy overboard as close to the person as possible.
- (ii) Post a lookout to keep the person overboard in sight.
- (iii) Launch rescue boat and maneuver to pick up person in the water, or maneuver the vessel to pick up the person in the water.
- (iv) Have crew member put on life jacket, attach a safety line to him or her, and have him or her stand by jump into the water to assist the person overboard if necessary.
- (v) If person is not immediately located, notify Coast Guard and other vessels in vicinity by radiotelephone.
- (vi) Continue search until released by Coast Guard.
- (3) Fire. (i) Cut off air supply to fire—close items such as hatches, ports, doors, ventilators, and louvers, and shut off ventilation system.
- (ii) Cut off electrical system supplying affected compartment if possible.
- (iii) If safe, immediately use portable fire extinguishers at base of flames for flammable liquid or grease fires or water for fires in ordinary combustible materials. Do not use water on electrical fires.
- (iv) If fire is in machinery spaces, shut off fuel supply and ventilation and activate fixed extinguishing system if installed.
- (v) Maneuver vessel to minimize effect of wind on fire.
- (vi) If unable to control fire, immediately notify the Coast Guard and other craft in the vicinity by radiotelephone.
- (vii) Move passengers away from fire, have them put on life jackets, and if necessary, prepare to abandon the vessel.
 - (b) [Reserved]

§185.514 Station bill.

- (a) A station bill must be posted by the master on a vessel of more than 19.8 meters (65 feet) in length having a Certificate of Inspection requiring more than four crew members at any one time, including the master.
- (b) The station bill required by paragraph (a) of this section must set forth the special duties and duty station of