

§ 25.139

in two orthogonal planes of the antenna.

(i) In the azimuth plane, plus and minus 10 degrees and plus and minus 180 degrees.

(ii) In the elevation plane, zero to 30 degrees.

(2) Cross-polarization patterns in the E- and H-planes, plus and minus 10 degrees.

(3) Main beam gain.

(e) Protection of receive earth stations from adjacent satellite interference is based on either the antenna performance specified in § 25.209 (a) and (b), or the actual receiving earth station antenna performance, if actual performance provides greater isolation from adjacent satellite interference. For purposes of insuring the correct level of protection, the applicant shall provide, for each earth station antenna type, the antenna performance plots for the 20 GHz band, including the format specified in paragraph (d) of this section.

(f) The earth station licensee shall not transmit towards a GSO FSS satellite unless it has prior authorization from the satellite operator or a space segment vendor authorized by the satellite operator. The specific transmission shall be conducted in accordance with the operating protocol specified by the satellite operator. The holder of an FCC blanket license pursuant to this section shall be responsible for operation of any transceiver to receive GSO FSS service provided by that licensee or provided by another party with the blanket licensee's consent. Operators of GSO FSS systems shall not transmit communications to or from user transceivers in the United States unless such communications are authorized under a service contract with the holder of a pertinent FCC blanket license or under a service contract with another party with authority for such transceiver operation delegated by such a blanket licensee.

(g) A licensee applying to renew its license must include on FCC Form 405 the number of constructed earth stations.

[65 FR 54169, Sept. 7, 2000, as amended at 66 FR 63515, Dec. 7, 2001; 68 FR 16966, Apr. 8, 2003; 69 FR 5710, Feb. 6, 2004; 73 FR 70900, Nov. 24, 2008]

47 CFR Ch. I (10–1–12 Edition)

§ 25.139 NGSO FSS coordination and information sharing between MVDDS licensees in the 12.2 GHz to 12.7 GHz band.

(a) NGSO FSS licensees shall maintain a subscriber database in a format that can be readily shared with MVDDS licensees for the purpose of determining compliance with the MVDDS transmitting antenna spacing requirement relating to qualifying existing NGSO FSS subscriber receivers set forth in § 101.129 of this chapter. This information shall not be used for purposes other than set forth in § 101.129 of this chapter. Only sufficient information to determine compliance with § 101.129 of this chapter is required.

(b) Within ten business days of receiving notification of the location of a proposed MVDDS transmitting antenna, the NGSO FSS licensee shall provide sufficient information from the database to enable the MVDDS licensee to determine whether the proposed MVDDS transmitting site meets the minimum spacing requirement.

(c) If the location of the proposed MVDDS transmitting antenna site does not meet the separation requirements of § 101.129 of this chapter, then the NGSO FSS licensee shall also indicate to the MVDDS licensee within the same ten day period specified in paragraph (b) of this section whether the proposed MVDDS transmitting site is acceptable at the proposed location.

(d) Nothing in this section shall preclude NGSO FSS and MVDDS licensees from entering into an agreement to accept MVDDS transmitting antenna locations that are shorter-spaced from existing NGSO FSS subscriber receivers than the distance set forth in § 101.129 of this chapter.

[67 FR 43037, June 26, 2002, as amended at 68 FR 43945, July 25, 2003]

SPACE STATIONS

§ 25.140 Qualifications of fixed-satellite space station licensees.

(a) New fixed-satellites shall comply with the requirements established in Report and Order, CC Docket No. 81–704 (available at address in § 0.445 of this chapter.) Applications must also meet the requirements in paragraphs (b)