

**Federal Railroad Administration, DOT**

**§ 236.551**

**§ 236.515 Visibility of cab signals.**

The cab signals shall be plainly visible to member or members of the locomotive crew from their stations in the cab.

[49 FR 3386, Jan. 26, 1984]

**§ 236.516 Power supply.**

Automatic cab signal, train stop, or train control device hereafter installed shall operate from a separate or isolated power supply.

[49 FR 3386, Jan. 26, 1984]

**RULES AND INSTRUCTIONS; ROADWAY**

**§ 236.526 Roadway element not functioning properly.**

When a roadway element except track circuit of automatic train stop, train control or cab signal system is not functioning as intended, the signal associated with such roadway element shall be caused manually to display its most restrictive aspect until such element has been restored to normal operative condition.

**§ 236.527 Roadway element insulation resistance.**

Insulation resistance between roadway inductor and ground shall be maintained at not less than 10,000 ohms.

[49 FR 3386, Jan. 26, 1984]

**§ 236.528 Restrictive condition resulting from open hand-operated switch; requirement.**

When a facing point hand-operated switch is open one-fourth inch or more, a trailing point hand-operated switch three-eighths inch or more, or hand-operated switch is not locked where facing point lock with circuit controller is used, the resultant restrictive condition of an automatic train stop or train control device of the continuous type or the resultant restrictive cab signal indication of an automatic cab signal device on an approaching locomotive shall be maintained to within 300 feet of the points of the switch.

**§ 236.529 Roadway element inductor; height and distance from rail.**

Inductor of the inert roadway element type shall be maintained with the

inductor pole faces at a height above the plane of the tops of the rails, and with its inner edge at a horizontal distance from the gage side of the nearest running rail, in accordance with specifications of the carrier.

[49 FR 3386, Jan. 26, 1984]

**§ 236.530 [Reserved]**

**§ 236.531 Trip arm; height and distance from rail.**

Trip arm of automatic train stop device when in the stop position shall be maintained at a height above the plane of the tops of the rails, and at a horizontal distance from its center line to gage side of the nearest running rail, in accordance with specifications of the carrier.

[49 FR 3386, Jan. 26, 1984]

**§ 236.532 Strap iron inductor; use restricted.**

No railroad shall use strap iron inductor or other roadway element with characteristics differing from its standard type on track where speed higher than restricted speed is permitted.

[49 FR 3386, Jan. 26, 1984]

**§ 236.533 [Reserved]**

**§ 236.534 Entrance to equipped territory; requirements.**

Where trains are not required to stop at the entrance to equipped territory, except when leaving yards and stations and speed until entering equipped territory does not exceed restricted speed, the automatic train stop, train control, or cab signal device shall be operative at least stopping distance from the entrance to such territory except where the approach thereto is governed by automatic approach signal.

**RULES AND INSTRUCTIONS; LOCOMOTIVES**

**§ 236.551 Power supply voltage; requirement.**

The voltage of power supply shall be maintained within 10 percent of rated voltage.