shall also confirm that the producer's milk is currently not excluded from the market (§ 58.137). Thereafter, the milk shall be tested in accordance with the provisions in §§ 58.133, 58.134 and 58.135.

[58 FR 26913, May 6, 1993]

§ 58.139 Record of tests.

Accurate records listing the results of quality and drug residue tests for each producer shall be kept on file at the plant. Additionally, the plant shall obtain the quality and drug residue test records (§ 58.148(a), (e) and (g)) for any producer transferring milk shipment from another plant. These records shall be available for examination by the inspector.

[58 FR 26913, May 6, 1993]

§ 58.140 Field service.

A representative of the plant shall arrange to promptly visit the farm of each producer whose milk tests positive for drug residue, exceeds the maximum somatic cell count level, or does not meet the requirements for acceptable milk. The purpose of the visit shall be to inspect the milking equipment and facilities and to offer assistance to improve the quality of the producer's milk and eliminate any potential causes of drug residues. A representative of the plant should routinely visit each producer as often as necessary to assist and encourage the production of high quality milk.

[58 FR 26913, May 6, 1993]

§ 58.141 Alternate quality control program.

When a plant has in operation an acceptable quality program, at the producer level, which is approved by the Administrator as being effective in obtaining results comparable to or higher than the quality program as outlined above for milk or cream, then such a program may be accepted in lieu of the program herein prescribed.

Operations and Operating Procedures

§ 58.142 Product quality and stability.

The receiving, holding and processing of milk and cream and the manufacturing, handling, packaging, storing and delivery of dairy products shall be in accordance with clean and sanitary methods, consistent with good commercial practices to promote the production of the highest quality of finished product and improve product stability. Milk should not be more than three days old when picked up from the producer and delivered to the plant, receiving station or transfer station.

§ 58.143 Raw product storage.

(a) All milk shall be held and processed under conditions and at temperatures that will avoid contamination and rapid deterioration. Drip milk from can washers and any other source shall not be used for the manufacture of dairy products. Bulk milk in storage tanks within the dairy plant shall be handled in such a manner as to minimize bacterial increase and shall be maintained at 45 °F. or lower until processing begins. This does not preclude holding milk at higher temperatures for a period of time, where applicable to particular manufacturing or processing practices.

(b) The bacteriological quality of commingled milk in storage tanks shall not exceed 1,000,000/ml.

[40 FR 47911, Oct. 10, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 67 FR 48976, July 29, 2002]

§ 58.144 Pasteurization or ultra-pasteurization.

When pasteurization or ultra-pasteurization is intended or required, or when a product is designated ''pasteurized'' or ''ultra-pasteurized'' every particle of the product shall be subjected to such temperatures and holding periods in approved systems as will assure proper pasteurization or ultra-pasteurization of the product. The heat treatment by either process shall be sufficient to insure public health safety and to assure adequate keeping quality, yet retaining the most desirable flavor and body characteristics of the finished product.

§ 58.145 Composition and wholesomeness.

All necessary precautions shall be taken to prevent contamination or

adulteration of the milk or dairy products during manufacturing. All substances and ingredients used in the processing or manufacturing of any dairy product shall be subject to inspection and shall be wholesome and practically free from impurities. The finished products shall comply with the requirements of the Federal Food, Drug, and Cosmetic Act as to their composition and wholesomeness.

§ 58.146 Cleaning and sanitizing treatment.

(a) *Equipment and utensils.* The equipment, sanitary piping and utensils used in receiving and processing of the milk, and manufacturing and handling of the product shall be maintained in a sanitary condition. Sanitary seal assemblies shall be removable on all agitators, pumps, and vats and shall be inspected at regular intervals and kept clean. Unless other provisions are recommended in the following supplement sections, all equipment not designed for C.I.P. cleaning or mechanical cleaning shall be disassembled after each day's use for thorough cleaning. Dairy cleaners, detergents, wetting agents or sanitizing agents, or other similar materials which will not contaminate or adversely affect the products may be used. Steel wool or metal sponges shall not be used in the cleaning of any dairy equipment or utensils.

(1) Product contact surfaces shall be subjected to an effective sanitizing treatment prior to use, except where dry cleaning is permitted. Utensils and portable equipment used in processing and manufacturing operations shall be stored above the floor in clean, dry locations and in a self draining position on racks constructed of impervious corrosion-resistant material.

(2) C.I.P. cleaning or mechanical cleaning systems shall be used only on equipment and pipeline systems which have been designed, engineered and installed for that purpose. When such cleaning is used, careful attention shall be given to the proper procedures to assure satisfactory cleaning. All C.I.P. installations and cleaning procedures shall be in accordance with 3–A Suggested Method for the Installation and Cleaning of Cleaned-In-Place Sanitary Milk Pipelines for Milk and Milk Products Plants. Because of the possibilities of corrosion, the recommendations of the cleaning compound manufacturer should be followed with respect to time, temperature and concentration of specific acid or alkaline solutions and bactericides. Such cleaning operation should be preceded by a thorough rinse at approximately 110–115 °F. continuously discarding the water. Following the circulation of the cleaning solution the equipment and lines shall be thoroughly rinsed with lukewarm water and checks should be made for effectiveness of cleaning. All caps, plugs, special fittings, valve seats, cross ends, pumps, and tee ends shall be opened or removed and brushed clean. All non-pasteurized product contact surfaces should be sanitized. Immediately prior to starting the product flow, the pasteurized product contact surfaces shall be given sanitizing treatment.

(b) *Milk cans and can washers.* Milk cans and lids shall be cleaned, sanitized and dried before returning to producers. Inspection, repair or replacement of cans and lids shall be adequate to substantially exclude from use cans and lids showing open seams, cracks, rust condition, milkstone or any unsanitary condition.

Washers shall be maintained in a clean and satisfactory operating condition and kept free from accumulation of scale or debris which will adversely affect the efficiency of the washer. Only washing compounds which are compatible with the water for effective cleaning, should be used. The can washer should be checked regularly during the run for proper operation. At the end of the day, the wash and rinse tanks should be drained and cleaned, jets and strainers cleaned, air filters checked and changed or cleaned if needed, and checks should be made for proper adjustment and condition of mechanical parts.

(c) *Milk transport tanks.* A covered or enclosed wash dock and cleaning and sanitizing facilities shall be available to all plants that receive or ship milk in tanks. Milk transport tanks, sanitary piping, fittings, and pumps shall be cleaned and sanitized at least once each day after use: Provided that, if they are not to be used immediately