

Standards for Plastic, and Rubber and Rubber-Like Material. All areas shall be free from cracks and rough surfaces and constructed so that they can be easily cleaned.

(b) *Curd conveying systems.* The curd conveying system, conveying lines and cyclone separator shall be constructed of stainless steel or other equally corrosion resistant metal and in such manner that it can be satisfactorily cleaned. The system shall be of sufficient size to handle the volume of curd and be provided with filtered air of the quality satisfactory for the intended use. Air compressors or vacuum pumps shall not be located in the processing or packaging areas.

(c) *Automatic salter.* The automatic salter shall be constructed of stainless steel or other equally corrosion resistant metal. This equipment shall be constructed to equally distribute the salt throughout the curd. It shall be designed to accurately weigh the amount of salt added. The automatic salter shall be constructed so that it can be satisfactorily cleaned. The salting system shall provide for adequate absorption of the salt in the curd. Water and steam used to moisten the curd prior to salting shall be potable water or culinary steam.

(d) *Automatic curd filler.* The automatic curd filler shall be constructed of stainless steel or other equally corrosion resistant metal. This equipment shall be of sufficient size to handle the volume of curd and constructed and controlled so as to accurately weigh the amount of curd as it fills. The curd filler shall be constructed so that it can be satisfactorily cleaned.

(e) *Hoop and barrel washer.* The washer shall be constructed so that it can be satisfactorily cleaned. It shall also be equipped with temperature and pressure controls to ensure satisfactory cleaning of the hoops or barrels. It should be adequately vented to the outside.

**§ 58.419 Curd mill and miscellaneous equipment.**

Knives, hand rakes, shovels, scoops, paddles, strainers, and miscellaneous equipment shall be stainless steel or of material approved in the 3-A Sanitary Standards for Plastic and Rubber-like

Material. The product contact surfaces of the curd mill should be of stainless steel. All pieces of equipment shall be so constructed that they can be kept clean and free from rough or sharp edges which might scratch the equipment or remove metal particles. The wires in the curd knives shall be stainless steel, kept tight and replaced when necessary.

**§ 58.420 Hoops, forms and followers.**

The hoops, forms, and followers shall be constructed of stainless steel, heavy tinned steel or other approved materials. If tinned, they shall be kept tinned and free from rust. All hoops, forms, and followers shall be kept in good repair. Drums or other special forms used to press and store cheese shall be clean and sanitary.

**§ 58.421 Press.**

The cheese press should be constructed of stainless steel and all joints welded and all surfaces, seams and openings readily cleanable. The pressure device shall be the continuous type. Press cloths shall be maintained in good repair and in a sanitary condition. Single service press cloths shall be used only once.

**§ 58.422 Brine tank.**

The brine tank shall be constructed of suitable non-toxic material and should be resistant to corrosion, pitting or flaking. The brine tank shall be operated so as to assure the brine is clean, well circulated, and of the proper strength and temperature for the variety of cheese being made.

**§ 58.423 Cheese vacuumizing chamber.**

The vacuum chamber shall be satisfactorily constructed and maintained so that the product is not contaminated with rust or flaking paint. An inner liner of stainless steel or other corrosion resistant material should be provided.

**§ 58.424 Monorail.**

The monorail shall be constructed so as to prevent foreign material from falling on the cheese or cheese containers.