

## § 1919.29

## 29 CFR Ch. XVII (7–1–13 Edition)

(1) Tests shall be conducted at maximum, minimum, and intermediate radius points, as well as such points in the arc of rotation as meet with the approval of the accredited person.

(2) An additional test shall be conducted with partial load and shall include all functions and movements contemplated in the use of the crane.

(e) In cases where shore-type cranes are mounted permanently aboard barges, the requirements of this Subpart E with respect to unit proof tests and examinations shall not apply and the applicable requirements of Subpart H of this part shall be adhered to with respect to unit proof tests and examinations.

### § 1919.29 Limitations on safe working loads and proof loads.

The proof loads specified by §§ 1919.27 and 1919.28 shall be adjusted as necessary to meet any pertinent limitations based on stability and/or on structural competence at particular radii. Safe working loads shall be reduced accordingly.

### § 1919.30 Examinations subsequent to unit tests.

(a) After satisfactory completion of the unit proof load tests required by §§ 1919.27 and 1919.28, the cargo gear and all component parts thereof shall be given a thorough visual examination, supplemented as necessary by other means, such as a hammer test or with electronic, ultrasonic, or other non-

destructive methods, to determine if any of the parts were damaged, deformed, or otherwise rendered unsafe for further use.

(b) When the test of gear referred to in paragraph (a) of this section is being conducted for the first time on a vessel, accessory gear shall be dismantled or disassembled for examination after the test. The sheaves and pins of the blocks included in this test need not be removed unless there is evidence of deformation or failure.

(c) For subsequent tests such parts of the gear shall be dismantled or disassembled after the test as necessary to determine their suitability for continued service.

(d) When blocks are disassembled all shell bolt nuts shall be securely locked upon reassembly.

(e) In carrying out the requirements of this section, replacement shall be required of:

(1) Any swivel found to have excessive tolerance as a result of wear on any bearing surface.

(2) Pins of blocks found to be shouldered, notched, or grooved from wear, in which case, in addition to replacing the pin, sheave bushings shall be examined for suitability for continued use.

### § 1919.31 Proof tests—loose gear.

(a) Chains, rings, shackles and other loose gear (whether accessory to a machine or not) shall be tested with a proof load against the article equal to that shown in the following table:

Article of gear	Proof load
Chain, ring, hook, shackle or swivel .....	100 percent in excess of the safe working load.
Blocks:	
Single sheave block .....	300 percent in excess of the safe working load. <sup>1</sup>
Multiple sheave block with safe working load up to and including 20 tons ..	100 percent in excess of the safe working load.
Multiple sheave block with safe working load over 20 tons up to and including 40 tons.	20 tons in excess of the safe working load.
Multiple sheave block with safe working load over 40 tons .....	50 percent in excess of the safe working load.
Pitched chains used with hand-operated blocks and rings, hooks, shackles or swivels permanently attached thereto.	50 percent in excess of the safe working load.
Hand-operated blocks used with pitched chains and rings, hooks, shackles or swivels permanently attached thereto.	50 percent in excess of the safe working load.

<sup>1</sup> The proof load applied to the block is equivalent to twice the maximum resultant load on the eye of pin of the block when lifting the nominal safe working load defined in (i) below. The proof load is, therefore, equal to four times the safe working load as defined in (i) below or twice the safe working load as defined in (ii) below.

(i) The nominal safe working load of a single-sheave block should be the maximum load which can be safely lifted by the block when the load is attached to a rope which passes around the sheave of the block.

(ii) In the case of a single-sheave block where the load is attached directly to the block instead of to a rope passing around the sheave, it is permissible to lift a load equal to twice the nominal safe working load of the block as defined in (i) above.

(iii) In the case of a lead block so situated that an acute angle cannot be formed by the two parts of the rope passing over it (i.e., the angle is always 90° or more), the block need not have a greater nominal safe working load than one-half the maximum resultant load which can be placed upon it.