## **Environmental Protection Agency**

Table 6 to Subpart AAAAA of Part 63—Periodic Monitoring for Compliance With Opacity and Visible Emissions Limits

As required in  $\S63.7121$  you must periodically demonstrate compliance with each opacity and VE limit that applies to you, according to the following table:

For	For the following emission limitation	You must demonstrate ongoing compliance
Each PSH operation subject to an opacity limitation as required in Table 1 to this subpart, or any vents from buildings subject to an opacity limitation.	a. 7–10 percent opacity, depending on the PSH operation, as required in Table 1 to this subpart.	(i) Conducting a monthly 1-minute VE check of each emission unit in accordance with § 63.7121(e); the check must be conducted while the affected source is in operation; (ii) If no VE are observed in 6 consecutive monthly checks for any emission unit, you may decrease the frequency of VE checking from monthly to semiannually for that emission unit; if VE are observed during any semiannual check, you must resume VE checking of that emission unit on a monthly basis and maintain that schedule until no VE are observed in 6 consecutive monthly checks; (iii) If no VE are observed during the semiannual check for any emission unit, you may decrease the frequency of VE checking from semi-annually to annually for that emission unit; if VE are observed during any annual check, you must resume VE checking of that emission unit on a monthly basis and maintain that schedule until no VE are observed in 6 consecutive monthly checks; and (iv) If VE are observed during any VE check, you must conduct a 6-minute test of opacity in accordance with Method 9 of appendix A to part 60 of this chapter; you must begin the Method 9 test within 1 hour of any observation of VE and the 6-minute opacity reading must not exceed the applica-
Any building subject to a VE limit, according to item 8 of Table 1 to this subpart.	a. No VE	ble opacity limit.  (i) Conducting a monthly VE check of the building, in accordance with the specifications in § 63.7112(k); the check must be conducted while all the enclosed PSH operations are operating;  (ii) The check for each affected building must be at least 5 minutes, with each side of the building and roof being observed for at least 1 minute;  (iii) If no VE are observed in 6 consecutive monthly checks of the building, you may decrease the frequency of checking from monthly to semi-annually for that affected source; if VE are observed during any semi-annual check, you must resume checking on a monthly basis and maintain that schedule until no VE are observed in 6 consecutive monthly checks; and

## Pt. 63, Subpt. AAAAA, Table 7

## 40 CFR Ch. I (7-1-13 Edition)

For	For the following emission limitation	You must demonstrate ongoing compliance
		(iv) If no VE are observed during the semi-annual check, you may decrease the frequency of checking from semi-annually to annually for that affected source; and if VE are observed during any annual check, you must resume checking of that emission unit on a monthly basis and maintain that schedule until no VE are observed in 6 consecutive monthly checks (the source is in compliance if no VE are observed during any of these checks).

## Table 7 to Subpart AAAAA of Part 63—Requirements for Reports

As required in  $\S63.7131$ , you must submit each report in this table that applies to you.

You must submit a	The report must contain	You must submit the report
1. Compliance report	a. If there are no deviations from any emission limitations (emission limit, operating limit, opacity limit, and VE limit) that applies to you, a statement that there were no deviations from the emission limitations during the reporting period;	Semiannually according to the requirements in § 63.7131(b).
	b. If there were no periods during which the CMS, including any operating parameter monitoring system, was out-of-control as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out-of-control during the reporting period;	Semiannually according to the requirements in §63.7131(b).
	If you have a deviation from any emission limitation (emission limit, operating limit, opacity limit, and VE limit) during the reporting period, the report must contain the information in §63.7131(d):	Semiannually according to the requirements in §63.7131(b).
	d. If there were periods during which the CMS, including any operating parameter monitoring system, was out-of-control, as specified in § 63.8(c)(7), the report must contain the information in § 63.7131(e); and	Semiannually according to the requirements in § 63.7131(b).
	e. If you had a startup, shutdown or mal- function during the reporting period and you took actions consistent with your SSMP, the compliance report must include the information in §63.10(d)(5)(i).	Semiannually according to the requirements in §63.7131(b).
<ol><li>An immediate startup, shutdown, and malfunction report if you had a startup, shutdown, or malfunction during the re- porting period that is not consistent with your SSMP.</li></ol>	Actions taken for the event	By fax or telephone within 2 working days after starting actions inconsistent with the SSMP.
<ol><li>An immediate startup, shutdown, and malfunction report if you had a startup, shutdown, or malfunction during the re- porting period that is not consistent with your SSMP.</li></ol>	The information in § 63.10(d)(5)(ii)	By letter within 7 working days after the end of the event unless you have made alternative arrangements with the permitting authority. See § 63.10(d)(5)(ii).