Environmental Protection Agency

§ 63.7912 What are my inspection and monitoring requirements for separators?

- (a) If you use a floating roof according to $\S63.7910(b)(1)$, you must meet requirements in paragraphs (a)(1) and (2) of this section.
- (1) Measure the seal gaps at least annually according to the requirements in §63.1047(b)(1).
- (2) Visually inspect the floating roof at least annually according to the requirements in §63.1047(b)(2).
- (b) If you use a cover vented to a control device according to §63.7910(b)(1) or (2), you must meet requirements in paragraphs (b)(1) and (2) of this section.
- (1) You must visually inspect the cover and its closure devices for defects according to the requirements in \$63.1047(c).
- (2) You must monitor and inspect the closed vent system and control device according to the requirements in §63.7927 that apply to you.
- (c) If you use a pressurized separator that operates as a closed system according to §63.7910(b)(3), you must visually inspect each pressurized separator and closure devices for defects at annually to ensure they are operating according to the design requirements in §63.1045(b).

§ 63.7913 How do I demonstrate continuous compliance with the emissions limitations and work practice standards for separators?

- (a) You must demonstrate continuous compliance with the emissions limitations and work practice standards in §63.7910 applicable to your affected separators by meeting the requirements in paragraphs (b) through (d) of this section as applicable to your surface impoundments.
- (b) You must demonstrate continuous compliance for each separator using a floating roof according to §63.7910(b)(1) by meeting the requirements in paragraphs (b)(1) through (6) of this section.
- (1) Operating and maintaining the floating roof according to the requirements in $\S63.1043(b)$.
- (2) Performing seal gap measurement inspections at least annually according to the requirements in §63.1047(b)(1).

- (3) Visually inspecting the floating roof at least annually according to the requirements in §63.1047(b)(2).
- (4) Repairing defects according to the requirements in §63.1047(d).
- (5) Recording the information specified in §63.1048(a) and (b).
- (6) Keeping records to document compliance with the requirements according to the requirements in §63.7952.
- (c) You must demonstrate continuous compliance for each separator using a fixed roof vented through a closed vent system to a control device according to §63.7910(b)(2) by meeting the requirements in paragraphs (c)(1) through (6) of this section.
- (1) Operating and maintaining the fixed roof and its closure devices according to the requirements in §63.1042.
- (2) Performing visual inspections of the fixed roof and its closure devices for defects at least annually according to the requirements in §63.1047(a).
- (3) Repairing defects according to the requirements in §63.1047(d).
- (4) Recording the information specified in §63.1048(a).
- (5) Meeting each applicable requirement for demonstrating continuous compliance with the emission limitations and work practice standards for a closed vent system and control device in \$63.7928.
- (6) Keeping records to document compliance with the requirements of this subpart according to the requirements in \$63.7952.
- (d) You must demonstrate continuous compliance for each pressurized separator operated as a closed system according to §63.7910(b)(3) by meeting the requirements in paragraphs (d)(1) and (2) of this section.
- (1) Operating the pressurized separator at all times according to the requirements in §63.1045.
- (2) Visually inspecting each pressurized tank and closure devices for defects at least annually to ensure they are operating according to the design requirements in §63.1045(b), and recording the results of each inspection.

[68 FR 58190, Oct. 8, 2003, as amended at 71 FR 69017, Nov. 29, 2006]

§ 63.7915

TRANSFER SYSTEMS

§ 63.7915 What emissions limitations and work practice standards must I meet for transfer systems?

- (a) You must control HAP emissions from each new and existing transfer system subject to \$63.7886(b)(1)(v) according to emissions limitations and work practice standards in this section that apply to your affected transfer systems.
- (b) For each affected transfer system that is an individual drain system as defined in §63.7957, you must install and operate controls according to the requirements in §63.962.
- (c) For each affected transfer system that is not an individual drain system as defined in §63.7957, you must use one of the transfer systems specified in paragraphs (c)(1) through (3) of this section.
- (1) A transfer system that uses covers according to the requirements in §63.689(d).
- (2) A transfer system that consists of continuous hard piping. All joints or seams between the pipe sections must be permanently or semi-permanently sealed (e.g., a welded joint between two sections of metal pipe or a bolted and gasketed flange).
- (3) A transfer system that is enclosed and vented through a closed vent system to a control device according to the requirements specified in paragraphs (c)(3)(i) and (ii) of this section.
- (i) The transfer system is designed and operated such that an internal pressure in the vapor headspace in the enclosure is maintained at a level less than atmospheric pressure when the control device is operating, and
- (ii) The closed vent system and control device are designed and operated to meet the emissions limitations and work practice standards in §63.7925 that apply to your closed vent system and control device.
- (d) As provided in §63.6(g), you may request approval from the EPA to use an alternative to the work practice standards in this section that apply to your transfer systems. If you request for permission to use an alternative to the work practice standards, you must

submit the information described in $\S 63.6(g)(2)$.

[68 FR 58190, Oct. 8, 2003, as amended at 71 FR 69018, Nov. 29, 2006]

§ 63.7916 How do I demonstrate initial compliance with the emissions limitations and work practice standards for transfer systems?

- (a) You must demonstrate initial compliance with the emissions limitations and work practice standards in §63.7915 that apply to your affected transfer systems by meeting the requirements in paragraphs (b) through (e) of this section, as applicable to your transfer systems.
- (b) You must demonstrate initial compliance of each individual drain system using controls according to §63.7915(b) if you have submitted as part of your notification of compliance status, specified in §63.7950, a signed statement that you have met the requirements in paragraphs (b)(1) through (3) of this section.
- (1) You have installed air emission controls for each individual drain system and junction box according to the requirements in §63.962(a) and (b), and you have records documenting the installation and design.
- (2) You will operate the air emission controls according to the requirements in §63.962(b)(5).
- (3) You have performed an initial visual inspection of each individual drain system according to the requirements in §63.964(a), and you have records documenting the inspection results.
- (c) You must demonstrate initial compliance of each transfer system using covers according to §63.7915(c)(1) if you have submitted as part of your notification of compliance status, specified in §63.7950, a signed statement that you have met the requirements in paragraphs (c)(1) through (3) of this section.
- (1) Each transfer system is equipped with covers and closure devices according to the requirements in §63.689(d)(1) through (4), and you have records documenting the design and installation.
- (2) You have performed an initial inspection of each cover and its closure devices for defects according to the requirements in §63.695(d)(1) through (5),