Subpart BB—Silicon Carbide Production

§ 98.280 Definition of the source category.

Silicon carbide production includes any process that produces silicon carbide for abrasive purposes.

§ 98.281 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains a silicon carbide production process and the facility meets the requirements of either §98.2(a)(1) or (a)(2).

§ 98.282 GHGs to report.

You must report:

(a) CO₂ and CH₄ process emissions from all silicon carbide process units or furnaces combined.

(b) CO_2 , CH_4 , and N_2O emissions from each stationary combustion unit. You must report these emissions under subpart C of this part (General Stationary Fuel Combustion Sources) by following the requirements of subpart C.

§98.283 Calculating GHG emissions.

You must calculate and report the annual process CO_2 emissions from each silicon carbide process unit or production furnace using the procedures in either paragraph (a) or (b) of this section. You must determine CH_4 process emissions in accordance with the procedures specified in paragraph (d) of this section.

(a) Calculate and report under this subpart the process CO₂ emissions by operating and maintaining CEMS according to the Tier 4 Calculation Methodology specified in §98.33(a)(4) and all associated requirements for Tier 4 in subpart C of this part (General Stationary Fuel Combustion Sources).

(b) Calculate and report under this subpart the process CO_2 emissions using the procedures in paragraphs (b)(1) and (b)(2) of this section.

(1) Use Equation BB-1 of this section to calculate the facility-specific emissions factor for determining CO₂ emissions. The carbon content must be measured monthly and used to calculate a monthly CO₂ emissions factor:

$$EF_{CO2,n} = 0.65 * CCF_n * \left(\frac{44}{12}\right)$$
 (Eq. BB-1)

Where:

 $EF_{CO2,n} = CO_2$ emissions factor in month n (metric tons CO_2 /metric ton of petroleum coke consumed).

0.65 = Adjustment factor for the amount of carbon in silicon carbide product (assuming 35 percent of carbon input is in the carbide product).

CCF_n = Carbon content factor for petroleum coke consumed in month n from the sup-

plier or as measured by the applicable method incorporated by reference in §98.7 according to §98.284(c) (percent by weight expressed as a decimal fraction).

44/12 = Ratio of molecular weights, CO₂ to carbon.

(2) Use Equation BB-2 of this section to calculate annual ${\rm CO_2}$ process emissions from all silicone carbide production:

$$CO_2 = \sum_{n=1}^{12} \left[T_n * EF_{CO2,n} \right] * \frac{2000}{2205}$$
 (Eq. BB-2)

Where:

 ${
m CO_2} = {
m Annual} \ {
m CO_2} \ {
m emissions} \ {
m from \ silicon \ carbide \ production \ facility} \ ({
m metric \ tons} \ {
m CO_2}).$

 T_n = Petroleum coke consumption in month n (tons)