Environmental Protection Agency

monitoring system into compliance with this requirement.

[45 FR 33232, May 19, 1980, as amended at 50 FR 4514, Jan. 31, 1985; 71 FR 16909, Apr. 4, 2006]

§ 265.94 Recordkeeping and reporting.

- (a) Unless the ground water is monitored to satisfy the requirements of §265.93(d)(4), the owner or operator must:
- (1) Keep records of the analyses required in §265.92(c) and (d), the associated ground-water surface elevations required in §265.92(e), and the evaluations required in §265.93(b) throughout the active life of the facility, and, for disposal facilities, throughout the post-closure care period as well; and
- (2) Report the following ground-water monitoring information to the Regional Administrator:
- (i) During the first year when initial background concentrations are being established for the facility: concentrations or values of the parameters listed in §265.92(b)(1) for each ground-water monitoring well within 15 days after completing each quarterly analysis. The owner or operator must separately identify for each monitoring well any parameters whose concentration or value has been found to exceed the maximum contaminant levels listed in appendix III.
- (ii) Annually: Concentrations or values of the parameters listed in §265.92(b)(3) for each ground-water monitoring well, along with the required evaluations for these parameters under §265.93(b). The owner or operator must separately identify any significant differences from initial background found in the upgradient wells, in accordance with §265.93(c)(1). During the active life of the facility, this information must be submitted no later than March 1 following each calendar year.
- (iii) No later than March 1 following each calendar year: Results of the evaluations of ground-water surface elevations under §265.93(f), and a description of the response to that evaluation, where applicable.
- (b) If the ground water is monitored to satisfy the requirements of $\S 265.93(d)(4)$, the owner or operator must:

- (1) Keep records of the analyses and evaluations specified in the plan, which satisfies the requirements of §265.93(d)(3), throughout the active life of the facility, and, for disposal facilities, throughout the post-closure care period as well; and
- (2) Annually, until final closure of the facility, submit to the Regional Administrator a report containing the results of his or her ground-water quality assessment program which includes, but is not limited to, the calculated (or measured) rate of migration of hazardous waste or hazardous waste constituents in the ground water during the reporting period. This information must be submitted no later than March 1 following each calendar year.

[45 FR 33232, May 19, 1980, as amended at 48 FR 3982, Jan. 28, 1983; 50 FR 4514, Jan. 31, 1985]

Subpart G—Closure and Post-Closure

Source: 51 FR 16451, May 2, 1986, unless otherwise noted.

§ 265.110 Applicability.

Except as §265.1 provides otherwise:

- (a) Sections 265.111 through 265.115 (which concern closure) apply to the owners and operators of all hazardous waste management facilities; and
- (b) Sections 265.116 through 265.120 (which concern post-closure care) apply to the owners and operators of:
- (1) All hazardous waste disposal facilities:
- (2) Waste piles and surface impoundments for which the owner or operator intends to remove the wastes at closure to the extent that these sections are made applicable to such facilities in § 265.228 or § 265.258;
- (3) Tank systems that are required under §265.197 to meet requirements for landfills; and
- (4) Containment buildings that are required under §265.1102 to meet the requirement for landfills.
- (c) Section 265.121 applies to owners and operators of units that are subject to the requirements of 40 CFR 270.1(c)(7) and are regulated under an

§ 265.111

enforceable document (as defined in 40 CFR 270.1(c)(7)).

- (d) The Regional Administrator may replace all or part of the requirements of this subpart (and the unit-specific standards in §265.111(c)) applying to a regulated unit (as defined in 40 CFR 264.90), with alternative requirements for closure set out in an approved closure or post-closure plan, or in an enforceable document (as defined in 40 CFR 270.1(c)(7)), where the Regional Administrator determines that:
- (1) A regulated unit is situated among solid waste management units (or areas of concern), a release has occurred, and both the regulated unit and one or more solid waste management unit(s) (or areas of concern) are likely to have contributed to the release, and
- (2) It is not necessary to apply the closure requirements of this subpart (and/or those referenced herein) because the alternative requirements will protect human health and the environment, and will satisfy the closure performance standard of §265.111 (a) and (b).

[51 FR 16451, May 2, 1986, as amended at 51
FR 25479, July 14, 1986; 53 FR 34086, Sept. 2,
1988; 57 FR 37267, Aug. 18, 1992; 63 FR 56734,
Oct. 22, 1998; 71 FR 40274, July 14, 2006]

§ 265.111 Closure performance standard.

The owner or operator must close the facility in a manner that:

- (a) Minimizes the need for further maintenance, and
- (b) Controls, minimizes or eliminates, to the extent necessary to protect human health and the environment, post-closure escape of hazardous waste, hazardous constituents, leachate, contaminated run-off, or hazardous waste decomposition products to the ground or surface waters or to the atmosphere, and
- (c) Complies with the closure requirements of this subpart, including, but not limited to, the requirements of §§ 265.197, 265.228, 265.258, 265.280, 265.310, 265.351, 265.381, 265.404, and 265.1102.
- [51 FR 16451, May 2, 1986, as amended at 57 FR 37267, Aug. 18, 1992; 71 FR 40275, July 14, 2006]

§ 265.112 Closure plan; amendment of plan.

- (a) Written plan. By May 19, 1981, or by six months after the effective date of the rule that first subjects a facility to provisions of this section, the owner or operator of a hazardous waste management facility must have a written closure plan. Until final closure is completed and certified in accordance with §265.115, a copy of the most current plan must be furnished to the Regional Administrator upon request, including request by mail. In addition, for facilities without approved plans, it must also be provided during site inspections, on the day of inspection, to any officer, employee, or representative of the Agency who is duly designated by the Administrator.
- (b) Content of plan. The plan must identify steps necessary to perform partial and/or final closure of the facility at any point during its active life. The closure plan must include, at least:
- (1) A description of how each hazardous waste management unit at the facility will be closed in accordance with §265.111; and
- (2) A description of how final closure of the facility will be conducted in accordance with §265.111. The description must identify the maximum extent of the operation which will be unclosed during the active life of the facility; and
- (3) An estimate of the maximum inventory of hazardous wastes ever onsite over the active life of the facility and a detailed description of the methods to be used during partial and final closure, including, but not limited to methods for removing, transporting, treating, storing or disposing of all hazardous waste, identification of and the type(s) of off-site hazardous waste management unit(s) to be used, if applicable; and
- (4) A detailed description of the steps needed to remove or decontaminate all hazardous waste residues and contaminated containment system components, equipment, structures, and soils during partial and final closure including, but not limited to, procedures for cleaning equipment and removing contaminated soils, methods for sampling