§408.310

§408.310 Applicability; description of the Alaskan herring fillet processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of herring fillets in Alaska.

§408.311 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

§408.312 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any herring fillet processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak and Petersburg shall meet the following limitations:

	Effluent limitations		
Effluent characteristic	Maximum for any 1 day	any 1 consecutive days	
	Metric units (kg/kkg of seafood)		
TSS Oil and grease pH	32	24	
	27	10	
	(1)	(1)	
	English units (lb/1,000 lb of seafood)		
TSS	32	24	
Oil and grease	27	10	
pH	(1)	(1)	

40 CFR Ch. I (7–1–12 Edition)

(b) Any Alaskan herring fillet processing facility not covered under §408.312(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

§408.313 [Reserved]

§408.314 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard	
BOD <i>5</i> TSS pH Oil and grease	No limitation. Do. Do. Do.	

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

§408.315 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any herring fillet processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak and Petersburg shall meet the following limitations:

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kg/kkg of seafood)	
TSS	23 18	

¹ Within the range 6.0 to 9.0.