

Environmental Protection Agency

§ 471.71

§ 471.66 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

Subpart G—Uranium Forming Subcategory

§ 471.70 Applicability; description of the uranium forming subcategory.

This subpart applies to discharges of pollutants to waters of the United States, and introductions of pollutants into publicly owned treatment works from the process operations of the uranium forming subcategory.

§ 471.71 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) *Extrusion spent lubricants—subpart G—BPT.* There shall be no discharge process wastewater pollutants.

(b) *Extrusion tool contact cooling water.*

SUBPART G—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium extruded	
Cadium .....	0.117	0.052
Chromium .....	0.152	0.062
Copper .....	0.654	0.344
Lead .....	0.145	0.069
Nickel .....	0.661	0.437
Fluoride .....	20.5	9.08
Molybdenum .....	2.28	1.18
Oil and grease .....	6.88	4.13
TSS .....	14.1	6.71
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) *Heat treatment contact cooling water.*

SUBPART G—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of extruded or forged uranium heat treated	
Cadium .....	0.646	0.285
Chromium .....	0.836	0.342
Copper .....	3.61	1.90
Lead .....	0.798	0.380
Nickel .....	3.65	2.42
Fluoride .....	113	50.2
Molybdenum .....	12.6	6.5
Oil and grease .....	38	22.8
TSS .....	77.9	37.1
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(d) *Forging spent lubricants—subpart G—BPT.* There shall be no discharge of process wastewater pollutants.

(e) *Surface treatment spent baths.*

SUBPART G—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium surface treated	
Cadium .....	0.010	0.004
Chromium .....	0.012	0.005
Copper .....	0.052	0.027
Lead .....	0.012	0.006
Nickel .....	0.052	0.035
Fluoride .....	1.62	0.718
Molybdenum .....	0.180	0.093
Oil and grease .....	0.544	0.327
TSS .....	1.12	0.531
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(f) *Surface treatment rinse.*

SUBPART G—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium surface treated	
Cadium .....	0.115	0.050
Chromium .....	0.149	0.061
Copper .....	0.641	0.337
Lead .....	0.142	0.068
Nickel .....	0.647	0.428
Fluoride .....	20.1	8.90
Molybdenum .....	2.23	1.16
Oil and grease .....	6.74	4.05
TSS .....	13.8	6.57
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.