Environmental Protection Agency

SUBPART H-BPT

Pollutant or pollutant property	Maximum for any 1 day Maximum for monthly average	
	mg/off-kg (pounds per million off-pounds) of zinc electrocoated	
Chromium	1.01 4.35 0.664 3.35 45.8	0.412 2.29 0.275 1.40 27.5
TSSpH	93.9 (¹)	44.7 (¹)

¹ Within the range of 7.5 to 10.0 at all times.

(n) Degreasing spent solvents—subpart H—BPT. There shall be no discharge of process wastewater pollutants.

 $[50~\mathrm{FR}~34270,~\mathrm{Aug}.~23,~1985;~51~\mathrm{FR}~2888,~\mathrm{Jan}.~22,~1986]$

§ 471.82 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

(a) Rolling spent neat oils—subpart H— BAT. There shall be no discharge of process wastewater pollutants.

(b) Rolling spent emulsions.

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mil lion off-pounds) of zin- rolled with emulsions	
Chromium	0.0005 0.002 0.0003 0.002	0.0002 0.0009 0.0001 0.0006

(c) Rolling contact cooling water.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	lion off-pou	unds per mil- inds) of zinc contact cool-
Chromium Copper Cyanide Zinc	0.020 0.069 0.011 0.055	0.009 0.033 0.004 0.023

(d) Drawing spent emulsions.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mi lion off-pounds) of zin drawn with emulsions	
Chromium	0.002 0.008 0.001 0.006	0.0009 0.004 0.0005 0.003

(e) Direct chill casting contact cooling water.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	lion off-pou	unds per mil- unds) of zinc e direct chill
Chromium	0.019 0.065 0.010 0.052	0.008 0.031 0.004 0.021

(f) Stationary casting contact cooling water—subpart H—BAT. There shall be no discharge of process wastewater pollutants.

(g) Heat treatment contact cooling water.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		unds per mil- unds) of zinc
Chromium Copper Cyanide Zinc	0.029 0.098 0.016 0.078	0.012 0.047 0.006 0.032

§471.83

(h) Surface treatment spent baths.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mil- lion off-pounds) of zinc surface treated	
Chromium	0.033	0.014
Copper	0.114	0.054
Cyanide	0.018	0.007
Zinc	0.091	0.038

(i) Surface treatment rinse.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mil- lion off-pounds) of zinc surface treated	
Chromium Copper Cyanide Zinc	0.133 0.457 0.072 0.365	0.054 0.219 0.029 0.151

(j) Alkaline cleaning spent baths.

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium	0.002 0.005 0.0007 0.004	0.0006 0.002 0.0003 0.002

(k) Alkaline cleaning rinse.

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of zinc alkaline cleaned	
Chromium Copper Cyanide Zinc	0.626 2.17 0.338 1.73	0.254 1.03 0.135 0.710

$(1) \ Sawing \ or \ grinding \ spent \ emulsions.$

40 CFR Ch. I (7-1-13 Edition)

SUBPART H-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		unds per mil- unds) of zinc ground with
Chromium	0.009	0.004
Copper	0.031	0.015
Cyanide	0.005	0.002
Zinc	0.025	0.010

(m) Electrocoating rinse.

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mil- lion off-pounds) of zinc electrocoated	
Chromium	0.085 0.293 0.046 0.234	0.035 0.140 0.019 0.096

(n) Degreasing spent solvents—subpart H—BAT. There shall be no discharge or process wastewater pollutants.

 $[50~\mathrm{FR}~34270,~\mathrm{Aug}.~23,~1985;~51~\mathrm{FR}~2888,~\mathrm{Jan}.~22,~1986]$

§ 471.83 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

- (a) Rolling spent neat oils—subpart H—NSPS. There shall be no discharge of process wastewater pollutants.
 - (b) Rolling spent emulsions.

SUBPART H-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with emulsions	
Chromium Copper Cyanide Zinc Oil and grease TSS	0.0005 0.002 0.0003 0.002 0.014 0.021	0.0002 0.0009 0.0001 0.0006 0.014 0.017
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

⁽c) Rolling contact cooling water.