

§ 60.462

40 CFR Ch. I (7-1-13 Edition)

Prime coat operation means the coating application station, curing oven, and quench station used to apply and dry or cure the initial coating(s) on the surface of the metal coil.

Quench station means that portion of the metal coil surface coating operation where the coated metal coil is cooled, usually by a water spray, after baking or curing.

VOC content means the quantity, in kilograms per liter of coating solids, of volatile organic compounds (VOC's) in a coating.

(b) All symbols used in this subpart not defined below are given the same meaning as in the Act and in subpart A of this part.

- C_a= the VOC concentration in each gas stream leaving the control device and entering the atmosphere (parts per million by volume, as carbon).
- C_b= the VOC concentration in each gas stream entering the control device (parts per million by volume, as carbon).
- C_f= the VOC concentration in each gas stream emitted directly to the atmosphere (parts per million by volume, as carbon).
- D_c= density of each coating, as received (kilograms per liter).
- D_d= density of each VOC-solvent added to coatings (kilograms per liter).
- D_r= density of VOC-solvent recovered by an emission control device (kilograms per liter).
- E= VOC destruction efficiency of the control device (fraction).
- F= the proportion of total VOC's emitted by an affected facility that enters the control device (fraction).
- G= volume-weighted average mass of VOC's in coatings consumed in a calendar month per unit volume of coating solids applied (kilograms per liter).
- L_c= the volume of each coating consumed, as received (liters).
- L_d= the volume of each VOC-solvent added to coatings (liters).
- L_r= the volume of VOC-solvent recovered by an emission control device (liters).
- L_s= the volume of coating solids consumed (liters).
- M_d= the mass of VOC-solvent added to coatings (kilograms).
- M_c= the mass of VOC's in coatings consumed, as received (kilograms).
- M_r= the mass of VOC's recovered by an emission control device (kilograms).
- N= the volume-weighted average mass of VOC emissions to the atmosphere per unit volume of coating solids applied (kilograms per liter).
- Q_a= the volumetric flow rate of each gas stream leaving the control device and en-

- tering the atmosphere (dry standard cubic meters per hour).
- Q_b= the volumetric flow rate of each gas stream entering the control device (dry standard cubic meters per hour).
- Q_e= the volumetric flow rate of each gas stream emitted directly to the atmosphere (dry standard cubic meters per hour).
- R= the overall VOC emission reduction achieved for an affected facility (fraction).
- S= the calculated monthly allowable emission limit (kilograms of VOC per liter of coating solids applied).
- V_s= the proportion of solids in each coating, as received (fraction by volume).
- W_o= the proportion of VOC's in each coating, as received (fraction by weight).

§ 60.462 Standards for volatile organic compounds.

(a) On and after the date on which § 60.8 requires a performance test to be completed, each owner or operator subject to this subpart shall not cause to be discharged into the atmosphere more than:

- (1) 0.28 kilogram VOC per liter (kg VOC/l) of coating solids applied for each calendar month for each affected facility that does not use an emission control device(s); or
- (2) 0.14 kg VOC/l of coating solids applied for each calendar month for each affected facility that continuously uses an emission control device(s) operated at the most recently demonstrated overall efficiency; or
- (3) 10 percent of the VOC's applied for each calendar month (90 percent emission reduction) for each affected facility that continuously uses an emission control device(s) operated at the most recently demonstrated overall efficiency; or
- (4) A value between 0.14 (or a 90-percent emission reduction) and 0.28 kg VOC/l of coating solids applied for each calendar month for each affected facility that intermittently uses an emission control device operated at the most recently demonstrated overall efficiency.

§ 60.463 Performance test and compliance provisions.

- (a) Section 60.8(d) and (f) do not apply to the performance test.
- (b) The owner or operator of an affected facility shall conduct an initial