Coast Guard, DHS

(b) Warning sign at gangway. A sign shall be displayed to warn persons approaching the gangway, while a vessel is moored or anchored unless it is empty and gas-freed. The sign shall state in letters not less than 2 inches high substantially as follows:

Warning

No open lights. No smoking.

No visitors.

(c) Warning sign in radio room. A sign shall be placed in radio room warning against the use of radio equipment during transfer of Grade A, B, or C liquids, except by permission of senior deck officer.

(d) [Reserved]

(e) Additional placards or signs required in connection with the movement of certain open hopper type barges are described in §35.01-45.

[CGFR 65-50, 30 FR 16704, Dec. 30, 1965, as amended by CGFR 70-143, 35 FR 19905, Dec. 30, 1970; CGD 73-96, 42 FR 49024, Sept. 26, 1977; CGD 73-243, 45 FR 18000, Mar. 20, 1980]

§35.30–5 Fires, matches, and smoking—TB/ALL.

(a) General. In making the determinations required under paragraphs (b), (c), and (d) of this section the senior deck officer on duty, who shall be a licensed officer or certificated tankerman, shall exercise his skill and experience with due regard to attendant conditions and circumstances, including consideration for location of shore side facilities, maintenance of mobility, provision for fire protection, state or change of winds, tides, sea, weather conditions, forces of nature and other circumstances generally beyond human control.

(b) Boiler fires. Boiler fires are normally permitted during cargo transfer operations: *Provided*, That prior to loading Grades A, B, and C cargoes, the senior deck officer on duty, who shall be a licensed officer or certificated tankerman, shall make an inspection to determine whether in his judgment boiler fires may be maintained with reasonable safety during the loading operation.

(c) *Smoking*. Smoking is prohibited on the weather decks of tank vessels when they are not gas free or are alongside docks. At other times and places the senior deck officer on duty, who shall be a licensed officer or certificated tankerman, shall designate when and where the crew may smoke: *Provided*, That prior to loading Grade A, B, or C cargo the master or senior deck officer on duty shall make an inspection to determine if and where, in his judgment, smoking may be permitted with reasonable safety during the loading operation.

(d) *Matches*. The use of other than safety matches is forbidden aboard tank vessels at all times.

[CGFR 65-50, 30 FR 16704, Dec. 30, 1965, as amended by CGD 95-012, 60 FR 48049, Sept. 18, 1995]

§35.30-10 Cargo tank hatches, ullage holes, and Butterworth plates—TB/ ALL.

No cargo tank hatches, ullage holes, or Butterworth plates shall be opened or shall remain open without flame screens, except under the supervision of the senior members of the crew on duty, unless the tank opened is gas free.

§35.30–15 Combustible gas indicator— TB/ALL.

(a) The provisions of this section shall apply only to United States flag vessels.

(b) Manned tank barges and tankships authorized to carry Grade A, B, C, or D liquids at any temperature, or Grade E liquids at elevated temperatures, shall be provided with a combustible gas indicator suitable for determining the presence of explosive concentrations of the cargo carried. An indicator which bears the label of Underwriters' Laboratories Inc., Factory Mutual Engineering Division, or other organizations acceptable to the Commandant will be accepted as meeting this requirement.

§35.30–20 Emergency equipment—TB/ ALL

(a) Two emergency outfits, stored for use in widely separated, accessible locations, are required for the following:(1) All tankships on international

voyage. (2) All tankships over 1,000 gross tons.