

(b) In addition to the provisions of paragraph (a) of this section, the following requirements and alternatives also apply:

(1) The American Bureau of Shipping rules relating to anchor equipment are mandatory, not a guide.

(2) Vessels under 200 feet (61 meters) in length and with an American Bureau of Shipping equipment number of less than 150 may be equipped with either—

(i) One anchor of the tabular weight and one-half the tabulated length of anchor chain listed in the applicable standard, or

(ii) Two anchors of one-half the tabular weight with the total length of anchor chain listed in the applicable standard provided both anchors are in a position that allows for ready use at all times and the windlass is capable of heaving in either anchor.

(c) Standards of other recognized classification societies may be used, in lieu of those established by the American Bureau of Shipping, upon approval by the Commandant.

[CGFR 65-50, 30 FR 16953, Dec. 30, 1965, as amended by CGD 87-013, 53 FR 20624, June 6, 1988]

§ 77.07-10 Lakes, bays, and sounds, or river service.

(a) Vessels in lakes, bays, and sounds, or river service shall be fitted with such ground tackle and hawsers as deemed necessary by the Officer in Charge, Marine Inspection, depending upon the size of the vessel and the waters on which it operates.

(b) [Reserved]

§ 77.07-90 Vessels contracted for prior to November 19, 1952.

(a) Vessels contracted for prior to November 19, 1952, shall meet the following requirements:

(1) Installations previously accepted or approved shall be considered satisfactory for the same service so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. If the service of the vessel is changed, the suitability of the equipment will be established by the Officer in Charge, Marine Inspection.

(2) [Reserved]

(b) [Reserved]

Subpart 77.09—Radar

§ 77.09-1 When required.

All mechanically propelled vessels of 1,600 gross tons and over in ocean or coastwise service must be fitted with a marine radar system for surface navigation. Facilities for plotting radar readings must be provided on the bridge.

[CGD 75-074, 42 FR 5963, Jan. 31, 1977]

Subpart 77.11—Magnetic Compass and Gyrocompass

§ 77.11-1 When required.

(a) All mechanically propelled vessels in ocean, coastwise or Great Lakes service must be fitted with a magnetic compass.

(b) All mechanically propelled vessels 1,600 gross tons and over in ocean or coastwise service must be fitted with a gyrocompass in addition to the magnetic compass.

(c) Each vessel must have an illuminated repeater for the gyrocompass required under paragraph (b) of this section, that is at the main steering stand unless the gyrocompass is illuminated and is at the main steering stand.

[CGD 75-074, 42 FR 5963, Jan. 31 1977]

Subpart 77.27—Sounding Equipment

§ 77.27-1 When required.

All mechanically propelled vessels of 500 gross tons and over to ocean or coastwise service, and all mechanically propelled vessels of 500 gross tons and over in Great Lakes service and certificated for service on the River St. Lawrence eastward of the lower exit of the St. Lambert Lock at Montreal, Canada, must be fitted with an efficient electronic deep-sea sounding apparatus.

[CGD 95-027, 61 FR 26004, May 23, 1996]

Subpart 77.30—Emergency Equipment

§ 77.30-1 Application.

This subpart, except § 77.30-90, applies to each vessel that is not on an international voyage and is contracted for