§78.30–20

Watchmen shall not be required to perform any other duties while on watch.

(d) The uniform of the night watchman shall be conspicuously different from other persons so as to be readily distinguished. A rating badge marked "Watchman" shall be worn on the left sleeve and the front of the cap shall also be marked "Watchman".

(e) The watchman shall have in his possession at all time while on duty an efficient flashlight.

§78.30–20 Master's and officer's responsibility.

(a) Nothing in this part shall exonerate any master or officer in command from the consequences of any neglect to keep a proper lookout or to maintain a proper fire watch or from any neglect of any precaution which may be required by the ordinary practice of seamen or by the special circumstances of the case. When circumstances require it, additional watches shall be maintained to guard against fire or other danger and to give an alarm in case of accident or disaster.

(b) [Reserved]

Subpart 78.33—Reports of Accidents, Repairs, and Unsafe Equipment

§78.33–1 Repairs of boiler and pressure vessels.

(a) Before making any repairs to boilers or unfired pressure vessels, the chief engineer shall submit a report covering the nature of the repairs to the Officer in Charge, Marine Inspection, at or nearest the port where the repairs are to be made.

(b) [Reserved]

§78.33–5 Accidents to machinery.

(a) In the event of an accident to a boiler, unfired pressure vessel, or machinery tending to render the further use of the item unsafe until repairs are made, or if by ordinary wear such items become unsafe, a report shall be made by the chief engineer immediately to the Officer in Charge, Marine Inspection, or if at sea, immediately upon arrival at port.

(b) [Reserved]

46 CFR Ch. I (10–1–13 Edition)

§78.33–10 Notice required before repairs.

(a) No repairs or alterations, except in an emergency, shall be made to any lifesaving or fire detecting or extinguishing equipment without advance notice to the Officer in Charge, Marine Inspection. When emergency repairs or alterations have been made, notice shall be given to the Officer in Charge, Marine Inspection, as soon as practicable.

(b) [Reserved]

Subpart 78.35—Communication Between Deckhouses

§78.35-1 When required.

On all vessels navigating in other than protected waters, where the distance between deckhouses is more than 46 meters (150 feet) a fixed means of facilitating communication between both ends of the vessel, such as a raised fore and aft bridge or side tunnels, must be provided. Previously approved arrangements may be retained so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection.

[CGD 95-027, 61 FR 26004, May 23, 1996]

Subpart 78.36—Work Vests

§78.36–1 Application.

(a) Provisions of this subpart shall apply to all vessels inspected and certificated in accordance with this subchapter.

(b) [Reserved]

§78.36–5 Approved types of work vests.

(a) Each buoyant work vest carried under the permissive authority of this section must be approved under—

(1) Subpart $160.\overline{053}$ of this chapter; or

(2) Subpart 160.077 of this chapter as a commercial hybrid PFD.

(b) [Reserved]

[CGD 78-174A, 51 FR 4350, Feb. 4, 1986]

§78.36-10 Use.

(a) Approved buoyant work vests are considered to be items of safety apparel and may be carried aboard vessels to be worn by crew members when