Coast Guard, DHS

as 98.30-11 and a new 98.30-8 was added, effective Dec. 5, 2013. For the convenience of the user, the added text is set forth as follows:

§98.30–8 Materials authorized for transfer to and from an IBC.

Any hazardous material listed in Table 98.30-7(a) of §98.30-7 may be transferred to and from an IBC under this subpart, with the exception of Liquid Nitrogen.

§98.30-9 Stowage of portable tanks.

(a) No person may operate a vessel to which this subpart applies unless each portable tank is stowed on an open deck.

(b) No person may stow a portable tank—

(1) In the vicinity of another tank that contains a chemically incompatible product; and

(2) Unless all electrical equipment is explosion-proof or intrinsically safe, as defined in §§111.105–9 and 111.105–11 of this chapter, in the area of the tank and its associated equipment that is—

(i) Within 10 feet in any horizontal direction; and

(ii) Within 8 feet above the deck.

[CGD 73-172, 39 FR 22954, June 25, 1974, as amended by CGD 84-043, 55 FR 37412, Sept. 11, 1990; 55 FR 47477, Nov. 14, 1990]

EFFECTIVE DATE NOTES: 1. By 78 FR 54785, 54786, Sept. 6, 2013, §98.30-9 was redesignated as §98.30-12 and by revising the newly redesginated §98.30-9, effective Dec. 5, 2013. For the convenience of the user, the revised text is set forth as follows:

§98.30–9 Lifting a portable tank or IBC.

(a) No person may lift a portable tank and/ or IBC with another portable tank and/or IBC.

(b) All lifting requirements for IBCs must be followed in accordance with 49 CFR 178.704(c) and (f).

2. At 78 FR 54787, Sept. 6, 2013, newly redesignated §98.30-12 was amended by revising the section heading, in paragraph (a), after the words "portable tank", add the words "and/or IBC", in paragraph (b) introductory text, after the words "portable tank", add the words "and/or IBC"; and adding a new paragraph (c), effective Dec. 5, 2013. For the convenience of the user, the added text is set forth as follows:

 $\$98.30{-}12$ Stowage of portable tanks and IBCs.

* * * * *

(c) All IBCs must be secured as specified in $49\ \mathrm{CFR}$ 176.74.

§98.30–10 Pipe connections, and filling and discharge openings.

No person may transfer a hazardous material to or from a portable tank on board a vessel, unless each filling and discharge opening in the tank bottom is equipped with the following:

(a) For an IM 101 or IM 102 portable tank, the closures specified in 49 CFR 173.32c(g)(2); and

(b) For an MPT, the valves and closures specified in §§ 64.33 through 64.41 of this chapter.

[CGD 84-043, 55 FR 37412, Sept. 11, 1990]

EFFECTIVE DATE NOTES: 1. At 78 FR 54785, Sept. 6, 2013, \$98.30-10 was redesignated as \$98.30-13, effective Dec. 5, 2013.

2. At 54787, Sept. 6, 2013, in newly redesignated §98.30-10, after the words "portable tank", add the words "or IBC".

§98.30–11 Cargo pumps.

No person may operate a cargo pump to transfer a product to or from a portable tank unless the pump is installed—

(a) Above deck; or

(b) Below deck, in conformance with subpart 32.60 of this chapter.

EFFECTIVE DATE NOTES: 1. By 78 FR 54785, Sept. 6, 2013, §98.30–11 was redesignated as §98.30–14, effective Dec. 5, 2013.

2. At 54787, §98.30-11, was amended by removing the words "on board" and adding, in their place, the word "onboard", effective Dec. 5, 2013.

§98.30–13 Ground connection.

No person may transfer an inflammable or combustible product to or from a vessel unless—

(a) The portable tank and its pumping equipment is electrically grounded to the hull of the vessel; and

(b) The vessel is electrically grounded to an offshore platform, shore piping, or another vessel by a—

(1) Cargo hose constructed with an integral grounding wire if the end connections are used for electrical continuity; or

(2) Separate grounding that is maintained until the cargo hose is disconnected and drained.