

§ 590.506

Administrator to prevent product contamination and in accordance with acceptable environmental protection practices.

[36 FR 9814, May 28, 1971, as amended at 37 FR 6658, Apr. 1, 1972; 40 FR 20059, May 8, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 47 FR 745, Jan. 7, 1982; 60 FR 49170, Sept. 21, 1995]

§ 590.506 Candling and transfer-room facilities and equipment.

(a) The room shall be so constructed that it can be adequately darkened to assure accuracy in removal of inedible or loss eggs by candling. Equipment shall be arranged so as to facilitate cleaning and the removal of refuse and excess packing material.

(b) The construction of the floor shall allow thorough cleaning. The floors shall be of water-resistant composition and provided with proper drainage.

(c) An approved exhaust system shall be provided for the continuous removal directly to the outside of any steam, vapors, odors, or dust in the room. The room shall be maintained at reasonable working temperatures during operations.

(d) Candling devices of an approved type shall be provided to enable candlers to detect loss, inedible, dirty eggs, and eggs other than chicken eggs.

(e) Leaker trays shall be made of a material and of such design that is conducive to easy cleaning and sanitizing.

(f) Containers made of a material and of such design that are conducive to easy cleaning shall be provided for inedible eggs. All such containers shall be conspicuously marked.

(g) Containers made of a material and of such design that are conducive to easy cleaning shall be provided for trash unless clean, disposable containers are furnished daily.

(h) Shell egg conveyors shall be constructed so that they can be thoroughly cleaned.

[36 FR 9814, May 28, 1971, as amended at 37 FR 6659, Apr. 1, 1972. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 60 FR 49170, Sept. 21, 1995]

9 CFR Ch. III (1–13 Edition)

§ 590.508 Candling and transfer-room operations.

(a) Candling and transfer rooms and equipment shall be kept clean, free from cobwebs, dust, objectionable odors, and excess packing materials.

(b) Containers for trash and inedible eggs shall be removed from the candling rooms as often as necessary but at least once daily; and shall be cleaned and treated in such a manner as will prevent off odors or objectionable conditions in the plant.

(c) Shell eggs shall be handled in a manner to minimize sweating prior to breaking.

(d) Shell eggs with extensively damaged shells, unless prohibited under § 590.510(d), shall be placed into leaker trays and shall be broken promptly.

§ 590.510 Classifications of shell eggs used in the processing of egg products.

(a) The shell eggs shall be sorted and classified into the following categories in a manner approved by the National Supervisor:

(1) Eggs listed in paragraph (d) of this section.

(2) Dirty.

(3) Leakers as described in paragraph (c)(2) of this section.

(4) Eggs from other than chicken; duck, turkey, guinea, and goose eggs.

(5) Other eggs—satisfactory for use as breaking stock.

(b) Shell eggs having strong odors or eggs received in cases having strong odors shall be candled and broken separately to determine their acceptability.

(c) Shell eggs, when presented for breaking, shall be of edible interior quality and the shell shall be sound and free of adhering dirt and foreign material, except that:

(1) Checks and eggs with a portion of the shell missing may be used when the shell is free of adhering dirt and foreign material and the shell membranes are not ruptured.

(2) Eggs with clean shells which are damaged in candling and/or transfer and have a portion of the shell and shell membranes missing may be used only when the yolk is unbroken and the contents of the egg are not exuding over the outside shell. Such eggs shall