

equipment left behind, and atmosphere, monitored if necessary prior to re-entering and resuming work. In an oxygen-enriched atmosphere, the flammable range is severely broadened. This means that an oxygen-enriched atmosphere can promote very rapid burning.

6. *Ballasting or trimming.* Changing the position of the ballast, or trimming or in any way moving the vessel so as to expose cargo that had been previously trapped, can produce a change in the atmosphere of the tank. The atmosphere should be retested after any such move and prior to entry or work.

Section 1915.14 (a) and (b) Hot work. This is a reminder that other sections of the OSHA shipyard safety and health standards in part 1915 should be reviewed prior to starting any hot work. Most notably, subpart D, Welding, Cutting and Heating, places additional restrictions on hot work. The requirements of §§1915.51 and 1915.53 must be met before hot work is begun on any metal that is toxic or is covered by a preservative coating respectively; the requirements of §1915.54 must be met before welding, cutting, or heating is begun on any hollow containers or structures not covered by §1915.12.

Section 1915.12(a)(2). During hot work, more than 20.8 percent oxygen by volume can be unsafe since it extends the normal flammable range. The standard permits the oxygen level to reach 22 percent by volume in order to account for instrument error. However, the cause of excess oxygen should be investigated and the source removed.

Section 1915.16(b). If the entire vessel has been found to be in the same condition, then employers shall be considered to be in compliance with this requirement when signs using appropriate warning language in accordance with §1915.16(a) are posted at the gangway and at all other means of access to the vessel.

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44541, July 3, 2002; 76 FR 33609, June 8, 2011]

APPENDIX B TO SUBPART B OF PART 1915—REPRINT OF U.S. COAST GUARD REGULATIONS REFERENCED IN SUBPART B, FOR DETERMINATION OF COAST GUARD AUTHORIZED PERSONS

This appendix provides a complete reprint of U.S. Coast Guard regulations as of October 1, 1993, referenced in subpart B for purposes of determining who is a Coast Guard authorized person.

1. Title 46 CFR 35.01–1 (a) through (c) covering hot work on tank vessels reads as follows:

(a) The provisions of “Standard for the Control of Gas Hazards on Vessels to be Re-

paired,” NFPA No. 306, published by National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, shall be used as a guide in conducting the inspections and issuance of certificates required by this section.

(b) Until an inspection has been made to determine that such operation can be undertaken with safety, no alterations, repairs, or other such operations involving riveting, welding, burning, or like fire-producing actions shall be made:

(1) Within or on the boundaries of cargo tanks that have been used to carry flammable or combustible liquid or chemicals in bulk, or within spaces adjacent to such cargo tanks; or

(2) Within or on the boundaries of fuel tanks; or

(3) To pipe lines, heating coils, pumps, fittings, or other appurtenances connected to such cargo or fuel tanks.

(c) Such inspections shall be made and evidenced as follows:

(1) In ports or places in the United States or its territories and possessions, the inspection shall be made by a Marine Chemist certificated by the National Fire Protection Association; however, if the services of such certified Marine Chemists are not reasonably available, the Officer in Charge, Marine Inspection, upon the recommendation of the vessel owner and his contractor or their representative, shall select a person who, in the case of an individual vessel, shall be authorized to make such inspection. If the inspection indicates that such operations can be undertaken with safety, a certificate setting forth the fact in writing and qualified as may be required, shall be issued by the certified Marine Chemist or the authorized person before the work is started. Such qualifications shall include any requirements as may be deemed necessary to maintain, insofar as can reasonably be done, the safe conditions in the spaces certified, throughout the operation and shall include such additional tests and certifications as considered required. Such qualifications and requirements shall include precautions necessary to eliminate or minimize hazards that may be present from protective coatings or residues from cargoes.

2. Title 46 CFR 71.60(c)(1) covering hot work on passenger vessels reads as follows:

(a) The provisions of “Standard for the Control of Gas Hazards on Vessels to be Repaired,” NFPA No. 306, published by National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, shall be used as a guide in conducting the inspections and issuance of certificates required by this section.

(b) Until an inspection has been made to determine that such operation can be undertaken with safety, no alterations, repairs, or other such operations involving riveting,

welding, burning, or like fire-producing actions shall be made:

(1) Within or on the boundaries of cargo tanks which have been used to carry flammable or combustible liquid or chemicals in bulk, or within spaces adjacent to such cargo tanks; or

(2) Within or on the boundaries of fuel tanks; or

(3) To pipe lines, heating coils, pumps, fittings, or other appurtenances connected to such cargo or fuel tanks.

(c) Such inspections shall be made and evidenced as follows:

(1) In ports or places in the United States or its territories and possessions the inspection shall be made by a Marine Chemist certificated by the National Fire Protection Association; however, if the services of such certified Marine Chemist are not reasonably available, the Officer in Charge, Marine Inspection, upon the recommendation of the vessel owner and his contractor or their representative, shall select a person who, in the case of an individual vessel, shall be authorized to make such inspection. If the inspection indicated that such operations can be undertaken with safety, a certificate setting forth the fact in writing and qualified as may be required, shall be issued by the certified Marine Chemist or the authorized person before the work is started. Such qualifications shall include any requirements as may be deemed necessary to maintain, insofar as can reasonably be done, the safe conditions in the spaces certified throughout the operation and shall include such additional tests and certifications as considered required. Such qualifications and requirements shall include precautions necessary to eliminate or minimize hazards that may be present from protective coatings or residues from cargoes.

3. Title 46 CFR 91.50-1(c)(1) covering hot work on cargo and miscellaneous vessels as follows:

(a) The provisions of "Standard for the Control of Gas Hazards on Vessels to be Repaired," NFPA No. 306, published by National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, shall be used as a guide in conducting the inspections and issuance of certificates required by this section.

(b) Until an inspection has been made to determine that such operation can be undertaken with safety, no alterations, repairs, or other such operations involving riveting, welding, burning, or like fire-producing actions shall be made:

(1) Within or on the boundaries of cargo tanks which have been used to carry flammable or combustible liquid or chemicals in bulk, or within spaces adjacent to such cargo tanks; or,

(2) Within or on the boundaries of fuel tanks; or,

(3) To pipe lines, heating coils, pumps, fittings, or other appurtenances connected to such cargo or fuel tanks.

(c) Such inspections shall be made and evidenced as follows:

(1) In ports or places in the United States or its territories and possessions the inspection shall be made by a Marine Chemist certificated by the National Fire Protection Association; however, if the services of such certified Marine Chemist are not reasonably available, the Officer in Charge, Marine Inspection, upon the recommendation of the vessel owner and his contractor or their representative, shall select a person who, in the case of an individual vessel, shall be authorized to make such inspection. If the inspection indicated that such operations can be undertaken with safety, a certificate setting forth the fact in writing and qualified as may be required, shall be issued by the certified Marine Chemist or the authorized person before the work is started. Such qualifications shall include any requirements as may be deemed necessary to maintain, insofar as can reasonably be done, the safe conditions in the spaces certified throughout the operation and shall include such additional tests and certifications as considered required. Such qualifications and requirements shall include precautions necessary to eliminate or minimize hazards that may be present from protective coatings or residues from cargoes.

Subpart C—Surface Preparation and Preservation

§ 1915.31 Scope and application of subpart.

The standards contained in this subpart shall apply to ship repairing and shipbuilding and shall not apply to shipbreaking.

§ 1915.32 Toxic cleaning solvents.

(a) When toxic solvents are used, the employer shall employ one or more of the following measures to safeguard the health of employees exposed to these solvents.

(1) The cleaning operation shall be completely enclosed to prevent the escape of vapor into the working space.

(2) Either natural ventilation or mechanical exhaust ventilation shall be used to remove the vapor at the source and to dilute the concentration of vapors in the working space to a concentration which is safe for the entire work period.