

§ 1917.157

29 CFR Ch. XVII (7-1-14 Edition)

§ 1917.157 Battery charging and changing.

- (a) Only designated persons shall change or charge batteries.
- (b) Battery charging and changing shall be performed only in areas designated by the employer.
- (c) Smoking and other ignition sources are prohibited in charging areas.
- (d) Filler caps shall be in place when batteries are being moved.
- (e) Parking brakes shall be applied before batteries are charged or changed.
- (f) When a jumper battery is connected to a battery in a vehicle, the ground lead shall connect to ground away from the vehicle's battery. Ignition, lights and accessories on the vehicle shall be turned off before connections are made.
- (g) Batteries shall be free of corrosion buildup and cap vent holes shall be open.
- (h) Adequate ventilation shall be provided during charging.
- (i) Facilities for flushing the eyes, body and work area with water shall be provided wherever electrolyte is handled, except that this requirement does not apply when employees are only checking battery electrolyte levels or adding water.

- (j) Carboy tilters or siphons shall be used to handle electrolyte in large containers.
- (k) Battery handling equipment which could contact battery terminals or cell connectors shall be insulated or otherwise protected.
- (l) Metallic objects shall not be placed on uncovered batteries.
- (m) When batteries are being charged, the vent caps shall be in place.
- (n) Chargers shall be turned off when leads are being connected or disconnected.
- (o) Installed batteries shall be secured to avoid physical or electrical contact with compartment walls or components.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40202, July 25, 1997]

§ 1917.158 Prohibited operations.

- (a) Spray painting and abrasive blasting operations shall not be conducted in the vicinity of cargo handling operations.
- (b) Welding and burning operations shall not be conducted in the vicinity of cargo handling operations unless such hot work is part of the cargo operation.

APPENDIX I TO PART 1917—SPECIAL CARGO GEAR AND CONTAINER SPREADER TEST REQUIREMENTS (MANDATORY) [SEE § 1917.50(c)(5)]

Type gear	Test requirement	Tested by	Proof test	
A. All Special Cargo Handling Gear Purchased or Manufactured on or After January 21, 1998				
1. Safe Working Load—greater than 5 short tons (10,000 lbs./4.5 metric tons).	Prior to initial use	OSHA accredited agency only	Up to 20 short tons.	125% SWL
	Prior to reuse after structural damage repair		From 20 to 50 short tons	5 short tons in excess of SWL
	Every four years after initial proof load test	OSHA accredited agency or designated person (40)(1) 125% SWL	Over 50 short tons	110% SWL
2. Safe Working Load—5 short tons or less.	Prior to initial use Prior to reuse after structural damage repair	OSHA accredited agency or designated person	125% SWL	

3. Intermodal container spreaders not part of vessel's cargo handling gear.	Prior to initial use			
	Prior to reuse after structural damage repair Every four years after initial proof load test.	OSHA accredited agency only OSHA accredited agency or designated person.		125% SWL
B. All Special Cargo Handling Gear in Use Prior to January 21, 1998				
1. Any Safe Working Load.	Every four years starting on January 21, 1998.	OSHA accredited agency or designated person.	Up to 20 short tons.	5 short tons in excess of SWL 110% SWL
	Prior to initial use or prior to reuse after structural damage repair	OSHA accredited agency	From 20 to 50 short tons Over 50 short tons	
2. Intermodal container spreaders not part of ship's gear.	Every four years starting on January 21, 1998	OSHA accredited agency or designated person		125% SWL
	Prior to initial use or prior to reuse after structural damage repair	OSHA accredited agency		

[65 FR 40943, June 30, 2000]

PART 1918—SAFETY AND HEALTH REGULATIONS FOR LONGSHORING

Subpart A—General Provisions

- Sec.
 1918.1 Scope and application.
 1918.2 Definitions.
 1918.3 Incorporation by reference
 1918.4 OMB control numbers under the Paperwork Reduction Act.
 1918.5 Compliance duties owed to each employee.

Subpart B—Gear Certification

- 1918.11 Gear certification (See also §§ 1918.2, definition of "Vessel's cargo handling gear" and 1918.51).

Subpart C—Gangways and Other Means of Access

- 1918.21 General requirements.
 1918.22 Gangways.
 1918.23 Jacob's ladders.
 1918.24 Fixed and portable ladders.
 1918.25 Bridge plates and ramps (See also § 1918.86).
 1918.26 Access to barges and river towboats.

Subpart D—Working Surfaces

- 1918.31 Hatch coverings.
 1918.32 Stowed cargo and temporary landing surfaces.

- 1918.33 Deck loads.
 1918.34 Other decks.
 1918.35 Open hatches.
 1918.36 Weather deck rails.
 1918.37 Barges.

Subpart E—Opening and Closing Hatches

- 1918.41 Coaming clearances.
 1918.42 Hatch beam and pontoon bridles.
 1918.43 Handling hatch beams and covers.

Subpart F—Vessel's Cargo Handling Gear

- 1918.51 General requirements (See also § 1918.11 and appendix III of this part).
 1918.52 Specific requirements.
 1918.53 Cargo winches.
 1918.54 Rigging gear.
 1918.55 Cranes (See also § 1918.11).

Subpart G—Cargo Handling Gear and Equipment Other Than Ship's Gear

- 1918.61 General (See also appendix IV of this part).
 1918.62 Miscellaneous auxiliary gear.
 1918.63 Chutes, gravity conveyors and rollers.
 1918.64 Powered conveyors.
 1918.65 Mechanically-powered vehicles used aboard vessels.
 1918.66 Cranes and derricks other than vessel's gear.
 1918.67 Notifying ship's officers before using certain equipment.
 1918.68 Grounding.
 1918.69 Tools.
 1918.70–1918.80 [Reserved]