29 CFR citation	OMB con- trol No.
1915.502(b)	1218-0248
1915.502(c)	1218-0248
1915.502(d)	1218-0248
1915.504(a)	1218-0248
1915.505(a)	1218-0248
1915.505(b)1915.505(d)	1218-0248 1218-0248
1915.506(b)	1218-0248
1915.507(c)	1218-0248
1915.508(a)	1218-0248
1915.508(b)	1218-0248
1915.508(c)	1218-0248
1915.508(d)	1218-0248
1915.508(e)	1218-0248
1915.508(f)	1218-0248
1915.1001	1218-0195
1915.1003	1218-0085
1915.1004	1218-0084
1915.1006	1218-0086
1915.1007 1915.1008	1218-0083 1218-0087
1915.1008	1218-0087
1915.1010	1218-0082
1915.1011	1218-0090
1915.1012	1218-0080
1915.1013	1218-0079
1915.1014	1218-0088
1915.1015	1218-0044
1915.1016	1218–0081
1915.1017	1218-0010
1915.1018	1218-0104
1915.1025 1915.1026	1218-0092 1218-0252
1915.1026	1218-0252
1915.1027	1218-0103
1915.1020	1218-0180
1915.1044	1218-0101
1915.1045	1218-0126
1915.1047	1218-0108
1915.1048	1218-0145
1915.1050	1218-0184
1915.1120	1218-0065
1915.1200	1218-0072
1915.1450	1218–0131

[61 FR 5509, Feb. 13, 1996, as amended at 62 FR 33547, June 20, 1997; 63 FR 13340, Mar. 19, 1998; 70 FR 13371, Mar. 21, 2005; 71 FR 38086, July 5, 2006; 77 FR 19, Jan. 3, 2012]

§ 1915.9 Compliance duties owed to each employee.

(a) Personal protective equipment. Standards in this part requiring the employer to provide personal protective equipment (PPE), including respirators and other types of PPE, because of hazards to employees impose a separate compliance duty with respect to each employee covered by the requirement. The employer must provide PPE to each employee required to use the PPE, and each failure to provide PPE to an employee may be considered a separate violation.

(b) Training. Standards in this part requiring training on hazards and re-

lated matters, such as standards requiring that employees receive training or that the employer train employees, provide training to employees, or institute or implement a training program, impose a separate compliance duty with respect to each employee covered by the requirement. The employer must train each affected employee in the manner required by the standard, and each failure to train an employee may be considered a separate violation.

[73 FR 75587, Dec. 12, 2008]

Subpart B—Confined and Enclosed Spaces and Other Dangerous Atmospheres in Shipyard Employment

Source: 59 FR 37857, July 25, 1994, unless otherwise noted.

§ 1915.11 Scope, application and definitions applicable to this subpart.

(a) Scope and application. This subpart applies to work in confined and enclosed spaces and other dangerous atmospheres in shipyard employment, including vessels, vessel sections, and on land-side operations regardless of geographic location.

(b) Definitions applicable to this subpart. Adjacent spaces means those spaces bordering a subject space in all directions, including all points of contact, corners, diagonals, decks, tank tops, and bulkheads.

Assistant Secretary means the Assistant Secretary of Labor for Occupational Safety and Health, or designated representative.

Certified Industrial Hygienist (CIH) means an industrial hygienist who is certified by the American Board of Industrial Hygiene.

Coast Guard authorized person means an individual who meets the requirement of appendix B to subpart B of this part 1915 for tank vessels, for passenger vessels, and for cargo and miscellaneous vessels.

Dangerous atmosphere means an atmosphere that may expose employees to the risk of death, incapacitation, impairment of ability to self-rescue (i.e., escape unaided from a confined or

§ 1915.11

enclosed space), injury, or acute illness.

Director means the Director of the National Institute for Occupational Safety and Health, U.S. Department of Health and Human Services, or designated representative.

Enter with Restrictions denotes a space where entry for work is permitted only if engineering controls, personal protective equipment, clothing, and time limitations are as specified by the Marine Chemist, Certified Industrial Hygienist, or the shipyard competent person.

Entry means the action by which a person passes through an opening into a space. Entry includes ensuing work activities in that space and is considered to have occurred as soon as any part of the entrant's body breaks the plane of an opening into the space.

Hot work means any activity involving riveting, welding, burning, the use of powder-actuated tools or similar fire-producing operations. Grinding, drilling, abrasive blasting, or similar spark-producing operations are also considered hot work except when such operations are isolated physically from any atmosphere containing more than 10 percent of the lower explosive limit of a flammable or combustible substance.

Immediately dangerous to life or health (IDLH) means an atmosphere that poses an immediate threat to life or that is likely to result in acute or immediate severe health effects.

Inert or inerted atmosphere means an atmospheric condition where:

- (1) The oxygen content of the atmosphere in the space is maintained at a level equal to or less than 8.0 percent by volume or at a level at or below 50 percent of the amount required to support combustion, whichever is less; or
- (2) The space is flooded with water and the vapor concentration of flammable or combustible materials in the free space atmosphere above the water line is less than 10 percent of the lower explosive limit for the flammable or combustible material.

Labeled means identified with a sign, placard, or other form of written communication, including pictograms, that provides information on the status or

condition of the work space to which it is attached.

Lower explosive limit (LEL) means the minimum concentration of vapor in air below which propagation of a flame does not occur in the presence of an ignition source.

Marine Chemist means an individual who possesses a current Marine Chemist Certificate issued by the National Fire Protection Association.

Not Safe for Hot Work denotes a space where hot work may not be performed because the conditions do not meet the criteria for Safe for Hot Work.

Nationally Recognized Testing Laboratory (NRTL) means an organization recognized by OSHA, in accordance with appendix A of 29 CFR 1910.7, which tests for safety and lists or labels or accepts equipment and materials that meet all the criteria found in § 1910.7(b)(1) through (b)(4)(ii).

Not Safe for Workers denotes a space where an employee may not enter because the conditions do not meet the criteria for Safe for Workers.

Oxygen-deficient atmosphere means an atmosphere having an oxygen concentration of less than 19.5 percent by volume.

Oxygen-enriched atmosphere means an atmosphere that contains 22.0 percent or more oxygen by volume.

Safe for Hot Work denotes a space that meets all of the following criteria:

- (1) The oxygen content of the atmosphere does not exceed 22.0 percent by volume:
- (2) The concentration of flammable vapors in the atmosphere is less than 10 percent of the lower explosive limit;
- (3) The residues or materials in the space are not capable of producing a higher concentration than permitted in paragraph (1) or (2) of the above, under existing atmospheric conditions in the presence of hot work and while maintained as directed by the Marine Chemist or competent person, and
- (4) All adjacent spaces have been cleaned, or inerted, or treated sufficiently to prevent the spread of fire.

Safe for Workers denotes a space that meets the following criteria:

(1) The oxygen content of the atmosphere is at least 19.5 percent and below 22 percent by volume;

- (2) The concentration of flammable vapors is below 10 percent of the lower explosive limit (LEL);
- (3) Any toxic materials in the atmosphere associated with cargo, fuel, tank coatings, or inerting media are within permissible concentrations at the time of the inspection; and
- (4) Any residues or materials associated with the work authorized by the Marine Chemist, Certified Industrial Hygienist, or competent person will not produce uncontrolled release of toxic materials under existing atmospheric conditions while maintained as directed.

Space means an area on a vessel or vessel section or within a shipyard such as, but not limited to: cargo tanks or holds; pump or engine rooms; storage lockers; tanks containing flammable or combustible liquids, gases, or solids; rooms within buildings; crawl spaces; tunnels; or accessways. The atmosphere within a space is the entire area within its bounds.

Upper explosive limit (UEL) means the maximum concentration of flammable vapor in air above which propagation of flame does not occur on contact with a source of ignition.

Vessel section means a sub-assembly, module, or other component of a vessel being built, repaired, or broken.

Visual inspection means the physical survey of the space, its surroundings and contents to identify hazards such as, but not limited to, restricted accessibility, residues, unguarded machinery, and piping or electrical systems.

§1915.12 Precautions and the order of testing before entering confined and enclosed spaces and other dangerous atmospheres.

The employer shall ensure that atmosphereic testing is performed in the following sequence: oxygen content, flammability, toxicity.

- (a) Oxygen content. (1) The employer shall ensure that the following spaces are visually inspected and tested by a competent person to determine the atmosphere's oxygen content prior to initial entry into the space by an employee:
- (i) Spaces that have been sealed, such as, but not limited to, spaces that have been coated and closed up, and non-

ventilated spaces that have been freshly painted;

- (ii) Spaces and adjacent spaces that contain or have contained combustible or flammable liquids or gases;
- (iii) Spaces and adjacent spaces that contain or have contained liquids, gases, or solids that are toxic, corrosive, or irritant:
- (iv) Spaces and adjacent spaces that have been fumigated; and
- (v) Spaces containing materials or residues of materials that create an oxygen-deficient atmosphere.
- (2) If the space to be entered contains an oxygen deficient atmosphere, the space shall be labeled "Not Safe for Workers" or, if oxygen-enriched, "Not Safe for Workers—Not Safe for Hot Work." If an oxygen-deficient or oxygen-enriched atmosphere is found, ventilation shall be provided at volumes and flow rates sufficient to ensure that the oxygen content is maintained at or above 19.5 percent and below 22.0 percent by volume. The warning label may be removed when the oxygen content is equal to or greater than 19.5 and less than 22.0 percent by volume.
- (3) An employee may not enter a space where the oxygen content, by volume, is below 19.5 percent or above 22.0 percent. Exception: An employee may enter for emergency rescue or for a short duration for installation of ventilation equipment necessary to start work in the space provided:
- (i) The atmosphere in the space is monitored for oxygen content, by volume, continuously; and
- (ii) Respiratory protection and other appropriate personal protective equipment and clothing are provided in accordance with subpart I of this part.

NOTE TO PARAGRAPH (a): Other provisions for work in IDLH atmospheres are located in subpart I of this part.

- (b) Flammable atmospheres. (1) The employer shall ensure that spaces and adjacent spaces that contain or have contained combustible or flammable liquids or gases are:
- (i) Inspected visually by the competent person to determine the presence of combustible or flammable liquids; and