



2. All other sloped excavations shall be in accordance with the other options permitted in §1926.652(b).

APPENDIX C TO SUBPART P OF PART 1926—TIMBER SHORING FOR TRENCHES

(a) *Scope.* This appendix contains information that can be used timber shoring is provided as a method of protection from cave-ins in trenches that do not exceed 20 feet (6.1 m) in depth. This appendix must be used when design of timber shoring protective systems is to be performed in accordance with §1926.652(c)(1). Other timber shoring configurations; other systems of support such as hydraulic and pneumatic systems; and other protective systems such as sloping, benching, shielding, and freezing systems must be designed in accordance with the requirements set forth in §1926.652(b) and §1926.652(c).

(b) *Soil Classification.* In order to use the data presented in this appendix, the soil type or types in which the excavation is made must first be determined using the soil classification method set forth in appendix A of subpart P of this part.

(c) *Presentation of Information.* Information is presented in several forms as follows:

(1) Information is presented in tabular form in Tables C-1.1, C-1.2, and C-1.3, and Tables C-2.1, C-2.2 and C-2.3 following paragraph (g) of the appendix. Each table presents the minimum sizes of timber members to use in a shoring system, and each table contains data only for the particular soil type in which the excavation or portion of

the excavation is made. The data are arranged to allow the user the flexibility to select from among several acceptable configurations of members based on varying the horizontal spacing of the crossbraces. Stable rock is exempt from shoring requirements and therefore, no data are presented for this condition.

(2) Information concerning the basis of the tabular data and the limitations of the data is presented in paragraph (d) of this appendix, and on the tables themselves.

(3) Information explaining the use of the tabular data is presented in paragraph (e) of this appendix.

(4) Information illustrating the use of the tabular data is presented in paragraph (f) of this appendix.

(5) Miscellaneous notations regarding Tables C-1.1 through C-1.3 and Tables C-2.1 through C-2.3 are presented in paragraph (g) of this Appendix.

(d) *Basis and limitations of the data*—(1) *Dimensions of timber members.* (i) The sizes of the timber members listed in Tables C-1.1 through C-1.3 are taken from the National Bureau of Standards (NBS) report, "Recommended Technical Provisions for Construction Practice in Shoring and Sloping of Trenches and Excavations." In addition, where NBS did not recommend specific sizes of members, member sizes are based on an analysis of the sizes required for use by existing codes and on empirical practice.

(ii) The required dimensions of the members listed in Tables C-1.1 through C-1.3 refer to actual dimensions and not nominal dimensions of the timber. Employers wanting to use nominal size shoring are directed to Tables C-2.1 through C-2.3, or have this choice under §1926.652(c)(3), and are referred to The Corps of Engineers, The Bureau of Reclamation or data from other acceptable sources.

(2) *Limitation of application.* (i) It is not intended that the timber shoring specification apply to every situation that may be experienced in the field. These data were developed to apply to the situations that are most commonly experienced in current trenching practice. Shoring systems for use in situations that are not covered by the data in this appendix must be designed as specified in §1926.652(c).

(ii) When any of the following conditions are present, the members specified in the tables are not considered adequate. Either an alternate timber shoring system must be designed or another type of protective system designed in accordance with §1926.652.

(A) When loads imposed by structures or by stored material adjacent to the trench weigh in excess of the load imposed by a two-foot soil surcharge. The term "adjacent" as used here means the area within a horizontal distance from the edge of the trench equal to the depth of the trench.

(B) When vertical loads imposed on cross braces exceed a 240-pound gravity load distributed on a one-foot section of the center of the crossbrace.

(C) When surcharge loads are present from equipment weighing in excess of 20,000 pounds.

(D) When only the lower portion of a trench is shored and the remaining portion of the trench is sloped or benched unless: The sloped portion is sloped at an angle less steep than three horizontal to one vertical; or the members are selected from the tables for use at a depth which is determined from the top of the overall trench, and not from the toe of the sloped portion.

(e) *Use of Tables.* The members of the shoring system that are to be selected using this information are the cross braces, the uprights, and the wales, where wales are required. Minimum sizes of members are specified for use in different types of soil. There are six tables of information, two for each soil type. The soil type must first be determined in accordance with the soil classification system described in appendix A to subpart P of part 1926. Using the appropriate table, the selection of the size and spacing of the members is then made. The selection is based on the depth and width of the trench where the members are to be installed and, in most instances, the selection is also based on the horizontal spacing of the crossbraces. Instances where a choice of horizontal spacing of crossbracing is available, the horizontal spacing of the crossbraces must be chosen by the user before the size of any member can be determined. When the soil type, the width and depth of the trench, and the horizontal spacing of the crossbraces are known, the size and vertical spacing of the crossbraces, the size and vertical spacing of the wales, and the size and horizontal spacing of the uprights can be read from the appropriate table.

(f) *Examples to Illustrate the Use of Tables C-1.1 through C-1.3.*

(1) *Example 1.*

A trench dug in Type A soil is 13 feet deep and five feet wide.

From *Table C-1.1*, for acceptable arrangements of timber can be used.

Arrangement #B1

Space 4x4 crossbraces at six feet horizontally and four feet vertically.

Wales are not required.

Space 3x8 uprights at six feet horizontally. This arrangement is commonly called "skip shoring."

Arrangement #B2

Space 4x6 crossbraces at eight feet horizontally and four feet vertically.

Space 8x8 wales at four feet vertically.

Pt. 1926, Subpt. P, App. C

29 CFR Ch. XVII (7–1–14 Edition)

Space 2×6 uprights at four feet horizontally.

Arrangement #B3

Space 6×6 crossbraces at 10 feet horizontally and four feet vertically.

Space 8×10 wales at four feet vertically.

Space 2×6 uprights at five feet horizontally.

Arrangement #B4

Space 6×6 crossbraces at 12 feet horizontally and four feet vertically.

Space 10×10 wales at four feet vertically.

Spaces 3×8 uprights at six feet horizontally.

(2) Example 2.

A trench dug in Type B soil in 13 feet deep and five feet wide. From Table C-1.2 three acceptable arrangements of members are listed.

Arrangement #B1

Space 6×6 crossbraces at six feet horizontally and five feet vertically.

Space 8×8 wales at five feet vertically.

Space 2×6 uprights at two feet horizontally.

Arrangement #B2

Space 6×8 crossbraces at eight feet horizontally and five feet vertically.

Space 10×10 wales at five feet vertically.

Space 2×6 uprights at two feet horizontally.

Arrangement #B3

Space 8×8 crossbraces at 10 feet horizontally and five feet vertically.

Space 10×12 wales at five feet vertically.

Space 2×6 uprights at two feet vertically.

(3) Example 3.

A trench dug in Type C soil is 13 feet deep and five feet wide.

From Table C-1.3 two acceptable arrangements of members can be used.

Arrangement #B1

Space 8×8 crossbraces at six feet horizontally and five feet vertically.

Space 10×12 wales at five feet vertically.

Position 2×6 uprights as closely together as possible.

If water must be retained use special tongue and groove uprights to form tight sheeting.

Arrangement #B2

Space 8×10 crossbraces at eight feet horizontally and five feet vertically.

Space 12×12 wales at five feet vertically.

Position 2×6 uprights in a close sheeting configuration unless water pressure must be resisted. Tight sheeting must be used where water must be retained.

(4) Example 4.

A trench dug in Type C soil is 20 feet deep and 11 feet wide. The size and spacing of members for the section of trench that is over 15 feet in depth is determined using Table C-1.3. Only one arrangement of members is provided.

Space 8×10 crossbraces at six feet horizontally and five feet vertically.

Space 12×12 wales at five feet vertically.

Use 3×6 tight sheeting.

Use of Tables C-2.1 through C-2.3 would follow the same procedures.

(g) Notes for all Tables.

1. Member sizes at spacings other than indicated are to be determined as specified in §1926.652(c), "Design of Protective Systems."

2. When conditions are saturated or submerged use Tight Sheeting. Tight Sheeting refers to the use of specially-edged timber planks (e.g., tongue and groove) at least three inches thick, steel sheet piling, or similar construction that when driven or placed in position provide a tight wall to resist the lateral pressure of water and to prevent the loss of backfill material. Close Sheeting refers to the placement of planks side-by-side allowing as little space as possible between them.

3. All spacing indicated is measured center to center.

4. Wales to be installed with greater dimension horizontal.

5. If the vertical distance from the center of the lowest crossbrace to the bottom of the trench exceeds two and one-half feet, uprights shall be firmly embedded or a mudsill shall be used. Where uprights are embedded, the vertical distance from the center of the lowest crossbrace to the bottom of the trench shall not exceed 36 inches. When mudsills are used, the vertical distance shall not exceed 42 inches. Mudsills are wales that are installed at the toe of the trench side.

6. Trench jacks may be used in lieu of or in combination with timber crossbraces.

7. Placement of crossbraces. When the vertical spacing of crossbraces is four feet, place the top crossbrace no more than two feet below the top of the trench. When the vertical spacing of crossbraces is five feet, place the top crossbrace no more than 2.5 feet below the top of the trench.

TABLE C-1.1

TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *

SOIL TYPE A $P_a = 25 \times H + 72 \text{ psf}$ (2 ft Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (ACTUAL) AND SPACING OF MEMBERS **														
	CROSS BRACES					MALES		UPRIGHTS							
	HORIZ. SPACING (FEET)	WIDTH OF TRENCH (FEET)					VERT. SPACING (FEET)	SIZE (IN)	VERT. SPACING (FEET)	MAXIMUM ALLOWABLE HORIZONTAL SPACING (FEET)					
		UP TO 4	UP TO 6	UP TO 9	UP TO 12	UP TO 15				CLOSE	4	5	6	8	
5	UP TO 6	4X4	4X4	4X6	6X6	6X6	4	Not Req'd	---						
T0	UP TO 8	4X4	4X4	4X6	6X6	6X6	4	Not Req'd	---					2X6	
	UP TO 10	4X6	4X6	4X6	6X6	6X6	4	8X8	4				2X6		2X8
10	UP TO 12	4X6	4X6	6X6	6X6	6X6	4	8X8	4						
	UP TO 6	4X4	4X4	4X6	6X6	6X6	4	Not Req'd	---					3X8	
T0	UP TO 8	4X6	4X6	6X6	6X6	6X6	4	8X8	4			2X6			
15	UP TO 10	6X6	6X5	6X6	6X8	6X8	4	8X10	4				2X6		
	UP TO 12	6X6	6X6	6X6	6X8	6X8	4	10X10	4					3X8	
15	UP TO 6	6X6	6X6	6X6	6X8	6X8	4	6X8	4		3X6				
T0	UP TO 8	6X6	6X6	6X6	6X8	6X8	4	8X8	4		3X6				
20	UP TO 10	8X8	8X8	8X8	8X8	8X10	4	8X10	4		3X6				
	UP TO 12	8X8	8X8	8X8	8X8	8X10	4	10X10	4		3X6				
OVER 20	SEE NOTE 1														

* Mixed oak or equivalent with a bending strength not less than 850 psi.

** Manufactured members of equivalent strength may be substituted for wood.

TABLE C-1.2

TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *

SOIL TYPE B $P_a = 45 \text{ X H} + 72 \text{ psf}$ (2 ft. Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (ACTUAL) AND SPACING OF MEMBERS**											
	CROSS BRACES						WALES		UPRIGHTS			
	WIDTH OF TRENCH (FEET)						VERT. SPACING (FEET)	SIZE (IN)	MAXIMUM ALLOWABLE HORIZONTAL SPACING			
	HORIZ. SPACING (FEET)	UP TO 4	UP TO 6	UP TO 9	UP TO 12	UP TO 15			CLOSE	2	3	
5	UP TO 6	4X6	4X6	6X6	6X6	6X6	5	6X8	5		2X6	
TO	UP TO 8	6X6	6X6	6X6	6X8	6X8	5	8X10	5		2X6	
10	UP TO 10	6X6	6X6	6X6	6X8	6X8	5	10X10	5		2X6	
	See Note 1											
10	UP TO 6	6X6	6X6	6X6	6X8	6X8	5	8X8	5	2X6		
TO	UP TO 8	6X8	6X8	6X8	8X8	8X8	5	10X10	5	2X6		
15	UP TO 10	8X8	8X8	8X8	8X8	8X10	5	10X12	5	2X6		
	See Note 1											
15	UP TO 6	6X8	6X8	6X8	8X8	8X8	5	8X10	5	3X6		
TO	UP TO 8	8X8	8X8	8X8	8X8	8X10	5	10X12	5	3X6		
20	UP TO 10	8X10	8X10	8X10	8X10	10X10	5	12X12	5	3X6		
	See Note 1											
OVER 20	SEE NOTE 1											

* Mixed oak or equivalent with a bending strength not less than 850 psi.

** Manufactured members of equivalent strength may be substituted for wood.

TABLE C-1.3

TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *

SOIL TYPE C P_a = 80 X H + 72 psf (2 ft. Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (ACTUAL) AND SPACING OF MEMBERS**												
	CROSS BRACES							UPRIGHTS					
	HORIZ. SPACING (FEET)	WIDTH OF TRENCH (FEET)					VERT. SPACING (FEET)	SIZE (IN.)	VERT. SPACING (FEET)	MAXIMUM ALLOWABLE HORIZONTAL SPACING (FEET) (See Note 2)			
		UP TO 4	UP TO 6	UP TO 9	UP TO 12	UP TO 15				CLOSE			
5 TO 10	UP TO 6	6X8	6X8	6X8	8X8	8X8	5	8X10	5	2X6			
	UP TO 8	8X8	8X8	8X8	8X8	8X10	5	10X12	5	2X6			
	UP TO 10	8X10	8X10	8X10	8X10	10X10	5	12X12	5	2X6			
	See Note 1												
10 TO 15	UP TO 6	8X8	8X8	8X8	8X8	8X10	5	10X12	5	2X6			
	UP TO 8	8X10	8X10	8X10	8X10	10X10	5	12X12	5	2X6			
	See Note 1												
	See Note 1												
15 TO 20	UP TO 6	8X10	8X10	8X10	8X10	10X10	5	12X12	5	3X6			
	See Note 1												
	See Note 1												
	See Note 1												
OVER 20	SEE NOTE 1												

* Mixed Oak or equivalent with a bending strength not less than 850 psi.

** Manufactured members of equivalent strength may be substituted for wood.

TABLE C-2.1

TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *

SOIL TYPE A $P_a = 25 \text{ X H} \pm 72 \text{ psf}$ (2 ft. Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (S&S) AND SPACING OF MEMBERS **										UPRIGHTS			
	CROSS BRACES					WALES					MAXIMUM ALLOWABLE HORIZONTAL SPACING (FEET)			
	WIDTH OF TRENCH (FEET)					VERT. SPACING (FEET)					VERT. SPACING (FEET)			
	UP TO 4	UP TO 6	UP TO 9	UP TO 12	UP TO 15	UP TO 4	UP TO 6	UP TO 8	UP TO 10	UP TO 12	CLOSE	4	5	8
5	UP TO 6	4X4	4X4	4X4	4X4	4	4	4	4	4	Not Req'd	4X6		
TO 8	UP TO 8	4X4	4X4	4X4	4X4	4	4	4	4	4	Not Req'd			4X8
TO 10	UP TO 10	4X6	4X6	4X6	6X6	4	4	4	4	4	4X6			
TO 12	UP TO 12	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 15	UP TO 15	4X6	4X6	4X6	6X6	4	4	4	4	4	Not Req'd	4X10		
TO 18	UP TO 18	4X6	4X6	4X6	6X6	4	4	4	4	4	4X6			
TO 20	UP TO 20	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6	4X8	
TO 22	UP TO 22	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 24	UP TO 24	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 26	UP TO 26	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 28	UP TO 28	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 30	UP TO 30	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 32	UP TO 32	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 34	UP TO 34	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 36	UP TO 36	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 38	UP TO 38	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 40	UP TO 40	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 42	UP TO 42	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 44	UP TO 44	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 46	UP TO 46	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 48	UP TO 48	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 50	UP TO 50	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 52	UP TO 52	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 54	UP TO 54	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 56	UP TO 56	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 58	UP TO 58	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 60	UP TO 60	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 62	UP TO 62	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 64	UP TO 64	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 66	UP TO 66	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 68	UP TO 68	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 70	UP TO 70	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 72	UP TO 72	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 74	UP TO 74	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 76	UP TO 76	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 78	UP TO 78	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 80	UP TO 80	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 82	UP TO 82	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 84	UP TO 84	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 86	UP TO 86	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 88	UP TO 88	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 90	UP TO 90	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 92	UP TO 92	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 94	UP TO 94	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 96	UP TO 96	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 98	UP TO 98	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
TO 100	UP TO 100	4X6	4X6	4X6	6X6	4	4	4	4	4		4X6		
OVER 20	SEE NOTE 1													

* Douglas fir or equivalent with a bending strength not less than 1500 psi.

** Manufactured members of equivalent strength may be substituted for wood.

TABLE C-2.2

TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *
 SOIL TYPE B $P_a = 45 \text{ X H} + 72 \text{ psf}$ (2 ft. Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (S4S) AND SPACING OF MEMBERS **														
	CROSS BRACES						WALES		UPRIGHTS						
	HORIZ. SPACING (FEET)		WIDTH OF TRENCH (FEET)				VERT. SPACING (FEET)	SIZE (IN)	VERT. SPACING (FEET)	MAXIMUM ALLOWABLE HORIZONTAL SPACING (FEET)					
			UP TO 4	UP TO 6	UP TO 9	UP TO 12				UP TO 15	CLOSE	2	3	4	6
5	UP TO 6	4X6	4X6	4X6	6X6	6X6	5	6X8	5			3X12 4X8			4X12
TO	UP TO 8	4X6	4X6	6X6	6X6	6X6	5	8X8	5		3X8		4X8		
10	UP TO 10	4X6	4X6	6X6	6X6	6X6	5	8X10	5			4X8			
	See Note 1														
10	UP TO 6	6X6	6X6	6X6	6X6	6X8	5	8X8	5	3X6	4X10				
TO	UP TO 8	6X8	6X8	6X8	8X8	8X8	5	10X10	5	3X6	4X10				
15	UP TO 10	6X8	6X8	8X8	8X8	8X8	5	10X12	5	3X6	4X10				
	See Note 1														
15	UP TO 6	6X8	6X8	6X8	6X8	8X8	5	8X10	5	4X6					
TO	UP TO 8	6X8	6X8	6X8	6X8	8X8	5	10X12	5	4X6					
20	UP TO 10	8X8	8X8	8X8	8X8	8X8	5	12X12	5	4X6					
	See Note 1														
OVER 20	SEE NOTE 1														

* Douglas fir or equivalent with a bending strength not less than 1500 psi.

** Manufactured members of equivalent strength may be substituted for wood.

TABLE C-2.3
TIMBER TRENCH SHORING -- MINIMUM TIMBER REQUIREMENTS *
SOIL TYPE C $P_a = 80 \text{ X H} + 72 \text{ psf}$ (2 ft. Surcharge)

DEPTH OF TRENCH (FEET)	SIZE (S4S) AND SPACING OF MEMBERS **									
	CROSS BRACES					WALES		UPRIGHTS		
	HORIZ. SPACING (FEET)		WIDTH OF TRENCH (FEET)			VERT. SPACING (FEET)	SIZE (IN)	VERT. SPACING (FEET)	MAXIMUM ALLOWABLE HORIZONTAL SPACING (FEET)	
	UP	TO	UP	TO	UP	TO	UP	TO	CLOSE	
5	UP	TO	4	6	6	9	6X6	8X8	5	3X6
	UP	TO	6X6	6X6	6X6	6X6	8X8	5		
	UP	TO	8	6X6	6X6	6X6	8X8	5	3X6	
	UP	TO	10	6X6	6X6	8X8	8X8	5	3X6	
10	UP	TO	4	6X6	6X6	6X6	8X8	5		
	UP	TO	6	6X6	6X6	6X6	8X8	5		
	UP	TO	8	6X6	6X6	8X8	8X8	5		
	UP	TO	10	6X6	6X6	8X8	8X8	5		
15	UP	TO	4	6X6	6X6	6X6	8X8	5		
	UP	TO	6	6X6	6X6	6X6	8X8	5		
	UP	TO	8	6X6	6X6	8X8	8X8	5		
	UP	TO	10	6X6	6X6	8X8	8X8	5		
20	UP	TO	4	6X6	6X6	6X6	8X8	5		
	UP	TO	6	6X6	6X6	6X6	8X8	5		
	UP	TO	8	6X6	6X6	8X8	8X8	5		
	UP	TO	10	6X6	6X6	8X8	8X8	5		
OVER 20	UP	TO	4	6X6	6X6	6X6	8X8	5		
	UP	TO	6	6X6	6X6	6X6	8X8	5		
	UP	TO	8	6X6	6X6	8X8	8X8	5		
	UP	TO	10	6X6	6X6	8X8	8X8	5		

* Douglas fir or equivalent with a bending strength not less than 1500 psi.

** Manufactured members of equivalent strength may be substituted for wood.

APPENDIX D TO SUBPART P OF PART 1926—ALUMINUM HYDRAULIC SHORING FOR TRENCHES

(a) *Scope.* This appendix contains information that can be used when aluminum hydraulic shoring is provided as a method of protection against cave-ins in trenches that

do not exceed 20 feet (6.1m) in depth. This appendix must be used when design of the aluminum hydraulic protective system cannot be performed in accordance with § 1926.652(c)(2).

(b) *Soil Classification.* In order to use data presented in this appendix, the soil type or types in which the excavation is made must