Subpart Q—Concrete and Masonry Construction

AUTHORITY: Sec. 107, Contract Work Hours and Safety Standards Act (Construction Safety Act) (40 U.S.C. 333); Secs. 4, 6 and 8 Occupational Safety and Health Act of 1970 (29 U.S.C. 653, 655, and 657); Secretary of Labor's Order No. 12–71 (36 FR 8754), 8–76 (41 FR 25059), 9–83 (48 FR 35736), or 1–90 (55 FR 9033), as applicable; and 29 CFR part 1911.

SOURCE: 53 FR 22643, June 16, 1988, unless otherwise noted.

§ 1926.700 Scope, application, and definitions applicable to this subpart.

- (a) Scope and application. This subpart sets forth requirements to protect all construction employees from the hazards associated with concrete and masonry construction operations performed in workplaces covered under 29 CFR part 1926. In addition to the requirements in subpart Q, other relevant provisions in parts 1910 and 1926 apply to concrete and masonry construction operations.
- (b) Definitions applicable to this subpart. In addition to the definitions set forth in §1926.32, the following definitions apply to this subpart.
- (1) Bull float means a tool used to spread out and smooth concrete.
- (2) Formwork means the total system of support for freshly placed or partially cured concrete, including the mold or sheeting (form) that is in contact with the concrete as well as all supporting members including shores, reshores, hardware, braces, and related hardware.
- (3) Lift slab means a method of concrete construction in which floor, and roof slabs are cast on or at ground level and, using jacks, lifted into position.
- (4) Limited access zone means an area alongside a masonry wall, which is under construction, and which is clearly demarcated to limit access by employees.
- (5) Precast concrete means concrete members (such as walls, panels, slabs, columns, and beams) which have been formed, cast, and cured prior to final placement in a structure.
- (6) Reshoring means the construction operation in which shoring equipment (also called reshores or reshoring equipment) is placed, as the original

forms and shores are removed, in order to support partially cured concrete and construction loads.

- (7) Shore means a supporting member that resists a compressive force imposed by a load.
- (8) Vertical slip forms means forms which are jacked vertically during the placement of concrete.
- (9) Jacking operation means the task of lifting a slab (or group of slabs) vertically from one location to another (e.g., from the casting location to a temporary (parked) location, or from a temporary location to another temporary location, or to its final location in the structure), during the construction of a building/structure where the lift-slab process is being used.

[53 FR 22643, June 16, 1988, as amended at 55 FR 42328, Oct. 18, 1990]

§ 1926.701 General requirements.

- (a) Construction loads. No construction loads shall be placed on a concrete structure or portion of a concrete structure unless the employer determines, based on information received from a person who is qualified in structural design, that the structure or portion of the structure is capable of supporting the loads.
- (b) Reinforcing steel. All protruding reinforcing steel, onto and into which employees could fall, shall be guarded to eliminate the hazard of impalement.
- (c) Post-tensioning operations. (1) No employee (except those essential to the post-tensioning operations) shall be permitted to be behind the jack during tensioning operations.
- (2) Signs and barriers shall be erected to limit employee access to the posttensioning area during tensioning operations.
- (d) Riding concrete buckets. No employee shall be permitted to ride concrete buckets.
- (e) Working under loads. (1) No employee shall be permitted to work under concrete buckets while buckets are being elevated or lowered into position.
- (2) To the extent practical, elevated concrete buckets shall be routed so that no employee, or the fewest number of employees, are exposed to the hazards associated with falling concrete buckets.