

Safety & Environmental Enforcement, Interior

§ 250.1725

(6) A letter signed by your authorized representative stating that he/she witnessed the trawling test.

(e) If a temporarily abandoned well is protected by a subsea device installed in a water depth less than 100 feet, mark the site with a buoy installed according to the USCG requirements.

(f) Provide annual reports to the Regional Supervisor describing your plans to either re-enter and complete the well or to permanently plug the well.

(g) Ensure that all subsea wellheads, casing stubs, mud line suspensions, or other obstructions in water depths less than 300 feet remain protected.

(1) To confirm that the subsea protective covering remains properly installed, either conduct a visual inspection or perform a trawl test at least annually.

(2) If the inspection reveals that a casing stub or mud line suspension is no longer properly protected, or if the trawl does not pass over the subsea protective covering without causing damage to the covering, the casing stub or mud line suspension equipment, or the trawl, notify the appropriate District Manager within 5 days, and perform the necessary remedial work within 30 days of discovery of the problem.

(3) In your annual report required by paragraph (f) of this section, include the inspection date, results, and method used and a description of any remedial work you will perform or have performed.

(h) You may request approval to waive the trawling test required by paragraph (c) of this section if you plan to use either:

(1) A buoy with automatic tracking capabilities installed and maintained according to USCG requirements at 33 CFR part 67 (or its successor); or

(2) A design and installation method that has been proven successful by trawl testing of previous protective devices of the same design and installed in areas with similar bottom conditions.

§ 250.1723 What must I do when it is no longer necessary to maintain a well in temporary abandoned status?

If you or BSEE determines that continued maintenance of a well in a temporary abandoned status is not necessary for the proper development or production of a lease, you must:

(a) Promptly and permanently plug the well according to §250.1715;

(b) Remove any casing stub or mud line suspension equipment and any subsea protective covering. You must submit a request for approval to perform such work to the appropriate District Manager using form BSEE-0124, Application for Permit to Modify; and

(c) Clear the well site according to §§ 250.1740 through 250.1742.

REMOVING PLATFORMS AND OTHER FACILITIES

§ 250.1725 When do I have to remove platforms and other facilities?

(a) You must remove all platforms and other facilities within 1 year after the lease or pipeline right-of-way terminates, unless you receive approval to maintain the structure to conduct other activities. Platforms include production platforms, well jackets, single-well caissons, and pipeline accessory platforms. Other activities include those supporting OCS oil and gas production and transportation, as well as other energy-related or marine-related uses (including LNG) for which adequate financial assurance for decommissioning has been provided to a Federal agency which has given BSEE a commitment that it has and will exercise authority to compel the performance of decommissioning within a time following cessation of the new use acceptable to BSEE. The approval will specify:

(1) Whether you must continue to maintain any financial assurance for decommissioning; and

(2) Whether, and under what circumstances, you must perform any decommissioning not performed by the new facility owner/user.

(b) Before you may remove a platform or other facility, you must submit a final removal application to the Regional Supervisor for approval and