§ 127.1317

- (f) Ensure the display of the warning signs required by §127.1113;
- (g) Ensure that the requirements of this part concerning smoking and fire protection are met:
- (h) Ensure that qualified personnel are on duty in accordance with the examined Operations Manual and §§ 127.1301 and 127.1302; and
- (i) Test the following to determine that they are operable:
- (1) The communication system required by §127.1111.
- (2) The gas detectors required by §127.1203.

§ 127.1317 Declaration of Inspection.

- (a) Each person in charge of transfer for the facility shall ensure that no person transfers LHG to or from a vessel until a Declaration of Inspection that meets paragraph (c) of this section is executed and signed by both the person in charge aboard the vessel and the person in charge for the facility.
- (b) No person in charge of transfer for the facility may sign the Declaration unless that person has fulfilled the requirements of §127.1315 and has indicated fulfillment of each requirement by writing his or her initials in the appropriate space on the Declaration.
 - (c) Each Declaration must contain—
- (1) The name of the vessel and that of the facility;
- (2) The date and time that the transfer begins;
- (3) A list of the requirements in §127.1315 with the initials of both the person in charge aboard the vessel and the person in charge for the facility after each requirement, indicating the fulfillment of the requirement;
- (4) The signatures of both the person in charge aboard the vessel and the person in charge for the facility, and the date and time of signing, indicating that they are both ready to begin transfer; and
- (5) The signature of each relief person in charge and the date and time of each relief.
- (d) The person in charge of transfer for the facility shall give one signed copy of the Declaration to the person in charge of transfer aboard the vessel and retain the other.
- (e) Each operator of a facility shall retain a signed copy of the Declaration

at the facility for 30 days after the transfer.

§ 127.1319 Transfer of LHG.

- (a) The operator of a waterfront facility handling LHG shall notify the COTP of the time and place of each transfer of LHG in bulk at least 4 hours before it begins.
- (b) During transfer, each operator of a waterfront facility handling LHG shall ensure that—
- (1) The marine transfer area for LHG is under the supervision of a person in charge certified for transfers of LHG, who has no other assigned duties during the transfer;
- (2) The person in charge supervises transfers only to or from one vessel at a time unless authorized by the COTP.
- (3) No person transferring fuel or oily waste is involved in the transfer; and
- (4) No vessel is moored outboard of any LHG vessel unless allowed by the COTP or the examined Operations Manual of the facility.
- (c) During transfer, each person in charge of transfer for the facility shall—
- (1) Maintain communication with the person in charge of transfer aboard the LHG vessel;
- (2) Ensure that an inspection of the transfer piping and equipment for leaks, frost, defects, and other threats to safety takes place at least once every transfer;
 - (3) Ensure that-
- (i) Transfer of LHG is discontinued as soon as a release or fire is detected in the area or aboard the vessel; and
- (ii) Transfer of flammable LHG is discontinued when electrical storms or uncontrolled fires approach near the area; and
- (4) Ensure that the outdoor lighting required by §127.1109 is turned on between sunset and sunrise.
- (d) Upon completion of transfer of LHG, each operator of a waterfront facility handling LHG shall ensure that hoses and loading arms used for transfer are drained of LHG residue and depressurized before disconnecting from the vessel.

NOTE TO §127.1319: Corresponding standards for vessels appear at 46 CFR part 154.