

§ 63.499

40 CFR Ch. I (7–1–14 Edition)

(D) If all recorded values for a monitored parameter during an operating day are below the maximum, or above the minimum, level established in the Notification of Compliance Status in § 63.506(e)(5) or in the operating permit, the owner or operator may record that all values were below the maximum or above the minimum level, rather than calculating and recording a daily average for that operating day.

(E) For flares, records of the times and duration of all periods during which the pilot flame is absent, shall be kept rather than daily averages. The records specified in this paragraph are not required during periods when emissions are not routed to the flare.

(iii) Hourly records of whether the flow indicator specified under § 63.497(d)(1) was operating and whether a diversion was detected at any time during the hour, as well as records of the times of all periods when the vent stream is diverted from the control device or the flow indicator is not operating.

(iv) Where a seal mechanism is used to comply with § 63.497(d)(2), hourly records of flow are not required.

(A) For compliance with § 63.497(d)(2), the owner or operator shall record whether the monthly visual inspection of the seals or closure mechanisms has been done, and shall record instances when the seal mechanism is broken, the bypass line damper or valve position has changed, or the key for a lock-and-key type configuration has been checked out, and records of any car-seal that has broken.

(B) [Reserved]

(e) If the back-end process operation is subject to an organic HAP emission limitation in § 63.494(a)(4), the records specified in paragraphs (e)(1) through (4) of this section.

(1) The applicable organic HAP emission limitation determined in accordance with § 63.494(a)(4)(i) through (iv).

(2) The organic HAP emissions from all back-end process operations for each month, along with documentation of all calculations and other information used in the engineering assessment to estimate these emissions.

(3) The mass of elastomer product produced each month.

(4) The total mass of organic HAP emitted for each 12-month period divided by the total mass of elastomer produced during the 12-month period, determined in accordance with § 63.495(g)(5).

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38063, June 19, 2000; 76 FR 22591, Apr. 21, 2011]

§ 63.499 Back-end process provisions—reporting.

(a) The owner or operator of an affected source with back-end process operations shall submit the information required in paragraphs (a)(1) through (a)(3) of this section, for each back-end process operation at the affected source, as part of the Notification of Compliance Status specified in § 63.506(e)(5).

(1) The type of elastomer product processed in the back-end operation.

(2) The type of process (solution process, emulsion process, etc.)

(3) If the back-end process operation is subject to a residual organic HAP limitation in § 63.494(a)(1) through (3), whether compliance will be achieved by stripping technology, or by control or recovery devices.

(b) Each owner or operator of a back-end process operation using stripping to comply with a residual organic HAP limitation in § 63.494(a)(1) through (3), and demonstrating compliance by stripper parameter monitoring, shall submit reports as specified in paragraphs (b)(1) and (2) of this section.

(1) As part of the Notification of Compliance Status specified in § 63.506(e)(5), the owner or operator shall submit the information specified in § 63.498(c)(1).

(2) For organic HAP content/stripper monitoring parameter re-determinations, and the addition of new grades, the information specified in § 63.498(c)(1) shall be submitted in the next periodic report specified in § 63.506(e)(6).

(c) Each owner or operator of an affected source with a back-end process operation control or recovery device that shall comply with a residual organic HAP limitation in § 63.494(a)(1) through (3), shall submit the information specified in paragraphs (c)(1) through (3) of this section as part of

## Environmental Protection Agency

## § 63.500

the Notification of Compliance Status specified in § 63.506(e)(5).

(1) The residual organic HAP content, adjusted for the control or recovery device emission reduction, determined in accordance with § 63.496(c)(1), for each test run in the compliance determination.

(2) The operating parameter level established in accordance with § 63.497(c), along with supporting documentation.

(3) The information specified in paragraphs (c)(3)(i) when using a flare, and the information specified in paragraph (c)(3)(ii) of this section when using a boiler or process heater.

(i) The flare design (i.e., steam-assisted, air-assisted, or non-assisted); all visible emission readings, heat content determinations, flow rate measurements, and exit velocity determinations made during the compliance determination; and all periods during the compliance determination when the pilot flame is absent.

(ii) A description of the location at which the vent stream is introduced into the boiler or process heater.

(d) Whenever a process change, as defined in § 63.496(d), is made that causes the redetermination of the compliance status for the back-end process operations subject to a residual organic HAP limitation in § 63.494(a)(1) through (3), the owner or operator shall submit a report within 180 days after the process change, as specified in § 63.506(e)(7)(iii). The report shall include:

(1) A description of the process change;

(2) The results of the redetermination of the compliance status, determined in accordance with § 63.496(b), and recorded in accordance with § 63.498(d)(1), and

(3) Documentation of the re-establishment of a parameter level for the control or recovery device, defined as either a maximum or minimum operating parameter, that indicates proper operation of the control or recovery device, in accordance with § 63.497(c) and recorded in accordance with § 63.498(d)(2).

(e) If an owner or operator uses a control or recovery device other than those listed in § 63.497(a) or requests approval to monitor a parameter other

than those specified in § 63.497(a), the owner or operator shall submit a description of planned reporting and recordkeeping procedures as required under § 63.506(e)(3) or (e)(8). The Administrator will specify appropriate reporting and recordkeeping requirements as part of the review of the Precompliance Report or Operating Permit application.

(f) If the back-end process operation is subject to an organic HAP emission limitation in § 63.494(a)(4), the owner and operator must submit the information specified in paragraphs (f)(1) and (2) of this section.

(1) The applicable organic HAP emission limitation determined in accordance with § 63.494(a)(4)(i) through (iv), shall be submitted no later than 180 days from the date of publication of the final rule amendments in the FEDERAL REGISTER.

(2) Beginning with the first periodic report required to be submitted by § 63.506(e)(6) that is at least 13 months after the compliance date, the total mass of organic HAP emitted for each of the rolling 12-month periods in the reporting period divided by the total mass of elastomer produced during the corresponding 12-month period, determined in accordance with § 63.495(g)(5).

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38068, June 19, 2000; 76 FR 22592, Apr. 21, 2011]

### **§ 63.500 Back-end process provisions—carbon disulfide limitations for styrene butadiene rubber by emulsion processes.**

(a) Owners or operators of sources subject to this subpart producing styrene butadiene rubber using an emulsion process shall operate the process such that the carbon disulfide concentration in each crumb dryer exhausts shall not exceed 45 ppmv.

(1) The owner or operator shall develop standard operating procedures for the addition of sulfur containing shortstop agents to ensure that the limitation in paragraph (a) of this section is maintained. There shall be a standard operating procedure representing the production of every grade of styrene butadiene rubber produced at the affected source using a sulfur containing shortstop agent.