AUTHENTICATED
U.S. GOVERNMENT
INFORMATION
GPO

Table JJ-5 to Subpart JJ of Part 98—Methane Conversion Factors

Manure Management System Component	MCFs by Average Annual Ambient Temperature (degrees C)																		
	Cool					Temperate											Warm		
	<10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	>28
Uncovered Anaerobic Lagoon	66%	68%	70%	71%	73%	74%	75%	76%	77%	77%	78%	78%	78%	79%	79%	79%	79%	80%	80%
Liquid/slurry (with crust cover)	10%	11%	13%	14%	15%	17%	18%	20%	22%	24%	26%	29%	31%	34%	37%	41%	44%	48%	50%
Liquid/slurry (w/o crust cover)	17%	19%	20%	22%	25%	27%	29%	32%	35%	39%	42%	46%	50%	55%	60%	65%	71%	78%	80%
Storage pits <1 month	3.0%					3.0%											30.0%		
Storage pits >1 month	17%	19%	20%	22%	25%	27%	29%	32%	35%	39%	42%	46%	50%	55%	60%	65%	71%	78%	80%
Solid manure storage	2.0%					4.0%											5.0%		
Dry lots (including feedlots)	1.0%					1.5%											2.0%		
High-rise houses for poultry production (without litter)	1.5%					1.5%											1.5%		
Poultry production with litter	1.5%					1.5%											1.5%		
Deep bedding systems for cattle and swine(<1 month)	3.0%					3.0%											30.0%		
Deep bedding systems for cattle and swine (>1 month)	17%	19%	20%	22%	25%	27%	29%	32%	35%	39%	42%	46%	50%	55%	60%	65%	71%	78%	80%
Manure Composting - In Vessel	0.5%					0.5%											0.5%		
Manure Composting - Static Pile	0.5%					0.5%											0.5%		
Manure Composting- Extensive/ Passive	0.5%					1.0%											1.5%		
Manure Composting- Intensive	0.5%					1.0%											1.5%		
Aerobic Treatment	0.0%					0.0%											0.0%		

TABLE JJ–6 TO SUBPART JJ OF PART 98—COLLECTION EFFICIENCIES OF ANAEROBIC DIGESTERS

Anaerobic digester type	Cover type	Methane collection efficiency
Covered anaerobic lagoon (biogas capture)	Bank to bank, impermeable	0.975
	Modular, impermeable	0.70
Complete mix, fixed film, or plug flow digester	Enclosed Vessel	0.99