

Environmental Protection Agency

§ 98.122

factor used to calculate the CH₄ emissions.

§ 98.118 Definitions.

All terms used of this subpart have the same meaning given in the Clean Air Act and subpart A of this part.

TABLE K-1 TO SUBPART K OF PART 98—ELECTRIC ARC FURNACE (EAF) CH₄ EMISSION FACTORS

Alloy product produced in EAF	CH ₄ emission factor (kg CH ₄ per metric ton product)		
	EAF Operation		
	Batch-charging	Sprinkle-charging ^a	Sprinkle-charging and >750 °C ^b
Silicon metal	1.5	1.2	0.7
Ferrosilicon 90%	1.4	1.1	0.6
Ferrosilicon 75%	1.3	1.0	0.5
Ferrosilicon 65%	1.3	1.0	0.5

^a Sprinkle-charging is charging intermittently every minute.

^b Temperature measured in off-gas channel downstream of the furnace hood.

Subpart L—Fluorinated Gas Production

SOURCE: 75 FR 74831, Dec. 1, 2010, unless otherwise noted.

§ 98.120 Definition of the source category.

(a) The fluorinated gas production source category consists of processes that produce a fluorinated gas from any raw material or feedstock chemical, except for processes that generate HFC-23 during the production of HCFC-22.

(b) To produce a fluorinated gas means to manufacture a fluorinated gas from any raw material or feedstock chemical. Producing a fluorinated gas includes producing a fluorinated GHG as defined at § 98.410(b). Producing a fluorinated gas also includes the manufacture of a chlorofluorocarbon (CFC) or hydrochlorofluorocarbon (HCFC) from any raw material or feedstock chemical, including manufacture of a CFC or HCFC as an isolated intermediate for use in a process that will result in the transformation of the CFC or HCFC either at or outside of the production facility. Producing a fluorinated gas does not include the reuse or recycling of a fluorinated gas, the creation of HFC-23 during the production of HCFC-22, the creation of intermediates that are created and

transformed in a single process with no storage of the intermediates, or the creation of fluorinated GHGs that are released or destroyed at the production facility before the production measurement in § 98.414(a).

§ 98.121 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains a fluorinated gas production process that generates or emits fluorinated GHG and the facility meets the requirements of either § 98.2(a)(1) or (a)(2). To calculate GHG emissions for comparison to the 25,000 metric ton CO₂e per year emission threshold in § 98.2(a)(2), calculate process emissions from fluorinated gas production using uncontrolled GHG emissions.

§ 98.122 GHGs to report.

(a) You must report CO₂, CH₄, and N₂O combustion emissions from each stationary combustion unit. You must calculate and report these emissions under subpart C of this part (General Stationary Fuel Combustion Sources) by following the requirements of subpart C.

(b) You must report under subpart O of this part (HCFC-22 Production and HFC-23 Destruction) the emissions of HFC-23 from HCFC-22 production processes and HFC-23 destruction processes. Do not report the generation and