

Environmental Protection Agency

§ 98.353

and/or industrial wastewater treatment sludge.

§ 98.352 GHGs to report.

(a) You must report CH₄ generation, CH₄ emissions, and CH₄ recovered from treatment of industrial wastewater at each anaerobic lagoon and anaerobic reactor.

(b) You must report CH₄ emissions and CH₄ recovered from each anaerobic sludge digester.

(c) You must report CH₄ emissions and CH₄ destruction resulting from each biogas collection and biogas destruction device.

(d) You must report under subpart C of this part (General Stationary Fuel Combustion Sources) the emissions of CO₂, CH₄, and N₂O from each stationary

combustion unit associated with the biogas destruction device, if present, by following the requirements of subpart C of this part.

[75 FR 39767, July 12, 2010, as amended at 76 FR 73903, Nov. 29, 2011]

§ 98.353 Calculating GHG emissions.

(a) For each anaerobic reactor and anaerobic lagoon, estimate the annual mass of CH₄ generated according to the applicable requirements in paragraphs (a)(1) through (a)(2) of this section.

(1) If you measure the concentration of organic material entering the anaerobic reactors or anaerobic lagoon using methods for the determination of chemical oxygen demand (COD), then estimate annual mass of CH₄ generated using Equation II-1 of this section.

$$CH_4G_n = \sum_{w=1}^{52} [Flow_w * COD_w * B_o * MCF * 0.001] \quad (\text{Eq. II-1})$$

Where:

CH₄G_n = Annual mass CH₄ generated from the nth anaerobic wastewater treatment process (metric tons).

n = Index for processes at the facility, used in Equation II-7.

w = Index for weekly measurement period.

Flow_w = Volume of wastewater sent to an anaerobic wastewater treatment process in week w (m³/week), measured as specified in § 98.354(d).

COD_w = Average weekly concentration of chemical oxygen demand of wastewater entering an anaerobic wastewater treatment process (for week w)(kg/m³), measured as specified in § 98.354(b) and (c).

B_o = Maximum CH₄ producing potential of wastewater (kg CH₄/kg COD), use the value 0.25.

MCF = CH₄ conversion factor, based on relevant values in Table II-1 of this subpart.

0.001 = Conversion factor from kg to metric tons.

(2) If you measure the concentration of organic material entering an anaerobic reactor or anaerobic lagoon using methods for the determination of 5-day biochemical oxygen demand (BOD₅), then estimate annual mass of CH₄ generated using Equation II-2 of this section.

$$CH_4G_n = \sum_{w=1}^{52} [Flow_w * BOD_{5,w} * B_o * MCF * 0.001] \quad (\text{Eq. II-2})$$

Where:

CH₄G_n = Annual mass of CH₄ generated from the anaerobic wastewater treatment process (metric tons).

n = Index for processes at the facility, used in Equation II-7.

w = Index for weekly measurement period.

Flow_w = Volume of wastewater sent to an anaerobic wastewater treatment process in

week w(m³/week), measured as specified in § 98.354(d).

BOD_{5,w} = Average weekly concentration of 5-day biochemical oxygen demand of wastewater entering an anaerobic wastewater treatment process for week w(kg/m³), measured as specified in § 98.354(b) and (c).

§ 98.353

40 CFR Ch. I (7-1-14 Edition)

B_0 = Maximum CH_4 producing potential of wastewater (kg CH_4 /kg BOD_5), use the value 0.6.

MCF = CH_4 conversion factor, based on relevant values in Table II-1 to this subpart.

0.001 = Conversion factor from kg to metric tons.

(b) For each anaerobic reactor and anaerobic lagoon from which biogas is not recovered, estimate annual CH_4 emissions using Equation II-3 of this section.

$$CH_4E_n = CH_4G_n \quad (\text{Eq. II-3})$$

Where:

CH_4E_n = Annual mass of CH_4 emissions from the wastewater treatment process n from which biogas is not recovered (metric tons).

CH_4G_n = Annual mass of CH_4 generated from the wastewater treatment process n, as calculated in Equation II-1 or II-2 of this section (metric tons).

(c) For each anaerobic sludge digester, anaerobic reactor, or anaerobic lagoon from which some biogas is recovered, estimate the annual mass of CH_4 recovered according to the requirements in paragraphs (c)(1) and (c)(2) of

this section. To estimate the annual mass of CH_4 recovered, you must continuously monitor biogas flow rate and determine the volume of biogas each week and the cumulative volume of biogas each year that is collected and routed to a destruction device as specified in § 98.354(h). If the gas flow meter is not equipped with automatic correction for temperature, pressure, or, if necessary, moisture content, you must determine these parameters as specified in paragraph (c)(2)(ii) of this section.

(1) If you continuously monitor CH_4 concentration (and if necessary, temperature, pressure, and moisture content required as specified in § 98.354(f)) of the biogas that is collected and routed to a destruction device using a monitoring meter specifically for CH_4 gas, as specified in § 98.354(g), you must use this monitoring system and calculate the quantity of CH_4 recovered for destruction using Equation II-4 of this section. A fully integrated system that directly reports CH_4 quantity requires only the summing of results of all monitoring periods for a given year.

$$R_n = \sum_{m=1}^M \left[(V)_m * (K_{MC})_m * \frac{(C_{CH_4})_m}{100\%} * 0.0423 * \frac{520^\circ R}{(T)_m} * \frac{(P)_m}{1 \text{ atm}} * \frac{0.454}{1,000} \right] \quad (\text{Eq. II-4})$$

Where:

R_n = Annual quantity of CH_4 recovered from the nth anaerobic reactor, sludge digester, or lagoon (metric tons CH_4 /yr)

n = Index for processes at the facility, used in Equation II-7.

M = Total number of measurement periods in a year. Use M = 365 (M = 366 for leap years) for daily averaging of continuous monitoring, as provided in paragraph (c)(1) of this section. Use M = 52 for weekly sampling, as provided in paragraph (c)(2) of this section.

m = Index for measurement period.

$(V)_m$ = Cumulative volumetric flow for the measurement period in actual cubic feet (acf). If no biogas was recovered during a monitoring period, use zero.

$(K_{MC})_m$ = Moisture correction term for the measurement period, volumetric basis.

= 1 when $(V)_m$ and $(C_{CH_4})_m$ are measured on a dry basis or if both are measured on a wet basis.

= $1 - (f_{H_2O})_m$ when $(V)_m$ is measured on a wet basis and $(C_{CH_4})_m$ is measured on a dry basis.

= $1/[1 - (f_{H_2O})_m]$ when $(V)_m$ is measured on a dry basis and $(C_{CH_4})_m$ is measured on a wet basis.

$(f_{H_2O})_m$ = Average moisture content of biogas during the measurement period, volumetric basis, (cubic feet water per cubic feet biogas).

$(C_{CH_4})_m$ = Average CH_4 concentration of biogas during the measurement period, (volume %).

0.0423 = Density of CH_4 lb/cf at 520 °R or 60 °F and 1 atm.

520 °R = 520 degrees Rankine.

$(T)_m$ = Average temperature at which flow is measured for the measurement period (°R). If the flow rate meter automatically corrects for temperature to 520° R, replace "520° R/ $(T)_m$ " with "1".

$(P)_m$ = Average pressure at which flow is measured for the measurement period (atm).

Environmental Protection Agency

§ 98.353

If the flow rate meter automatically corrects for pressure to 1 atm, replace “P_m/1” with “1”.
 0.454/1,000 = Conversion factor (metric ton/lb).

(2) If you do not continuously monitor CH₄ concentration according to paragraph (c)(1) of this section, you must determine the CH₄ concentration, temperature, pressure, and, if necessary, moisture content of the biogas that is collected and routed to a destruction device according to the requirements in paragraphs (c)(2)(i) through (c)(2)(ii) of this section and calculate the quantity of CH₄ recovered for destruction using Equation II-4 of this section.

(i) Determine the CH₄ concentration in the biogas that is collected and routed to a destruction device in a location near or representative of the location of the gas flow meter at least once each calendar week; if only one measurement is made each calendar week, there must be at least three days between measurements. For a given calendar week, you are not required to determine CH₄ concentration if the cumulative volume of biogas for that calendar week, determined as specified in paragraph (c) of this section, is zero.

(ii) If the gas flow meter is not equipped with automatic correction for temperature, pressure, or, if necessary, moisture content:

(A) Determine the temperature and pressure in the biogas that is collected and routed to a destruction device in a location near or representative of the location of the gas flow meter at least once each calendar week; if only one measurement is made each calendar week, there must be at least three days between measurements.

(B) If the CH₄ concentration is determined on a dry basis and biogas flow is determined on a wet basis, or CH₄ concentration is determined on a wet basis

and biogas flow is determined on a dry basis, and the flow meter does not automatically correct for moisture content, determine the moisture content in the biogas that is collected and routed to a destruction device in a location near or representative of the location of the gas flow meter at least once each calendar week that the cumulative biogas flow measured as specified in §98.354(h) is greater than zero; if only one measurement is made each calendar week, there must be at least three days between measurements.

(d) For each anaerobic sludge digester, anaerobic reactor, or anaerobic lagoon from which some quantity of biogas is recovered, you must estimate both the annual mass of CH₄ that is generated, but not recovered, according to paragraph (d)(1) of this section and the annual mass of CH₄ emitted according to paragraph (d)(2) of this section.

(1) Estimate the annual mass of CH₄ that is generated, but not recovered, using Equation II-5 of this section.

$$CH_4L_n = R_n * \left(\frac{1}{CE} - 1 \right) \quad (\text{Eq. II-5})$$

Where:

CH₄L_n = Leakage at the anaerobic process n (metric tons CH₄).

n = Index for processes at the facility, used in Equation II-7.

R_n = Annual quantity of CH₄ recovered from the nth anaerobic reactor, anaerobic lagoon, or anaerobic sludge digester, as calculated in Equation II-4 of this section (metric tons CH₄).

CE = CH₄ collection efficiency of anaerobic process n, as specified in Table II-2 of this subpart (decimal).

(2) For each anaerobic sludge digester, anaerobic reactor, or anaerobic lagoon from which some quantity of biogas is recovered, estimate the annual mass of CH₄ emitted using Equation II-6 of this section.

$$CH_4E_n = CH_4L_n + R_n (1 - [(DE_1 * f_{Dest_1}) + (DE_2 * f_{Dest_2})]) \quad (\text{Eq. II-6})$$

Where:

CH₄E_n = Annual quantity of CH₄ emitted from the process n from which biogas is recovered (metric tons).

n = Index for processes at the facility, used in Equation II-7.

CH₄L_n = Leakage at the anaerobic process n, as calculated in Equation II-5 of this section (metric tons CH₄).

§ 98.354

40 CFR Ch. I (7–1–14 Edition)

R_n = Annual quantity of CH_4 recovered from the n th anaerobic reactor or anaerobic sludge digester, as calculated in Equation II-4 of this section (metric tons CH_4).

DE_1 = Primary destruction device CH_4 destruction efficiency (lesser of manufacturer's specified destruction efficiency and 0.99). If the biogas is transported off-site for destruction, use $DE = 1$.

f_{Dest-1} = Fraction of hours the primary destruction device was operating calculated as the annual hours when the destruction device was operating divided by the annual operating hours of the biogas recovery system. If the biogas is transported off-site for destruction, use $f_{Dest} = 1$.

DE_2 = Back-up destruction device CH_4 destruction efficiency (lesser of manufacturer's specified destruction efficiency and 0.99).

f_{Dest-2} = Fraction of hours the back-up destruction device was operating calculated as the annual hours when the destruction device was operating divided by the annual operating hours of the biogas recovery system.

(e) Estimate the total mass of CH_4 emitted from all anaerobic processes from which biogas is not recovered (calculated in Eq. II-3) and all anaerobic processes from which some biogas is recovered (calculated in Equation II-6) using Equation II-7 of this section.

$$CH_4E_T = \sum_{n=1}^j CH_4E_n \quad (\text{Eq. II-7})$$

Where:

CH_4E_T = Annual mass CH_4 emitted from all anaerobic processes at the facility (metric tons).

n = Index for processes at the facility.

CH_4E_n = Annual mass of CH_4 emissions from process n (metric tons).

j = Total number of processes from which methane is emitted.

[75 FR 39767, July 12, 2010, as amended at 76 FR 73903, Nov. 29, 2011; 78 FR 71972, Nov. 29, 2013]

§ 98.354 Monitoring and QA/QC requirements.

(a) For calendar year 2011 monitoring, the facility may submit a request to the Administrator to use one or more best available monitoring methods as listed in § 98.3(d)(1)(i) through (iv). The request must be submitted no later than October 12, 2010 and must contain the information in

§ 98.3(d)(2)(ii). To obtain approval, the request must demonstrate to the Administrator's satisfaction that it is not reasonably feasible to acquire, install, and operate a required piece of monitoring equipment by January 1, 2011. The use of best available monitoring methods will not be approved beyond December 31, 2011.

(b) You must determine the concentration of organic material in wastewater treated anaerobically using analytical methods for COD or BOD_5 specified in 40 CFR 136.3 Table 1B. For the purpose of determining concentrations of wastewater influent to the anaerobic wastewater treatment process, samples may be diluted to the concentration range of the approved method, but the calculated concentration of the undiluted wastewater must be used for calculations and reporting required by this subpart.

(c) You must collect samples representing wastewater influent to the anaerobic wastewater treatment process, following all preliminary and primary treatment steps (*e.g.*, after grit removal, primary clarification, oil-water separation, dissolved air flotation, or similar solids and oil separation processes). You must collect and analyze samples for COD or BOD_5 concentration at least once each calendar week that the anaerobic wastewater treatment process is operating; if only one measurement is made each calendar week, there must be at least three days between measurements. You must collect a sample that represents the average COD or BOD_5 concentration of the waste stream over a 24-hour sampling period. You must collect a minimum of four sample aliquots per 24-hour period and composite the aliquots for analysis. Collect a flow-proportional composite sample (either constant time interval between samples with sample volume proportional to stream flow, or constant sample volume with time interval between samples proportional to stream flow). Follow sampling procedures and techniques presented in Chapter 5, Sampling, of the "NPDES Compliance Inspection Manual," (incorporated by reference, *see* § 98.7) or Section 7.1.3, Sample Collection Methods, of the "U.S.