

**Environmental Protection Agency**

**§ 98.414**

**§ 98.411 Reporting threshold.**

Any supplier of industrial greenhouse gases who meets the requirements of § 98.2(a)(4) must report GHG emissions.

**§ 98.412 GHGs to report.**

You must report the GHG emissions that would result from the release of the nitrous oxide and each fluorinated GHG that you produce, import, export, transform, or destroy during the calendar year.

**§ 98.413 Calculating GHG emissions.**

(a) Calculate the total mass of each fluorinated GHG or nitrous oxide produced annually, except for amounts that are captured solely to be shipped off site for destruction, by using Equation OO-1 of this section:

$$P = \sum_{p=1}^n P_p \quad (\text{Eq. OO-1})$$

P = Mass of fluorinated GHG or nitrous oxide produced annually.

P<sub>p</sub> = Mass of fluorinated GHG or nitrous oxide produced over the period "p".

(b) Calculate the total mass of each fluorinated GHG or nitrous oxide produced over the period "p" by using Equation OO-2 of this section:

$$P_p = O_p - U_p \quad (\text{Eq. OO-2})$$

Where:

P<sub>p</sub> = Mass of fluorinated GHG or nitrous oxide produced over the period "p" (metric tons).

O<sub>p</sub> = Mass of fluorinated GHG or nitrous oxide that is measured coming out of the production process over the period p (metric tons).

U<sub>p</sub> = Mass of used fluorinated GHG or nitrous oxide that is added to the production process upstream of the output measurement over the period "p" (metric tons).

(c) Calculate the total mass of each fluorinated GHG or nitrous oxide transformed by using Equation OO-3 of this section:

$$T = F_T * E_T \quad (\text{Eq. OO-3})$$

Where:

T = Mass of fluorinated GHG or nitrous oxide transformed annually (metric tons).

F<sub>T</sub> = Mass of fluorinated GHG fed into the transformation process annually (metric tons).

E<sub>T</sub> = The fraction of the fluorinated GHG or nitrous oxide fed into the transformation process that is transformed in the process (metric tons).

(d) Calculate the total mass of each fluorinated GHG destroyed by using Equation OO-4 of this section:

$$D = F_D * DE \quad (\text{Eq. OO-4})$$

Where:

D = Mass of fluorinated GHG destroyed annually (metric tons).

F<sub>D</sub> = Mass of fluorinated GHG fed into the destruction device annually (metric tons).

DE = Destruction efficiency of the destruction device (fraction).

**§ 98.414 Monitoring and QA/QC requirements.**

(a) The mass of fluorinated GHGs or nitrous oxide coming out of the production process shall be measured using flowmeters, weigh scales, or a combination of volumetric and density measurements with an accuracy and precision of one percent of full scale or better. If the measured mass includes more than one fluorinated GHG, the concentrations of each of the fluorinated GHGs, other than low-concentration constituents, shall be measured as set forth in paragraph (n) of this section. For each fluorinated GHG, the mean of the concentrations of that fluorinated GHG (mass fraction) measured under paragraph (n) of this section shall be multiplied by the mass measurement to obtain the mass of that fluorinated GHG coming out of the production process.

(b) The mass of any used fluorinated GHGs or used nitrous oxide added back into the production process upstream of the output measurement in paragraph (a) of this section shall be measured using flowmeters, weigh scales, or a combination of volumetric and density measurements with an accuracy and precision of one percent of full scale or better. If the mass in paragraph (a) of this section is measured by weighing containers that include returned heels as well as newly produced fluorinated GHGs, the returned heels