§415.65

In cases when POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for Copper (T), Lead(T) and Nickel (T) are the same as specified in §415.62(b).

§415.65 New source performance standards (NSPS).

(a) Any new source subject to this subpart and using the mercury cell process must achieve the following new source performance standards (NSPS):

SUBPART	F-CHLOR-	Alkali-N	I ERCURY	Cells
---------	----------	----------	-----------------	-------

	NSPS lin	NSPS limitations		
Pollutant or pollutant property	Maximum for any 1 day Average o daily value for 30 con secutive day			
	Kq/kkg (or pounds per 1,000 lb) of product			
TSS	0.64	0.32		
Mercury (T)	0.00023	0.00010		
Total Residual Chlorine	0.0032	0.0019		
pH	(1)	(1)		

¹ Within the range 6.0 to 9.0.

(b) Any new source subject to this subpart and using the diaphragm cell process must achieve the following new source performance standards (NSPS):

SUBPART F-CHLOR-ALKALI-DIAPHRAGM CELLS

	NSPS limitations		
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Kq/kkg (or pounds per 1,000 lb) of product		
TSS Lead (T)	1.1 0.0047	0.51 0.0019	
Total Residual Chlorine pH	0.013 (¹)	0.0079 (¹)	

¹ Within the range 6.0 to 9.0.

§415.66 Pretreatment standards for new sources (PSNS).

(a) Except as provided in 40 CFR 403.7, any new source subject to this subpart and using the mercury cell process, which introduces pollutants into a publicly owned treatment works, must comply with 40 CFR part 403 and achieve the following Pretreatment Standards for New Sources (PSNS):

40 CFR Ch. I (7-1-12 Edition)

SUBPART F-CHLOR-ALKALI-MERCURY CELLS

	PSNS effluent limita- tions		
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days	
	Milligrams per liter		
Mercury (T)	0.11	0.048	

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for mercury (T) are the same as specified in §415.65(a).

(b) Except as provided in 40 CFR 403.7, any new source subject to this subpart and using the diaphragm cell process, which introduces pollutants into a publicly owned treatment works, must compy with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS):

SUBPART F-DIAPHRAGM CELLS

	PSNS effluent limitations		
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Milligrams per liter (mg/1)		
Lead(T)	0.53	0.21	

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for Lead(T) are the same as specified in §415.65(b).

[47 FR 28278, June 29, 1982, as amended at 47 FR 55226, Dec. 8, 1982]

§415.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and using the mercury cell process must