

§ 428.22

methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

[39 FR 6662, Feb. 21, 1974, as amended at 40 FR 18173, Apr. 25, 1975]

§ 428.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kg/kg of product) | |
| COD | 12.00 | 8.00 |
| BOD ₅ | 0.60 | .40 |
| TSS | 0.98 | .65 |
| Oil and grease | 0.24 | .16 |
| pH | (¹) | (¹) |
| | English units (lb/1,000 lb of product) | |
| | | |
| | | |
| COD | 12.00 | 8.00 |
| BOD ₅ | 0.60 | .40 |
| TSS | 0.98 | .65 |
| Oil and grease | 0.24 | .16 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

[39 FR 6662, Feb. 21, 1974, as amended at 60 FR 33963, June 29, 1995]

§ 428.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

40 CFR Ch. I (7–1–14 Edition)

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kg/kg of product) | |
| COD | 3.12 | 2.08 |
| BOD ₅ | 0.12 | .08 |
| TSS | 0.24 | .16 |
| Oil and grease | 0.12 | .08 |
| pH | (¹) | (¹) |
| | English units (lb/1,000 lb of product) | |
| | | |
| | | |
| COD | 3.12 | 2.08 |
| BOD ₅ | 0.12 | .08 |
| TSS | 0.24 | .16 |
| Oil and grease | 0.12 | .08 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

§ 428.24 [Reserved]

§ 428.25 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: The limitations shall be as specified in § 428.22.

Subpart C—Solution Crumb Rubber Subcategory

§ 428.30 Applicability; description of the solution crumb rubber subcategory.

The provisions of this subpart are applicable to discharges of pollutants resulting from the manufacture of crumb rubber.

§ 428.31 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

[39 FR 6662, Feb. 21, 1974, as amended at 40 FR 18173, Apr. 25, 1975]