

**Environmental Protection Agency**

**§ 429.90**

**§ 429.81 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

**SUBPART G**

Pollutant or pollutant property	BPT Effluent Limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	English units (lb/1000 cubic feet of product)	
COD .....	68.5	34.5
Phenols .....	.14	.04
Oil and Grease .....	1.5	.75
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	Metric units (kg/1000 cu m of product)	
COD .....	1,100	550
Phenols .....	2.18	.65
Oil and Grease .....	24.0	12.0
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0 at all times.

**§ 429.82 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]**

**§ 429.83 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT). [Reserved]**

**§ 429.84 New source performance standards (NSPS).**

Any new source subject to this subpart must achieve the following new source performance standards (NSPS): There shall be no discharge of process wastewater pollutants into navigable waters.

**§ 429.85 Pretreatment standards for existing sources (PSES).**

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and meet the following pretreatment standards for existing sources (PSES):

**SUBPART G  
[PSES Effluent Limitations]**

Pollutant or pollutant property	Maximum for any 1 day (mg/l)
Oil and grease .....	100
Copper .....	5
Chromium .....	4
Arsenic .....	4

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as guidance.

[Grams per cubic meter of production]

Pollutant or pollutant property	Maximum for any 1 day
Oil and grease .....	20.5
Copper .....	.62
Chromium .....	.41
Arsenic .....	.41

**§ 429.86 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): There shall be no introduction of process wastewater pollutants into publicly owned treatment works.

**Subpart H—Wood Preserving—Boulton Subcategory**

**§ 429.90 Applicability; description of the wood preserving—Boulton subcategory.**

This subpart applies to discharges to waters of the United States and to the