Environmental Protection Agency

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of sawed or ground nickel-cobalt rinsed	
Chromium	0.067 0.100 10.8	0.027 0.067 4.78

(aa) Steam cleaning condensate.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of nickel-cobalt steam cleaned	
Chromium	0.011 0.017 1.79	0.005 0.011 0.795

(bb) Hydrostatic tube testing and ultrasonic testing wastewater—subpart C—PSNS. There shall be no allowance discharge of process wastewater pollutants.

(cc) Degreasing spent solvents—subpart C—PSNS. There shall be no discharge of process wastewater pollutants.

(dd) Dye penetrant testing wastewater.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of nickel-cobalt tested with dye penetrant method	
Chromium	0.079 0.117 12.7	0.032 0.079 5.63

(ee) Electrocoating rinse.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of nickel-cobalt electrocoated	
Chromium	1.25 1.86 201	0.506 0.125 89.0

(ff) Miscellaneous wastewater sources.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of nickel-cobal formed	
Chromium Nickel Fluoride	0.091 0.136 14.7	0.037 0.091 6.50

[50 FR 34270, Aug. 23, 1985; 51 FR 2886, Jan. 22, 1986, as amended at 54 FR 11350, Mar. 17, 1989]

§ 471.36 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

Subpart D—Precious Metals Forming Subcategory

§ 471.40 Applicability; description of the precious metals forming subcategory.

This subpart applies to discharges of pollutants to waters of the United States, and introductions of pollutants into publicly owned treatment works from the process operations of the precious metals forming subcategory.

§ 471.41 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

- (a) Rolling spent neat oils—subpart D—BPT. There shall be no discharge of process wastewater pollutants.
 - (b) Rolling spent emulsions.

40 CFR Ch. I (7-1-14 Edition)

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	off-pounds)	nds per million of precious d with emul-
Chromium	0.026	0.012
Copper	0.147	0.077
Cyanide	0.023	0.010
Silver	0.032	0.013
Oil and grease	1.54	0.925
TSS	3.16	1.51
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

- (c) Drawing spent neat oils—subpart D—BPT. There shall be no discharge of process wastewater pollutants.
 - (d) Drawing spent emulsions.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		nds per million of precious vn with emul-
Cadmium	0.016	0.007
Copper	0.091	0.048
Cyanide	0.014	0.006
Silver	0.020	0.008
Oil and grease	0.950	0.570
TSS	1.95	0.926
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(e) Drawing spent soap solutions.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly aver-
	,,	age
	mg/off-kg (pounds per milli off-pounds) of precio metals drawn with soap s lutions	
Cadmium	0.001	0.0005
Copper	0.006	0.003
Cyanide	0.0009	0.0004
Silver	0.001	0.0006
Oil and grease	0.063	0.038
TSS	0.128	0.061
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(f) Metal powder production wet atomization wastewater.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of precion metals powder wet ator ized	
Cadmium	2.27	1.00
Copper	12.7	6.70
Cyanide	1.94	0.802
Silver	2.70	1.14
Oil and grease	134	80.2
TSS	274	130
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

 $\begin{array}{cccc} \hbox{(g)} & \textit{Heat} & \textit{treatment} & \textit{contact} & \textit{cooling} \\ \textit{water.} \end{array}$

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	off-pounds)	nds per million of extruded tals heat treat-
Cadmium	1.42	0.626
Copper	7.93	4.17
Cyanide	1.21	0.501
Silver	1.71	0.709
Oil and grease	83.4	50.1
TSS	171	81.3
pH	(1)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(h) Semi-continuous or continuous casting contact cooling water.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	off-pounds) metals cast	nds per million of precious by the semi- or continuous
Cadmium	3.50	1.55
Copper	19.6	10.3
Cyanide	2.99	1.24
Silver	4.23	1.75
Oil and grease	206	124
TSS	423	209
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

- (i) Stationary casting contact cooling water—subpart D—BPT. There shall be no discharge of process wastewater pollutants.
- (j) Direct chill casting contact cooling water.

Environmental Protection Agency

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	off-pounds)	nds per million of precious by the direct
Cadmium	3.67	1.62
Copper	20.5	10.8
Cyanide	3.13	1.30
Silver	4.43	1.84
Oil and grease	216	130
TSS	443	211
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(k) Shot casting contact cooling water.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals shot cast	
Cadmium	1.25 6.98	0.551 3.67
Copper Cyanide	1.07	0.441
Silver	1.51	0.624
Oil and grease	73.4	44.1
TSS	151	71.6
pH	(1)	(1)

 $^{^{\}rm 1}\,\mbox{Within}$ the range of 7.5 to 10.0 at all times.

(1) Wet air pollution control scrubber blowdown—subpart D—BPT. There shall be no discharge of process wastewater pollutants.

 $\begin{tabular}{ll} (m) & Pressure & bonding & contact & cooling \\ water. \end{tabular}$

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals and base meta pressure bonded	
Cadmium	0.029	0.013
Copper	0.159	0.084
Cyanide	0.024	0.010
Silver	0.034	0.014
Oil and grease	1.67	1.00
TSS	3.43	1.63
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals surface treated	
Cadmium	0.033	0.015
Copper	0.183	0.097
Cyanide	0.028	0.012
Silver	0.040	0.017
Oil and grease	1.93	1.16
TSS	3.95	1.88
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(o) Surface treatment rinse.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals surface treated	
Cadmium	2.10	0.924
Copper	11.7	5.16
Cyanide	1.79	0.739
Silver	2.53	1.05
Oil and grease	123	73.9
TSS	253	120
pH	(1)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

 $(p) \ \textit{Alkaline cleaning spent baths}.$

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day Maximum for monthly average	
	mg/off-kg (pounds per mil- lion off-pounds) of pre- cious metals alkaline cleaned	
Cadmium	0.021 0.114	0.009
Cyanide	0.018	0.007
Silver	0.025	0.010
Oil and grease	1.20	0.720
TSS	2.46	1.170
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(q) Alkaline cleaning rinse.

⁽n) Surface treatment spent baths.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals alkaline cleaned	
Codesium	0.01	1.00
Cadmium	3.81	1.68
Copper	21.3	11.2
Cyanide	3.25	1.35
Silver	4.59	1.91
Oil and grease	224	135
TSS	459	219
pH	(¹)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

 (\mathbf{r}) Alkaline cleaning prebonding wastewater.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals and base meta cleaned prior to bonding	
Cadmium	3.95	1.74
Copper	22.1	11.6
Cyanide	3.37	1.39
Silver	4.76	1.97
Oil and grease	232	139
TSS	476	226
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(s) Tumbling or burnishing wastewater.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals tumbled or bur- nished	
Cadmium	4.12	1.82
Copper	23.0	12.1
Cyanide	3.51	1.45
Silver	4.96	2.06
Oil and grease	242	145
TSS	496	236
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals sawed or ground with emulsions	
Cadmium	0.032	0.014
Copper	0.178	0.094
Cyanide	0.027	0.011
Silver	0.039	0.016
Oil and grease	1.87	1.12
TSS	3.83	1.82
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(v) Degreasing spent solvents—subpart D—BPT. There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2886, Jan. 22, 1986]

§ 471.42 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

- (a) Rolling spent neat oils—subpart D—BAT. There shall be no discharge of wastewater pollutants.
 - $\hbox{(b) $Rolling spent emulsions.}$

SUBPART D-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (po lion off-po cious meta emulsions	
Cadmium	0.026	0.012
Copper	0.147	0.077
Cyanide	0.023	0.010
Silver	0.032	0.013

- (c) Drawing spent neat oils—subpart D—BAT. There shall be no discharge of process wastewater pollutants.
 - (d) Drawing spent emulsions.

⁽t) Sawing or grinding spent neat oils—subpart D—BPT. There shall be no discharge of process wastewater pollutants.

⁽u) Sawing or grinding spent emulsions.