

§ 32.65-5

§ 32.65-5 Scantlings, material, and workmanship—TB/ALL.

The hull and deck houses shall be of steel or iron construction except that the pilothouse and decks over quarters may be constructed of wood. Scantlings, material, and workmanship, subdivision of cargo spaces, fitting of cofferdams, and testing of tanks shall be at least equivalent to the requirements of the American Bureau of Shipping or other recognized classification society.

§ 32.65-10 Subdivision of cargo space—TB/ALL.

The cargo space shall be divided into tight compartments as necessary to avoid excessive stresses and to provide stability.

§ 32.65-15 Cofferdams—TB/ALL.

Tank vessels equipped to carry Grade A, B, C, or D liquids shall have their galleys, living quarters, general cargo spaces, boiler rooms, and enclosed spaces containing propelling machinery or other machinery where sources of vapor ignition are normally present, segregated from their cargo tanks by cofferdams or equivalent pumprooms, tanks, or air spaces.

§ 32.65-20 Pumprooms—TB/ALL.

(a) Tank vessels handling Grade A, B, C, or D liquids shall have their cargo pumps isolated from all sources of vapor ignition by gastight bulkheads. Totally enclosed motors of the “explosion proof” type, motors ventilated on both the intake and exhaust by ducts to atmosphere, and engines driven by steam shall not be considered to be sources of vapor ignition. The gastight bulkhead between the pumproom and the pump-engine compartment may be pierced by fixed lights, drive shaft and pump-engine control rods, provided that the shafts and rods are fitted with stuffing boxes where they pass through the gastight bulkheads. The access to a cargo pumproom handling such liquids shall be from the open deck. (See § 32.60-20.0.)

§ 32.65-25 Living quarters—TB/ALL.

Partitions and sheathing shall be of approved fire-resistive construction.

46 CFR Ch. I (10-1-14 Edition)

§ 32.65-30 Tank vessels with independent tanks—TB/ALL.

Independent cargo tanks may be located in hold spaces or in other cargo tanks but in all cases a working space of at least 15 inches shall be provided around such independent tanks, or else provisions shall be made for moving them to secure such space. When independent cargo tanks are located in an enclosed space other than a cargo tank, such enclosed space shall be considered as equivalent to a pumproom, and shall be safeguarded as such, as required in the regulations in this subchapter.

§ 32.65-35 Tank vessels carrying Grade A liquids—TB/ALL.

Cargo tanks for Grade A liquids having a Reid vapor pressure in excess of 25 pounds shall be independent of the hull.

§ 32.65-40 Construction and testing of cargo tanks and bulkheads—TB/ALL.

(a) All cargo tanks to be vented at gage pressures of 4 pounds per square inch or less shall be constructed and tested as required by the requirements of the American Bureau of Shipping or other recognized classification society.

(b) All cargo tanks to be vented at gage pressures above 4 pounds per square inch shall be considered as pressure vessels and shall meet the requirements for such vessels as to construction and testing, as set forth in subchapter F (Marine Engineering) of this chapter.

(c) Gastight bulkheads shall be subjected to a thorough hose test.

[CGFR 65-50, 30 FR 16671, Dec. 30, 1965, as amended by CGFR 68-82, 33 FR 18805, Dec. 18, 1968]

Subpart 32.70—Hull Requirements for Steel Hull Tank Vessels Constructed Prior to November 10, 1936

§ 32.70-1 Application—TB/ALL.

All steel hull tank vessels, the construction or conversion of which was started prior to November 10, 1936, shall conform to the requirements in this subpart.