

§ 38.20-5

that the back pressure in the relief valve discharge lines shall not be more than 10 percent of the safety relief valve setting. In nonpressure vessel vent systems, however, where the maximum back pressure of 10 percent of the relief valve setting is insufficient to move the gases through any but an extremely large diameter vent pipe, the back pressure may exceed 10 percent provided:

(1) The pressure in the tank during venting does not exceed 120 percent of the tank maximum allowable pressure; and,

(2) The safety relief valve is sized to discharge the required capacity with the tank pressure and vent back pressure actually used.

(d) Return bends and restrictive pipe fittings are not permitted.

(e) Vents and headers shall be so installed as to prevent excessive stresses on safety relief valve mountings.

(f) The vent discharge riser shall be so located as to provide protection against mechanical injury and such discharge pipes shall be fitted with loose raincaps or other suitable means to prevent entrance of rain or snow.

(g) No valve of any type shall be fitted in the vent pipe between the safety relief valve and the vent outlets.

(h) Provisions shall be made to drain condensate from the vent header piping. Special precautions shall insure that condensate does not accumulate at or near the relief valves.

(i) Relief valves discharging liquid cargo shall not be connected to the branch vent or vent header lines from the cargo tanks. They may, however, be connected to an accumulator, the vapor space of which, may in turn, be connected to the vent header system. Relief valves in the cargo piping system may discharge back to the cargo tanks.

(j) Vapor discharged to the atmosphere in accordance with §38.05-25(b) shall utilize valves separate from the safety relief valves.

§ 38.20-5 Venting—T/ALL.

(a) Safety relief valves on cargo tanks in barges may be connected to individual or common risers which shall extend to a reasonable height above the deck. An alternate arrange-

46 CFR Ch. I (10-1-14 Edition)

ment consisting of a branch vent header system as required by §38.20-1 may be installed. In any case, the provisions of §38.20-1 (d) through (j) shall apply.

(b) Arrangements providing for venting cargo tanks at sea on unmanned barges will be considered by the Commandant upon presentation of plans.

§ 38.20-10 Ventilation—T/ALL.

(a) A power ventilation system shall be provided for compartments containing pumps, compressors, pipes, control spaces, etc. connected with the cargo handling facilities. These compartments shall be ventilated in such a way as to remove vapors from points near the floor level or bilges, or other areas where vapor concentrations may be expected. The compartments shall be equipped with power ventilation of the exhaust type having capacity sufficient to effect a complete change of air in not more than 3 minutes equal to the volume of the compartment and associated trunks.

(b) The power ventilation units shall not produce a source of vapor ignition in either the compartment or the ventilation system associated with the compartment. Inlets to exhaust ducts shall be provided and located at points where concentrations of vapors may be expected. Ventilation from the weather deck shall be provided. Ventilation outlets shall terminate away from any openings to the interior part of the vessel a lateral distance at least equal to that specified in §38.20-1(a). These outlets shall be so located as to minimize the possibility of recirculating contaminated air through the compartment.

(c) Means shall be provided for purging the following spaces of cargo vapors:

(1) The space surrounding nonpressure vessel type tanks, i.e., within the secondary barrier.

(2) The space surrounding pressure-vessel type tanks whose piping connections are below the weather deck in accordance with §38.10-1(h).

(3) The space surrounding tanks whose manhole openings are below the weather deck in accordance with §38.05-10(f).

(d) Power ventilation shall be provided for each auxiliary machinery or

working space located on and accessible from the cargo handling deck. Such ventilation systems shall be designed to preclude the entry of cargo vapors into the space via the open access or the ventilation system itself.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGFR 68-65, 33 FR 19985, Dec. 28, 1968]

Subpart 38.25—Periodic Tests and Inspections

§ 38.25-1 Tests and inspections—TB/ALL.

(a) Each tank shall be subjected to the tests and inspections described in this section in the presence of a marine inspector, except as otherwise provided in this part.

(1) An internal inspection of the tank is conducted within—

(i) Ten years after the last internal inspection if the tank is a pressure vessel type cargo tank on an unmanned barge carrying cargo at temperatures of -67°F (-55°C) or warmer; or

(ii) Eight years after the last internal inspection if the tank is of a type other than that described in paragraph (a)(1)(i) of this section.

(2) An external examination of unlagged tanks and the visible parts of lagged tanks shall be made at each inspection for certification and at such other times as considered necessary.

(3) The owner shall ensure that the amount of insulation deemed necessary by the marine inspector is removed from insulated tanks during each internal inspection to allow spot external examination of the tanks and insulation, or the thickness of the tanks may be gauged by a nondestructive means accepted by the marine inspector without the removal of insulation.

(4) If required by the Officer in Charge, Marine Inspection, the owner shall conduct nondestructive testing of each tank in accordance with § 38.25-3.

(5) If the tank is a pressure vessel type cargo tank with an internal inspection interval of 10 years, is 30 years old or older, determined from the date it was built, the owner shall conduct nondestructive testing of that tank, in accordance with § 38.25-3, during each internal inspection.

(b) If the marine inspector considers a hydrostatic test necessary to determine the condition of the tank, the owner shall perform the test at a pressure of $1\frac{1}{2}$ times the tank's—

(1) Maximum allowable pressure, as determined by the safety relief valve setting; or

(2) Design pressure, when cargo tanks operate at maximum allowable pressures reduced below the design pressure in order to satisfy special mechanical stress relief requirements.

NOTE: See the ASME Code, section VIII, appendix 3 for information on design pressure.

(c) For pressure vessels designed and/or supported such that they cannot safely be filled with water, the Commandant will consider a pneumatic test in lieu of the hydrostatic test. A leak test shall be performed in conjunction with the pneumatic test. Pneumatic testing shall be in accordance with subchapter F (Marine Engineering) of this chapter.

(d) Nonpressure vessel type tanks shall be tested to a pressure equal to the pressure on the bottom of the tank under the design conditions listed in § 38.05-4(e).

(e) In the application of the requirements for testing of the cargo tanks, the test shall in no case be less severe than the worst anticipated service condition of the cargo loading.

(f) In the design and testing of the independent cargo tanks, consideration shall be given to the possibility of the independent tanks being subjected to external loads.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGD 85-061, 54 FR 50962, Dec. 11, 1989; USCG-2014-0688, 79 FR 58280, Sept. 29, 2014]

§ 38.25-3 Nondestructive testing—TB/ALL.

(a) Before nondestructive testing may be conducted to meet § 38.25-1 (a)(4) and (a)(5), the owner shall submit a proposal to the Officer in Charge, Marine Inspection for acceptance that includes—

(1) The test methods and procedures to be used, all of which must meet section V of the ASME Boiler and Pressure Vessel Code (1986);