

§ 131.420 Manning and supervision.

(a) There must be enough trained persons aboard each survival craft to muster and assist untrained persons.

(b) Except as permitted by paragraph (c)(2) of this section, there must be enough deck officers, able seamen, or other certificated persons aboard each survival craft to manage the launching and handling of the survival craft.

(c) One person must be placed in charge of each survival craft to be used.

(1) Except as permitted by paragraph (c)(2) of this section, the person in command must be a deck officer, able seaman, or other certificated person.

(2) Considering the nature of the voyage, the number of persons permitted aboard, and the characteristics of the vessel, including gross tonnage, the cognizant OCMI may permit persons practiced in the handling of liferafts to be placed in charge of liferafts instead of persons required under paragraph (c)(1) of this section.

(3) A deck officer, able seaman, or other certificated person shall serve as second-in-command for each lifeboat either—

(i) Carried on a vessel in ocean service; or

(ii) Permitted to carry more than 40 persons.

(d) The person in charge and the second-in-command of each survival craft shall have a list of crew members and offshore workers assigned to the craft and shall see that the crew members are acquainted with their duties.

(e) Each motorized survival craft must have assigned a person capable of operating the engine and carrying out minor adjustments.

(f) The master shall ensure that the persons required under paragraphs (a), (b), and (c) of this section are equitably distributed among the vessel's survival crafts.

Subpart E—Tests, Drills, and Inspections

§ 131.505 Steering gear, whistle, and means of communication.

(a) On each vessel expected to be away from shore for more than 48 hours, the master shall examine and test the steering gear, the whistle, and

the means of communication between the pilothouse and the engine room 12 or fewer hours before departure. On every other vessel, the master shall do the same at least once a week.

(b) The date of each test and examination and the condition of the equipment must be noted in the vessel's logbook.

§ 131.510 Draft and loadline markings.

(a) The master of each vessel on an ocean or coastwise voyage shall enter in the vessel's logbook the drafts of the vessel, forward and aft, when leaving port.

(b) The master of each vessel subject to the requirements of subchapter E of this chapter shall, upon departure from port on an ocean or coastwise voyage, enter in the vessel's logbook a statement of the position of the loadline markings, port and starboard, relative to the surface of the water in which the vessel is then floating.

(c) If the master, when recording drafts, compensates for the density of the water in which the vessel is floating, he or she shall note this density in the vessel's logbook.

§ 131.513 Verification of compliance with applicable stability requirements.

(a) After loading but before departure, and at other times necessary to assure the safety of the vessel, the master shall verify that the vessel complies with requirements in its trim-and-stability book, stability letter, Certificate of Inspection, and Loadline Certificate, whichever apply, and then enter a statement of the verification in the log book. The vessel may not leave port until it is in compliance with these requirements.

(b) When determining compliance with applicable stability requirements, the master shall ascertain the vessel's draft, trim, and stability as necessary; and any stability calculations made in support of the determination must remain aboard the vessel for the duration of the voyage.

§ 131.515 Periodic sanitary inspections.

(a) The master shall make periodic inspections of the quarters, toilet and