

TABLE 133.175—SURVIVAL CRAFT EQUIPMENT—Continued

Item No.	Item	Oceans		Coastwise	
		Rigid life-raft (SOLAS A Pack)	Rescue boat	Rigid life-raft (SOLAS B Pack)	Rescue boat
20	Oars, units ⁴		1		1
	Paddles	2		2	
21	Painter	1	1	1	1
22	Provisions (units per person)	1			
23	Pump ⁵		1		1
24	Radar reflector	1		1	1
26	Repair kit ⁵		1		1
27	Sea anchor	2		2	1
28	Searchlight		1		1
29	Seasickness kit (units per person)	1		1	
30	Signal, smoke	2		1	
31	Signal, hand flare	6		6	
32	Signal, parachute flare	4		4	
34	Sponge ⁵	2	2	2	2
35	Survival instructions	1		1	
36	Table of lifesaving signals	1		1	
37	Thermal protective aids (percent of persons) ⁶	10%	10%	10%	10%
39	Towline		1		1
40	Water (liters per person)	1.5		1	
41	Whistle	1	1	1	1

Notes:
¹ Each liferaft equipped for 13 persons or more must carry two of these items.
² Not required for inflated or rigid-inflated rescue boats.
³ A hatchet counts towards this requirement in rigid rescue boats.
⁴ Oars are not required on a free-fall lifeboat; a unit of oars means the number of oars specified by the boat manufacturer.
⁵ Not required for a rigid rescue boat.
⁶ Sufficient thermal protective aids are required for at least 10% of the persons the survival craft is equipped to carry, but not less than two.

[CGD 84–069, 61 FR 25304, May 20, 1996, as amended by USCG–1999–6216, 64 FR 53227, Oct. 1, 1999]

PART 134—ADDED PROVISIONS FOR LIFTBOATS

- Sec.
- 134.100 Applicability.
- 134.110 Initial inspection.
- 134.120 Inspection for certification.
- 134.130 New construction.
- 134.140 Structural standards.
- 134.150 Liftboat-jacking systems.
- 134.160 Freeboard markings.
- 134.170 Operating manual.
- 134.180 Piping for fire-main suction.

AUTHORITY: 46 U.S.C. 3306, 3307; Department of Homeland Security Delegation No. 0170.1. Section 134.100 also issued under sec. 617, Pub. L. 111–281, 124 Stat. 2905.

SOURCE: CGD 82–004 and CGD 86–074, 62 FR 49352, Sept. 19, 1997, unless otherwise noted.

§ 134.100 Applicability.

(a) This part, as well as parts 125 through 133 of this subchapter, applies to each liftboat of United States flag to which this subchapter applies.
 (b) The design, construction and operating standards for liftboats of at least 6,000 GT ITC (500 GRT if GT ITC

is not assigned) must be specially approved by Commandant (CG–5PS).

[USCG–2012–0208, 79 FR 48938, Aug. 18, 2014]

§ 134.110 Initial inspection.

Liftboat jacking systems, liftboat legs, liftboat leg pads, and arrangements for supply of water to fire mains, as well as the items listed by §126.340 of this subchapter, will normally be inspected during the initial inspection to determine whether the liftboat was built in compliance with developed plans and meets applicable regulations.

§ 134.120 Inspection for certification.

Liftboat jacking systems, liftboat legs, liftboat leg pads, and arrangements for supply of water to fire mains, as well as the items listed by §126.430 of this subchapter, will normally be inspected during an inspection for certification and periodic inspection to determine whether the